

M5900 Series



Batch Data Terminal



Big business performance. Small business value.

With big business functionality at a small business price, the AML M5900 portable data terminal can help streamline and improve your business operations, while keeping IT costs low – no matter the size of your business.

Durable, easy to use, and packed with big business functionality, the AML M5900 portable data terminal is an ideal solution for everyday, all day data collection applications – including inventory control, factory floor management, price verification, shipping/receiving, asset tracking and more.



The AML M5900 portable terminal helps **business do more, for less.**



Applications

- Inventory
- Stock Control
- Shipping/
- Factory Floor
- Price Verification
- Asset Tracking
- Receiving

Features

Durable, ergonomic design

Graphical 160 x 160 backlit LCD display

High performance 200 MHz ARM9 Processor

SQLite database engine

Rechargeable, high capacity 2600 mAh Lithium-Ion battery

55-key alphanumeric or 35-key numeric keypad

On-board Program Generator (OPG)

Preloaded with six common data collection applications

PC-based M5900 Program Generator

Multiple integrated scan engine options, including 2D Imager

RS232 and USB ports

Benefits

Built for everyday, all day use.

Easy to read, even in dimly lit environments. Accommodates 20 lines x 20 characters of text.

Rapid access to large look-up tables or stored data.

Powerful handling of data files.

Much longer life than conventional batteries. Ensures extended periods of operation w/o interruption.

Multi-functional keypad options support most data collection applications.

Create simple applications, right on the M5900, from the Run Program Menu.

Easily scan bar codes and collect basic data.

Quickly and efficiently create custom applications for the M5900.

Choose the most appropriate bar code scanner for your specific data collection application.

Simple and easy data upload.

General Specs

| | |
|---|---|
| Dimensions | 225 mm L x 89 mm W x 57 mm D; 8.875" L x 3.5" W x 2.25" D |
| Weight | 16 oz / 454 g (M5900); 25 oz / 709 g (M5900i) |
| Drop Specifications | 4 ft. (1.2m) drop to concrete (M5900); 5 ft. (1.5m) drop to concrete (M5900i); |
| Display | Graphical 160 x 160 backlit EL LCD; 20 lines x 20 characters |
| Battery | Rechargeable 2600 mAh Lithium-Ion |
| Backup Battery | Rechargeable lithium protects RAM and real-time clock |
| Keypad | 55-key alphanumeric or 35-key numeric keypad |
| Integrated Barcode Scanners (optional) | Short-Range Laser; Standard Laser; Long-Range Laser; Advanced Long Range Laser; 2D Imager |

Performance Specs

| | |
|----------------------------|---|
| CPU | 32 bit, 200 MHz ARM9 Processor |
| Operating System | Open source, embedded Linux® |
| Memory | 32MB DRAM, 16MB Flash ROM; 10MB available for user programs and data files |
| Data Communications | Serial RS232 (RJ-45) supported by M5910 Terminal Charger / Serial Adapter; USB (Type II) |

Environmental Specs

| | |
|--------------------------------------|--------------------------------------|
| Operating Temp | -10° to 50° C / 14° to 122° F |
| Storage Temp | -25° to 50° C / -13° to 122° F |
| Humidity | 5% to 90% RH, non-condensing |
| Electrostatic Discharge (EDS) | 15kVDC through air; 4kVDC contact |
| Sealing | IP51 (dust, drip water proof) |

M5900i Industrial Configuration



The M5900i features a forward-scanning pistol grip handle and protective boot. Enhanced 5 ft. (1.5m) drop rating to concrete.



Software Specs

| | |
|--------------|--|
| Tools | Preloaded with six everyday data collection applications. Includes an On-board Program Generator (OPG). Supports programs generated with the AML M5900 PC-based Program Generator. Tool chain available to developers upon request. |
|--------------|--|

Peripherals & Accessories (optional)

| | |
|-----------------|--|
| Chargers | In-line terminal charger; Terminal charger (single slot charging & communications); Modem terminal charger; 4-Position terminal charger; 4-Position battery charger; Vehicle mount charger |
|-----------------|--|

| | |
|----------------|-------------------|
| Holster | Holster with belt |
|----------------|-------------------|



Terminal Charger



4-Position
Terminal Charger



In-line Terminal
Charger

Regulatory Specs

| | |
|-----------------------|----------------------------|
| Certifications | FCC Part 15 Class A |
| Laser Safety | CDRH Class II, IEC Class 2 |



Maintenance & Support

| | |
|--------------------------|--|
| Standard Warranty | One year standard warranty agreement |
| Optional | Extended Warranty Plus (3 years); Extended Warranty (3 years); CARE Plan Extended Warranty (3 years) |

Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries. Specifications are subject to change without notice. All names and products are the trademarks or registered trademarks of their respective organizations.



Corporate Headquarters
2190 Regal Parkway
Euless, Texas 76040

Sales & Customer Service
Tel: 800-648-4452
Fax: 817-685-6232
Email: sales@amitd.com

www.amitd.com
www.amlkiosks.com
Local: 817-571-9015
Fax: 817-571-6176

Technical Support
Tel: 877-842-3990
Fax: 817-685-6232
Email: support@amitd.com



© 2011 American Microsystems, Ltd.