M7100

Wireless Hand-Held Terminal

Powerful performance for mobile data collection applications

The AML M7100 Wireless Hand-Held Terminal is redefining the standard for wireless data collection technology. Incorporating the best of today's wireless technology, with the reliable performance of open source, embedded Linux®, the M7100 maximizes flexibility, performance, and value in mobile data collection computing. Built tough and optimized for cost-effectiveness, the M7100 is an ideal solution for real-time, information-intensive applications in retail, distribution, warehousing, manufacturing, and health care.

User friendly functionality

The M7100 is richly configured with advanced features to optimize operational efficiency and productivity – ensuring the rapid, timely processing of mission critical data, even in the most demanding applications. Powered by the fast Intel® StrongARM® processor, the M7100 is equipped with 16MB of built-in RAM and 4MB Flash ROM for ample storage capacity. Its internal radio supports IEEE 802.11b wireless local area network (WLAN) connectivity for real-time, high-rate data transfer between wireless operators and host applications (optional wireless wide area network GSM/GPRS connectivity for route accounting, delivery, and other field service applications). Extended operation is ensured by the M7100's enhanced power management, which supports eight-hour work shifts without recharging.

The M7100 integrates into a wide range of computing environments and supports AML's Windows® compatible CommandLink[™] wireless application design software and C++. VT100/VT220 terminal emulation is standard on the M7100, with options available for 3270 and 5250 terminal emulation. The M7100's computing flexibility simplifies the application development process, making the terminal quick and easy to implement –maximizing your return on investment.

Designed for maximum flexibility

Rugged but ergonomic, the M7100 provides comfort and ease of use in scan-intensive applications. The M7100 sports a lightweight, contoured design for comfortable, one-handed operation over extended periods of use. The graphical 160 x 160 backlit LCD with multi-font capability is easy to read, even in dimly lit environments. The spacious LCD screen supports the display of large amounts of information, minimizing the need for screen scrolling.

The M7100 is designed to provide maximum flexibility across a wide range of data collection applications. The M7100 features an easy-to-use 55-key alphanumeric keypad, multiple integrated scanner options (both 1D and 2D), RS-232 and infrared communication ports. Accessories include single and four position communications/charging cradles, four position battery charger, vehicle mount charger, removable pistol grip with trigger, protective rubber boot, and multiple holsters.

AML is a leading developer & manufacturer of reliable, high-performance bar code and data collection products. Since 1983, AML and its partners have helped thousands of companies worldwide to increase business efficiency and productivity – in manufacturing, warehousing, retail, health care, finance, government, and education. AML products are made in the United States.



AML

Wireless Hand-Held Terminal

Features	Benefits
Rugged, ergonomic design	Supports comfortable, one-handed operation over extended periods of use. Holds up in industrial environments.
Intel StrongARM® Processor	Rapid processing power
Integrated IEEE 802.11b radio with up to 11Mbps throughput Optional: GSM/GPRS connectivity	Industry standard WLAN radio technology for real-time, high-rate data transfer
16MB RAM , 4MB Flash ROM Optional: 32MB RAM/16MB ROM	Ample storage capacity, even for the most information-intensive applications
Graphical 160 x 160 backlit LCD display with multi-font capability	Easy to read, even in dimly lit environments
55-key alphanumeric keypad	Maximizes data entry across a wide range of data collection applications
Rechargeable, high capacity 1500 mAh Lithium-Ion battery	Enhanced power management for eight-hour work shifts without recharging
Open source, embedded Linux® architecture	Highly reliable system performance
IrDA Communication Port	Allows communication to peripheral devices



M7100

Wireless Hand-Held Terminal

Physical Characteristics

Dimensions & Weight:Overall:8.875° length x 3.5° width x 2.25° depth; 16 oz 225mm length x 89mm width x 57mm depth; 453gDrop Specifications:4 ft. (1.2m) to concreteDisplay:Graphical 160 x 160 backlit EL LCD with multi-font capabilityBattery:Rechargeable 1500 mAh Lithium-IonOperating Temperature:14° to 122°F/-10° to 50°CStorage Temperature:-13° to 122°F/-25° to 50°CHumidity:5% to 90% RH non-condensingElectrostatic Discharge (EDS):15 kVdc air; 4kVdc contactKeypad:55-key alphanumericIntegrated Scanner Options:Standard Laser; Long Range Laser; Advanced Long Range Laser; Long Range CCD; 2D ImagerPerformance CharacteristicsAMM® and StorogARM® are trademarks of ARM. LtdCPU:Intel StrongARM® SA1110 @ 133MHzOperating Platform:Open source, embedded Linux®Memory:16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROMApplication Development:AML commandLink™ Wireless Data Collection Software and C+++Communications:IrD; S.; 2 or 1 Mbps, auto-selectFrequency:2.4 GHzOutput Power:17dBm max (20dBm optional)Encryption:None, 40 Bit, 128 Bit (WEP)Wireless Wide Area Network:EGSM 900/ DCS 1800/ PCS 1900Circuit Switch Data:Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4KbpsFax:Group 3 / Class 2.GPRS:Class B, Multi-iot Class B (4 down/1 up/5 per frame), Simultaneous network registration of GS.AT Command Set:Complying with GSM 07.05, 07.07 including GPRS-specific or extende	Physical Characteristics		
Display: Graphical 160 x 160 backlit EL LCD with multi-font capability Battery: Rechargeable 1500 mAh Lithium-Ion Operating Temperature: 14" to 122"F/-10" to 50"C Storage Temperature: -13" to 122"F/-25" to 50"C Humidity: 5% to 90% RH non-condensing Electrostatic Discharge (EDS): 15 kVdc air; 4kVdc contact Keypad: 55-key alphanumeric Integrated Scanner Options: Standard Laser; Long Range Laser; Advanced Long Range Laser; Long Range CCD; 2D Imager Performance Characteristics AAM® and StrongAM® are trademarks of AAM, Ltd. CPU: Intel StrongARM® SA1110 @ 133MHz Operating Platform: Open source, embedded Linux® Memory: 16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROM Application Development: AML CommandLink™ Wireless Data Collection Software and C++ Communications: IrDA; RS-232 Wireless Local Area Network: IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requ	Dimensions & Weight:		
Battery: Rechargeable 1500 mAh Lithium-Ion Operating Temperature: 14° to 122°F/-10° to 50°C Storage Temperature: -13° to 122°F/-25° to 50°C Humidity: 5% to 90% RH non-condensing Electrostatic Discharge (EDS): 15 kVdc air; 4kVdc contact Keypad: 55-key alphanumeric Integrated Scanner Options: Standard Laser; Long Range Laser; Advanced Long Range Laser; Long Range CCD; 2D Imager Performance Characteristics ARM® and StrongARM® are trademarks of ARM, tot CPU: Intel StrongARM® SA1110 @ 133MHz Operating Platform: Open source, embedded Linux® Memory: 16M8 RAM/4MB ROM; Optional 32MB RAM/16MB ROM Application Development: AML CommandLink™ Wireless Data Collection Software and C++ Communications: IrDA; RS-232 Wireless Local Area Network: IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: CPC1 800/ PCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps	Drop Specifications:	4 ft. (1.2m) to concrete	
Operating Temperature: 14° to 122°F/-10° to 50°C Storage Temperature: -13° to 122°F/-25° to 50°C Humidity: 5% to 90% RH non-condensing Electrostatic Discharge (EDS): 15 kVdc air; 4kVdc contact Keypad: 55-key alphanumeric Integrated Scanner Options: Standard Laser; Long Range Laser; Advanced Long Range Laser; Long Range CCD; 2D Imager Performance Characteristics RRM® and StrongARM® are trademarks of ARM. Ltd. CPU: Intel StrongARM® SA1110 @ 133MHz Operating Platform: Open source, embedded Linux® Memory: 16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROM Application Development: AML CommandLink™ Wireless Data Collection Software and C++ Communications: IrDA; RS-232 Wireless Local Area Network: IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSW/GPRS (Data only, Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) <tr< td=""><td>Display:</td><td colspan="2">Graphical 160 x 160 backlit EL LCD with multi-font capability</td></tr<>	Display:	Graphical 160 x 160 backlit EL LCD with multi-font capability	
Storage Temperature: -13° to 122°F/-25° to 50°C Humidity: 5% to 90% RH non-condensing Electrostatic Discharge (EDS): 15 kVdc air; 4kVdc contact Keypad: 55-key alphanumeric Integrated Scanner Options: Standard Laser; Long Range Laser; Advanced Long Range Laser; Long Range CCD; 2D Imager Performance Characteristics ARM® and StrongARM® are trademarks of ARM, Ltd. CPU: Intel StrongARM® SA1110 @ 133MHz Operating Platform: Open source, embedded Linux® Memory: 16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROM Application Development: AML CommandLink™ Wireless Data Collection Software and C++ Communications: IrDA; RS-232 Wireless Data Communications IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous	Battery:	Rechargeable 1500 mAh Lithium-Ion	
Humidity: 5% to 90% RH non-condensing Electrostatic Discharge (EDS): 15 kVdc air; 4kVdc contact Keypad: 55-key alphanumeric Integrated Scanner Options: Standard Laser; Long Range Laser; Advanced Long Range Laser; Long Range CCD; 2D Imager Performance Characteristics ARM® and StrongARM® are trademarks of ARM.Ltd. CPU: Intel StrongARM® SA1110 @ 133MHz Operating Platform: Open source, embedded Linux® Memory: 16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROM Application Development: AML CommandLink™ Wireless Data Collection Software and C++ Communications: IrDA; RS-232 Wireless Data Communications IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.44Kbps Fax:	Operating Temperature:	14° to 122°F/-10° to 50°C	
Electrostatic Discharge (EDS): 15 kVdc air; 4kVdc contact Keypad: 55-key alphanumeric Integrated Scanner Options: Standard Laser; Long Range Laser; Advanced Long Range Laser; Long Range CCD; 2D Imager Performance Characteristics ARM® and StrongARM® are trademarks of ARM, Ltd. CPU: Intel StrongARM® SA1110 @ 133MHz Operating Platform: Open source, embedded Linux® Memory: 16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROM Application Development: AML CommandLink™ Wireless Data Collection Software and C++ Communications: IrDA; RS-232 Wireless Data Communications IEEE 802.11b Standard Data Rate: 11,5.5,2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class	Storage Temperature:	-13° to 122°F/-25° to 50°C	
Keypad: 55-key alphanumeric Integrated Scanner Options: Standard Laser; Long Range Laser; Advanced Long Range Laser; Long Range CCD; 2D Imager Performance Characteristics ARM® and StrongARM® are trademarks of ARM. Ltd. CPU: Intel StrongARM® SA1110 @ 133MHz Operating Platform: Open source, embedded Linux® Memory: 16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROM Application Development: AML CommandLink™ Wireless Data Collection Software and C+++ Communications: IrDA; RS-232 Wireless Data Communications: IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only, Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class 8, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. <td>Humidity:</td> <td colspan="2">5% to 90% RH non-condensing</td>	Humidity:	5% to 90% RH non-condensing	
Integrated Scanner Options: Standard Laser; Long Range Laser; Advanced Long Range Laser; Long Range CCD; 2D Imager Performance Characteristics ARM® and StrongARM® are trademarks of ARM, Ltd. CPU: Intel StrongARM® SA1110 @ 133MHz Operating Platform: Open source, embedded Linux® Memory: 16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROM Application Development: AML CommandLink™ Wireless Data Collection Software and C++ Communications: IrDA; RS-232 Wireless Data Communications IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only, Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05,	Electrostatic Discharge (EDS):	15 kVdc air; 4kVdc contact	
Long Range CCD; 2D Imager Long Rame of the second secon	Keypad:	55-key alphanumeric	
CPU: Intel StrongARM® SA1110 @ 133MHz Operating Platform: Open source, embedded Linux® Memory: 16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROM Application Development: AML CommandLink™ Wireless Data Collection Software and C++ Communications: IrDA; RS-232 Wireless Data Communications: IrDA; RS-232 Wireless Local Area Network: IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Integrated Scanner Options:		
Operating Platform: Open source, embedded Linux® Memory: 16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROM Application Development: AML CommandLink™ Wireless Data Collection Software and C++ Communications: IrDA; RS-232 Wireless Data Communications: IrDA; RS-232 Wireless Local Area Network: IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class 8, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Performance Characteristics	$\mbox{ARM} \circledast$ and $\mbox{StrongARM} \circledast$ are trademarks of ARM, Ltd.	
Memory: 16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROM Application Development: AML CommandLink™ Wireless Data Collection Software and C++ Communications: IrDA; RS-232 Wireless Data Communications: IrDA; RS-232 Wireless Data Communications: IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	CPU:	Intel StrongARM® SA1110 @ 133MHz	
Application Development: AML CommandLink™ Wireless Data Collection Software and C++ Communications: IrDA; RS-232 Wireless Data Communications IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Operating Platform:	Open source, embedded Linux®	
Communications: IrDA; RS-232 Wireless Data Communications Wireless Local Area Network: IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Memory:	16MB RAM/4MB ROM; Optional 32MB RAM/16MB ROM	
Wireless Data Communications Wireless Local Area Network: IEEE 802.11b Standard Data Rate: 11,5.5,2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Application Development:	AML CommandLink ${}^{\rm TM}$ Wireless Data Collection Software and C++	
Wireless Local Area Network: IEEE 802.11b Standard Data Rate: 11, 5.5, 2 or 1 Mbps, auto-select Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Communications:	IrDA; RS-232	
Data Rate:11, 5.5, 2 or 1 Mbps, auto-selectFrequency:2.4 GHzOutput Power:17dBm max (20dBm optional)Encryption:None, 40 Bit, 128 Bit (WEP)Wireless Wide Area Network:Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.)Tri-band Operations:EGSM 900/ DCS 1800/ PCS 1900Circuit Switch Data:Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4KbpsFax:Group 3 / Class 2.GPRS:Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS.AT Command Set:Complying with GSM 07.05, 07.07 including GPRS-specific or	Wireless Data Communication	ns	
Frequency: 2.4 GHz Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Wireless Local Area Network:	IEEE 802.11b Standard	
Output Power: 17dBm max (20dBm optional) Encryption: None, 40 Bit, 128 Bit (WEP) Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Data Rate:	11, 5.5, 2 or 1 Mbps, auto-select	
Encryption:None, 40 Bit, 128 Bit (WEP)Wireless Wide Area Network:Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.)Tri-band Operations:EGSM 900/ DCS 1800/ PCS 1900Circuit Switch Data:Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4KbpsFax:Group 3 / Class 2.GPRS:Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS.AT Command Set:Complying with GSM 07.05, 07.07 including GPRS-specific or	Frequency:	2.4 GHz	
Wireless Wide Area Network: Optional Tri Band GSM/GPRS (Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.) Tri-band Operations: EGSM 900/ DCS 1800/ PCS 1900 Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Output Power:	17dBm max (20dBm optional)	
(Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account. Replaces standard IEEE 802.11b WLAN radio.)Tri-band Operations:EGSM 900/ DCS 1800/ PCS 1900Circuit Switch Data:Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4KbpsFax:Group 3 / Class 2.GPRS:Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS.AT Command Set:Complying with GSM 07.05, 07.07 including GPRS-specific or	Encryption:	None, 40 Bit, 128 Bit (WEP)	
Circuit Switch Data: Asynchronous, Transparent / Non-Transparent Mode, Up to 14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Wireless Wide Area Network:	(Data only. Does not support voice. Requires optional 32MB/16MB memory upgrade and customer supplied GSM cellular account.	
14.4Kbps Fax: Group 3 / Class 2. GPRS: Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS. AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Tri-band Operations:	EGSM 900/ DCS 1800/ PCS 1900	
GPRS:Class B, Multi-slot Class 8 (4 down/1 up/5 per frame), Simultaneous network registration of GS.AT Command Set:Complying with GSM 07.05, 07.07 including GPRS-specific or	Circuit Switch Data:		
AT Command Set: Complying with GSM 07.05, 07.07 including GPRS-specific or	Fax:	Group 3 / Class 2.	
	GPRS:		
	AT Command Set:		
Antenna: Internal (WLAN or WWAN)	Antenna:	Internal (WLAN or WWAN)	



Optional Peripherals & Accessories		
Cradles:	Single slot & four position communication/charging cradles available	
Vehicle:	Vehicle mount terminal charger; vehicle mount cradle (non-charging)	
Four Position Battery Charger:	Simultaneously charges 1-4 batteries	
Pistol Grip:	Removable pistol grip with trigger	
Holsters:	Functional holster with belt; holster with shoulder strap; protective rubber boot	
Regulatory		
EMI/RFI:	FCC Part 15 Class A	
Laser Safety:	CDRH Class II, IEC Class 2	
Safety:	Mexico NOM/NYCE - NOM 019 SCFI	
Connectivity		
Terminal Emulation:	VT100/VT220 Standard; Optional 3270 & 5250 Terminal Emulation	
Built-in Software Functions:	TELNET Client, FTP Server, Web Server, Web Browser (requires optional memory upgrade)	

Specifications and information are subject to change without notice. All trademarks are property of their respective owners.

Options

Extended Warranty coverage (3 years) Extended Warranty Plus coverage (3 years) CARE Plan Extended Warranty coverage (3 years)

Maintenance & Support

A one (1) year warranty agreement is included with the purchase of the M7100.







