



NetVanta 3305

Multi-Slot Access Router Supporting up to Three T1s Worth of Bandwidth

Product Features

- Dual Interchangeable Network Interface Modules (NIMs)
- Dual auto-sensing 10/100Base-T interfaces for LAN segmentation
- Stateful inspection firewall for network security
- Quality of Service (QoS) for delay sensitive traffic like VoIP
- Command Line Interface (CLI) mimics industry *de facto* standard
- Optional DSX-1 interface supplies TDM voice transport
- Comprehensive PPP dial backup scheme prevents network downtime
- VLAN Trunking (802.1Q) for routing between VLANs
- Network Address Translation (NAT) for IP Addresses Concealing
- Optional VPN for secure corporate connectivity across the Internet
- Built-in DSU/CSU for circuit protection
- Feature-rich ADTRAN Operating System (OS)
- Industry-leading five-year North American warranty

The NetVanta® 3000 Series of modular access routers are designed for cost-effective Internet access, corporate Frame Relay, point-to-point connectivity, ADSL, and Virtual Private Networking (VPN). The NetVanta 3000 Series currently consists of the NetVanta 3200, 3205, and 3305 with a variety of interchangeable Network Interface Modules (NIMs) and Dial Backup Modules (DIMs).

Modular Hardware

The NetVanta 3305 is a dual-slot, dual-Ethernet 1U high, rackmountable metal enclosure. A single slot within any of the NetVanta 3000 Series will house a variety of NIMs and DIMs, which include a 56/64k, T1/FT1, T1/FT1 with DSX-1, Dual T1s, E1/FE1, E1/FE1 with G.703, ADSL, or a Serial interface. For dial backup an Analog Modem, an ISDNBRI, or Serial DIM is available for preventing downtime by dialing around a failed circuit to any PPP compliant device.

Standard-based Protocols

The versatile hardware platform of the NetVanta 3305 is further complemented with the ADTRAN® Operating System (AOS). AOS allows for the support of static and default routes, demand and policy-based routing, and allows for fast, accurate network convergence using routing protocols such as BGP, OSPF, and RIP. In addition, AOS terminates Frame Relay, Multilink Frame Relay, PPP, Multilink PPP, PPPoE, PPPoA, RFC 1483, and HDLC WAN protocols. Multi-homing is also available to provide redundant or backup WAN links to multiple ISPs, guaranteeing a wide-area connection.

Security

For added security, AOS provides a powerful, high performance stateful inspection firewall. It will examine all incoming and outgoing packets against the security policies established by the IT manager. In addition, the firewall can identify and protect against common Denial of Service (DoS) attacks like TCP syn flooding, IP spoofing, ICMP redirect, ping-of-death, and IP reassembly problems. With the AOS Enhanced Feature Pack Upgrade, the NetVanta 3000 Series adds the support for IPSec compliant VPN. The

NetVanta 3305 supports up to 500 simultaneous VPN tunnels, while supporting encryption algorithms like DES, 3DES, and AES. With this upgrade, the NetVanta 3000 Series is fully compatible with ADTRAN's IPSec VPN equipped NetVanta products: Ethernet switches, access routers, and VPN/Firewall appliances.

Quality of Service (QoS)

QoS is also supported for delay sensitive traffic like VoIP or video. To prioritize mission critical traffic and control network congestion, the NetVanta 3305 uses Low Latency Queuing, Weighted Fair Queuing (WFQ), Class-based WFQ, and DiffServ marking to establish priority of IP packets routed over the WAN.

VoIP Ready

In combination with the QoS features, a specialized SIP Application Layer Gateway (ALG) allows SIP traffic to traverse NAT-enabled firewalls. For an enterprise network, this interoperability allows IP PBXs, phones, and other SIP-based devices to set up, tear down, and pass voice and call control messages seamlessly through the integral NAT-enabled firewall.

Administration

AOS offers a standard Command Line Interface (CLI) that mimics the widely adopted, industry *de facto* standard. The sequence of commands to configure similar devices is almost identical, virtually eliminating training costs associated with re-learning a new operating system or costly industry certifications. The CLI also allows for configuration scripts to be used, saved, and downloaded for a quick and easy recovery mechanism. In addition, an intuitive web-based GUI provides step-by-step configuration wizards, management capability, and the ability to upload firmware updates.

ADTRAN, the leader in WAN connectivity, offers reliable equipment that increases network performance, lowers cost, and positions networks for the future. The NetVanta 3000 Series is no exception. In addition, these products are backed by an industry-leading five-year North American warranty, free firmware downloads, and world-class 24-hour technical support from ADTRAN.





ADTRAN, Inc.

Attn: Enterprise Networks
901 Explorer Boulevard
Huntsville, AL 35806

P.O. Box 140000
Huntsville, AL 35814-4000

256 963-8000 voice
256 963-8699 fax

General Information
800 9ADTRAN
info@adtran.com
www.adtran.com

Pre-Sales
Technical Support
800 615-1176 toll-free
application.engineer@adtran.com
www.adtran.com/support

Where to Buy
877 280-8416 toll-free
channel.sales@adtran.com
www.adtran.com/where2buy

Post-Sales
Technical Support
888 423-8726
support@adtran.com
www.adtran.com/support

ACES Installation & Maintenance Service
888 874-ACES
aces@adtran.com
www.adtran.com/support

International Inquiries
256 963 8000 voice
256 963-6300 fax
international@adtran.com
www.adtran.com/international

For the regional office nearest you, visit:
www.adtran.com/regional

For more information regarding
ADTRAN's export license, please
visit www.adtran.com/exportlicense



ADTRAN is an ISO 9001, ISO 14001,
and a TL 9000 certified supplier.

61200880L1-8J 11.1 November 2005
Copyright © 2005 ADTRAN, Inc.
All rights reserved.

NetVanta® 3305



Multi-Slot Access Router Supporting up to Three T1s worth of Bandwidth

Physical Interface

- **Dual NIM:** 56/64k, T1/FT1, T1/FT1 with DSX-1, Dual T1s, E1/FE1, E1/FE1 with G.307, ADSL, and Serial
- **DIM:** Analog Modem, ISDN BRI (U and S/T), and Serial
- **Dual LAN:** Auto-sensing 10/100Base-T Full Duplex (RJ-45)
- Console Port

Diagnostics LEDs

- Power
- **Dual WAN:** link, transmit, receive
- **Dual LAN:** link, transmit, receive
- **Dual Dial Backup:** transmit and receive

Processor and Memory

- 120 MHz, Motorola MPC 866
- **RAM:** 64 MB
- **FLASH:** 16 MB

Security

Firewall

- Stateful Inspection Firewall
- Denial of Service (DoS) Protection
- Access Control Lists
- Application Level Gateways (ALGs)

Network Address Translation

- Basic NAT (1:1), NAT (Many:1), and 1:1 Port Translation
- NAT compatible SIP ALG

Secure Management

- Multi-level access control
- RADIUS AAA
- TACACS+
- SSH CLI and SSL GUI
- Port Authentication (802.1x)

Optional Virtual Private Network (VPN)

- **IPSec Mode:** Tunnel
- **Encryption:** DES, 3DES, and AES
- **Diffie Hellman Group Support:**
 - Group 1: MODP 768
 - Group 2: MODP 1024
- **Hash Algorithms:** MD5-HMAC and SHA1-HMAC
- **Authentication Mechanisms:**
 - XAUTH
 - Secure ID
 - X.509 Digital certificates
 - DSS Signatures
 - Preshared keys
- **Key Management:** IKE (ISAKMP/Oakley)
- **IKE Modes:**
 - Main
 - Aggressive
 - Perfect Forward Secrecy
 - Mode Config
- Dead Peer Detection
- NAT Traversal V2

Quality of Service (QoS)

- Class-based Weighted Fair Queuing, Low Latency, and Weighted Fair Queuing
- DiffServ Packet Marking and Recognition
- Frame Relay Fragmentation

Routing

- eBGP/iBGP
- OSPF
- RIP (v1 and v2)
- Demand Routing
- Policy-based Routing
- GRE
- ATM (ADSL)
- Frame Relay
- Multilink Frame Relay
- PPP
- Multilink PPP
- PPPoE
- PPPoA
- IGMP v2
- RFC 1483
- HDLC
- PPP Dial Backup
- PAP and CHAP
- Multihoming

Frame Relay

- Point-to-point
- RFC 1490 Encapsulation (Multiprotocol Over Frame Relay)
- **LMI types:** LMI, ANSI (Annex D), CCITT (Annex A) and Static

DHCP

- Client, Server, and Relay

Administration

- Familiar Command Line Interface (CLI)
- Web-based GUI
- n-Command™ support
- SNMP v2
- SYSLOG logging
- Email alerts (SMTP)
- Policy statistics

Environment

- **Operating Temperature:** 0° to 50 °C (32° to 122 °F)
- **Storage Temperature:** -20° to 70 °C (-4° to 158 °F)
- **Relative Humidity:** Up to 95%, non-condensing

Physical

- **Chassis:** 1U rackmountable metal enclosure
- **Dimensions:** 1.25" H, 17.25" W, 7.75" D
- **Weight:** 7.5 lbs.
- **Power:** 100-250 VAC, 50/60 Hz, 6 W max.

Agency Approvals

- FCC Part 68
- Industry Canada CS03
- UL & Canadian UL (CUL), IEC/EN, CSA
- CE Mark

Product Includes

- User Manual, Quick Start Guide, AC Power Cord

Ordering Information

Equipment	Part #
Systems	
NetVanta 3305 Chassis	1202880L1
with T1/FT1 NIM	4200882L1
with T1/FT1+DSX-1 NIM	4200883L1
NetVanta 3305 Chassis with VPN	4200880L2
VPN Upgrade Kit	4200368L1

Specifications subject to change without notice. ADTRAN and NetVanta are registered trademarks of ADTRAN, Inc. n-Command is a trademark of ADTRAN, Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.