



AirTrack Performance Product **2200T** THERMAL TRANSFER

GLOSS POLYPROPYLENE LABEL SPECIFICATIONS

Features

- Thermal transfer, gloss polypropylene with a permanent, acrylic adhesive.
- Ideal for indoor or short-term outdoor applications.
- Topcoat is resistant to moisture, chemicals, grease, and UV rays when imaged with the correct ribbon.
- Adheres well to plastic and glass containers of all size and shape, and “glove friendly” for easy handling

Compliance and Certifications

- FDA 21 CFR 175.105 for indirect food contact

Suggested Applications

- Cold Storage
- Food Labeling
- Product Identification
- Shipping/Receiving
- Tote Labeling
- Work in Process

Compatible Ribbon Formulations

WAX	WAX-RESIN	RESIN
13	20	31
	21	32
	22	33
		34
		40

Material Construction

COMPONENT	DESCRIPTION	CALIPER
Facestock	High gloss, top coated polypropylene	2.5 mil
Adhesive	Permanent, emulsion acrylic	
Liner	40 lb. high density liner	2.3 mil

Material Performance

CONDITIONS	TEMPERATURE
Minimum Application Temp	40°F (4°C)
Service Temperature Range	-40°F to 200°F (-40°C to 93°C)

All materials should be tested under actual application conditions to determine performance suitability.