



AirTrack® Performance Product **ATT THERMAL TRANSFER**

PAPER LABEL SPECIFICATIONS

Features

- Thermal transfer, top coated paper with a permanent, all-temp adhesive.
- Designed for indoor and limited outdoor use.
- Optimal imaging and consistently scannable barcodes.
- Recommended for thermal printing applications up to 14 inches per second.
- High initial tack and excellent holding power, performing exceptionally well in cold, ambient, and warm environments
- Adheres well to corrugate, plastic, and metals.

Compliance and Certifications

- FDA 21 CFR 175.105 for indirect food contact

Suggested Applications

- Food Labeling
- Healthcare/Laboratory
- Product Identification
- Shipping
- Warehouse/Rack
- Work in Process

Compatible Ribbon Formulations

WAX	WAX-RESIN
11	20
12	21
13	22
14	

Material Construction

COMPONENT	DESCRIPTION	CALIPER
Facestock	44 lb. top coated paper	3.0 mil
Adhesive	Permanent, all-temp emulsion acrylic	0.7 mil
Liner	42.7 lb. supercalendered paper silicone coated (one side)	2.5 mil
Overall material construction thickness (±10%)		6.2 mil

Material Performance

CONDITIONS	TEMPERATURE
Minimum Application Temp	-10°F (-23°C)
Service Temperature Range	-60°F to 225°F (-51°C to 107°C)
Storage Conditions	72°F (22°C) at 50% RH, Shelf life of 1 year

All materials should be tested under actual application conditions to determine performance suitability. All information is subject to change without notice.