



AirTrack® Performance Product RECEIPT PAPER

SPECIFICATIONS

Features

- Good for general imaging, graphics, and logo imaging
- Low caliper, receipt-grade paper

Compliance and Certifications

- BPA Free

Suggested Applications

- Event Ticketing
- Parking Receipts
- ATM & Banking
- Event Ticketing
- Parking Receipts
- Retail Point-of-Sale

Product Characteristics

COMPONENT	VALUE
Caliper (mils/ μ m)	2.10 $\pm$ 0.15/53 $\pm$
Basis Weight 17 x 22-500 (lbs) g/m ²	11.6 $\pm$ 0.7 43.7 $\pm$ 2.9

Thermal Response - Nominal

STATIC ($^{\circ}$ C $\pm$ 5 $^{\circ}$)	
0.2 ODU	87
1.0 ODU	136
Maximum Density (ODU)	1.23
Temperature Required	148

DYNAMIC - ATLANTEK 400 (mJ/mm ²)	
0.2 ODU 5.1	5.1
1.0 ODU 6.9	8.5
Maximum Density (ODU)	1.50
Energy Required	13.2

Additional Characteristics

COMPONENT	VALUE
Brightness (UV Included)	>85
Gurley Stiffness Nominal (mg)	MD 20 CD 9
Elmendorf Tear Nominal (g)	MD 23 CD 30
Parker Print Surf	<2.00