

ALTV615DC416UL, ALTV615DC416UCB UL Listed DC CCTV Power Supply

Rev. DSALTV615DC416UL - B14F



Overview

 These Altronix DC Wall Mount CCTV Power Supplies provide 6VDC to 15VDC distributed via sixteen (16) Class 2 Rated fuse or PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV615DC416UL

- Sixteen (16) Class 2 Rated fuse protected power limited outputs.
- Outputs are rated @ 3.5 amp.

ALTV615DC416UCB

- Sixteen (16) Class 2 Rated PTC protected outputs.
- Outputs are rated @ 2.5 amp.

Specifications

- Input 115VAC 50/60Hz, .9 amp.
- 6VDC to 15VDC adjustable @ 4 amp total supply current.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.
- Illuminated power disconnect circuit breaker with manual reset.
- AC and DC power LEDs.
- Spare fuses included (on fuse protected models).

- Unit maintains camera synchronization.
- Ease of installation saves time & eliminates costly labor.
- Product weight:
 - ALTV615DC416UL: 10.1 lbs.
 - ALTV615DC416UCB: 10.1 lbs.
- Shipping weight:
 - ALTV615DC416UL: 11.0 lbs.
 - ALTV615DC416UCB: 11.0 lbs.

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions

13"H x 13.5"W x 3.5"D

