

Avery Dennison® Monarch® 9416XL Printer

SMALL PRINTERS FOR TIGHT SPACES

The Avery Dennison® 9416XL printers fit into areas where there is traditionally not a lot of room to spare: retail back rooms and shipping docks. They're perfect for:

- Shipping and routing labels
- Small signs
- Receipts
- Replacement tags

Available for thermal direct or thermal transfer supplies.

OPTIMUM SPEED FOR MAXIMUM PRODUCTIVITY

- Equipped with a 32-bit RISC processor. Prints at speeds up to 4 ips (3 ips on 300 dpi), increasing your productivity for quick label or tag turnaround
- Featuring 4 Mb Flash and 8 Mb SDRAM. With more memory to work with, print jobs go faster, increasing productivity. Also has a slot

FLEXIBLE SUPPLY CHOICE

- Non-indexed
- Continuous
- Die cut
- Black mark
- Roll
- Fanfold

VERSATILE OPTIONS

- Ethernet
- Keyboard
- External supply holder
- Cutter
- Choice of thermal direct or thermal transfer printing
- 203 dpi or 300 dpi printing

ELEVATING BRANDS. ACCELERATING PERFORMANCE.

For more information call: 800.543.6650, prompt 5 or
email: printersolutions@averydennison.com



Innovative, intelligent and sustainable labeling and printing solutions that accelerate supply chain performance, increase productivity and elevate the consumer experience.

Avery Dennison® Monarch® 9416XL Printer



SPECIFICATIONS

9416XL THERMAL TRANSFER

HEIGHT: 7.4" (118 MM)

WIDTH: 8.38" (213 MM)

DEPTH: 12.36" (314 MM)

WEIGHT: 6.3 LBS (2.86 KG) W/O POWER SUPPLY

SHIPPING WEIGHT: 12 LBS (5.4 KG)

9416XL THERMAL DIRECT

HEIGHT: 6.3" (168 MM)

WIDTH: 8.25" (210 MM)

DEPTH: 9.4" (239 MM)

WEIGHT: 4.1 LBS. (1.9 KG) W/O POWER SUPPLY

SHIPPING WEIGHT: 9 LBS. (4.1 KG)

COMMON SPECIFICATIONS FOR BOTH PRINTERS

PROCESSOR: 32-bit RISC Processor

MEMORY: 4 Mb Flash, 8 Mb SDRAM, SD card reader

PRINTER LANGUAGE: MPCLII/EPL2 (auto detect)

CONNECTIVITY: PC/host interface: Serial, Centronics/Parallel Port, USB

FONTS: Standard fonts: 5 A/N, OCRA (like), CG Triumvirate
Loadable fonts: True Type, Bit Map

PRINTHEAD: 4.09" (104 mm)

PRINTER WARRANTY: One (1) year parts and labor.

PRINTHEAD WARRANTY: 1 million inches, or six months, whichever occurs first

BARCODE TYPES: UPCA +2/+5, UPCE +2/+5, EAN8 +2/+5, EAN13 +2/+5, EAN128, Code 39, Codabar (NW7), Code 128 UCC (A,B,C), Code 93, Code 16K, Code 11, MSI, PDF417, MicroPDF417, POSTNET, MaxiCode, Plessey, I 2 of 5

MEDIA WIDTH: 0.78" - 4.4" (20-112mm)

MEDIA THICKNESS 2.36 - 6.3 mill

CORE DIAMETER 1" - 3" (25.4mm - 76.2mm)

EVERY DENNISON® SERVICE AND SUPPORT

Our technical specialists and service representatives can provide installation support, training and operating recommendations. For more information call 800.543.6650, option 7.

AMERICAS

170 Monarch Lane
Miamisburg, OH 45342
937 865 2123 (direct)
Tel +800 543 6650
(8:00 a.m.–6:30 p.m., EDT)
Fax +937 865 6663

ASIA

No. 7 Chun Ying Street
Tseung Kwan O Industrial
Estate
New Territories, Hong Kong
Tel +852 2372 3169
Fax +852 2995 0014

WESTERN EUROPE

1 Thomas Road
Wooburn Green
Bucks HP10 0PE
Tel +(44) 1628 859500
Fax +(44) 1628 859567

ASIA PACIFIC NEW SOUTH WA

61 Vore Street
Silverwater NSW 2128
Tel +(02) 9647 1833
Fax +(02) 9647 1914
Toll free (Outside Sydney only)

Accelerating supply chain
performance and elevating
the consumer experience.