

Inventory Accuracy, Visibility and Loss Prevention

Avery Dennison 9906 Tabletop

Elevating Brands and Accelerating Performance
Throughout the Global Retail Supply Chain



Accelerate Performance: Inventory Accuracy, Visibility and Loss Prevention

Improve Inventory Management, Visibility and Loss Prevention through integrated solutions from manufacturing source to consumer that increase speed, accuracy, visibility, productivity and margins.

Durable, Reliable and Easily Integrated

The Avery Dennison 9906 Printer has a large graphical display for a more user-friendly menu system as well as support for Asian fonts. The right choice for retailers or distribution centers printing less than 10,000 labels or tags per week, including:

- Shipping labels
- Replacement tags
- Routing labels

Compact, Sleek and Quiet

The compact design of the 9906 ensures it fits into some of the tightest workspaces in distribution centers and retail stores.

Its design and low-noise printing output avoid disruption to the retail customer experience.

Elevates Brand

Prints identical replacement tags that are indistinguishable from the tags applied at the source. Customers won't be able to tell if the item has been retagged.

Decreases Downtime

The unique ribbon tensioning system means fewer parts to maintain and replace, reducing costs and avoiding downtime in your inventory control process.

Data Stream Flexibility

Full range of connectivity options, including RS-232, USB 2.0, Ethernet and wireless 802.11b/g networking. Material handling options including liner peel, liner take-up, and ticket and tag cutting.

Sustainable

Energy Star rated, reducing your impact on the environment, saving on energy and costs.

Global Service Bureau

In addition to utilizing on-site printing for greater efficiency, also consider Ticket Express®, Avery Dennison's global service bureau. With Ticket Express, you can order variably imprinted tags and labels, including RFID, fabric and paper versions, when and where you need them - anywhere in the world. Using both in-plant printing and Ticket Express gives you the best combination of speed and flexibility.

Elevating Brands. Accelerating Performance.

Experience Avery Dennison supply chain solutions at our worldwide Customer Design and Innovation Centers. For more information on Avery Dennison 9906 Tabletop Bar Code Printer or to schedule a tour of our Customer Design and Innovation Centers, please call 800.543.6650, prompt 5, or e-mail rbis.solutions@averydennison.com.

To learn more or receive complete warranty information as well as other terms and conditions, please contact your Avery Dennison representative or visit our website at www.rbis.averydennison.com.



Inventory Accuracy, Visibility and Loss Prevention

Avery Dennison® 9906 Tabletop Bar Code Printer

Elevating Brands and Accelerating Performance
Throughout the Global Retail Supply Chain



Avery Dennison® 9906 Tabletop Bar Code Printer

Standard Features

Dimensions

Height: 11" (279mm)
Width: 10.5" (267mm)
Depth: 16.1" (409mm)

Weight:

22.1 lbs (10kg)

Shipping Weight:

25 lbs (11.4 kg)

Printing Method:

Thermal direct or Thermal transfer

Printhead:

4.09" (102mm/812 dots)
203 dots/inch (8 dots/mm)

Memory:

Model BA:
4 MB Flash, 16 MB SDRAM
Model EF:
32 MB Flash, 32 MB SDRAM

Bar Codes:

UPCA +2/+5, UPCE +2/+5, EAN8 +2/+5, EAN13 +2/+5, EAN128 Interleaved 2 of 5, Extended Code 39, Codabar (NW7), Code 128, Code 16K, Code 93, MSI, Postnet, Intelligent Mail, GS1 Databar, PDF417, Maxi-Code, Data Matrix (ECC-200), Quick Response (QR Code), Aztec

Standard Fonts:

Bitmap - Standard, Reduced, Bold, OCRA-like, CG Triumvirate, and CG Triumvirate Bold
TrueType® - EFF Swiss Bold

Font Magnification:

1x to 7x for Bitmapped fonts, 4 to 250 pt. for scalable / TrueType™ fonts

Standard PC/Host Interface:

RS-232C Serial (115, 200 BPS)
USB 2.0 Host; USB 2.0 Device

Sensing Method:

Edge justified, die cut, black mark, aperture

Printer Control Language(s):

MPCL, Easyplug, MLI

Printer Warranty:

One (1) year parts and labor.
Full written warranty statement available upon request.

Printhead Warranty:

One (1) million inches or six (6) months, whichever occurs first

Supplies

Only Avery Dennison supplies are recommended. Use non-perforated supplies in peel mode, butt cut, die cut or non-indexed.

Supply Types:

Labels and Tags

Supply Sizes:

Width: 0.75" to 4.5"
(19 mm to 114 mm)
Length: 0.50" to 50"
(13 mm to 1270 mm)
Width with peel: 1.5" - 4.25" (38 mm to 108 mm)
Maximum length with indexed supplies: 17.5" (445 mm)
Supply Roll OD: 8" on 3" core

Typical Supply Roll Length:

492' (150 m)

Supply Thickness:

0.0055" to 0.010"
(.1397 mm to .2540 mm)

Ribbon Length:

1476.38' (450 m)

Environmental Ranges

Operating Temperature:

Thermal Transfer:
40° to 95°F (4° to 35°C)
Thermal Direct:
40° to 104°F (4° to 40°C)

Storage:

15° to 120°F (-10° to 49°C)

Humidity/Operating and Storage:

5% to 90% non-condensing

Electrostatic Discharge and Air Quality:

Some problems with electronic equipment may occur in environments prone to static discharge or extreme dust conditions. Avery Dennison suggests that you take precautions to minimize these problems.

Performance

Power Source:

90-264 VAC with
Auto select 50/60 Hz
"Energy Star" qualified

Print Speed:

- 2.5 ips (64 mm) - default for serial bar codes
- 4.0 ips (102 mm)
- 6.0 ips (152 mm) - default for parallel bar codes

Option & Accessories

Options:

- Peel mode with on demand sensor
- Peel mode with liner take-up
- Tear bar with peel mode
- 300 dpi printhead
- ADK script programming for special applications
- Internal Ethernet with MonarchNet2™
- 802.11 b/g wireless with MonarchNet2™
- Parallel port (IEEE-1284)
- Tag cutter

Accessories:

- 935 Rewind
- 939i Keypad
- USB QWERTY keyboard
- 929 Tag catch tray

In our ongoing effort to deliver the best technology, specifications are subject to change without notice.

The information contained herein is believed to be reliable but Avery Dennison makes no representations concerning the accuracy or correctness of the data. This product, like any other, should be tested by the customer/user thoroughly under end user conditions to ensure the product meets the particular requirements. Independent results may vary. Avery Dennison and the logo are registered trademarks of Avery Dennison Corp. Third party trademarks and/or trade names used herein are the property of their respective owner(s). Avery Dennison liability is limited to the replacement value of defective products. In no event shall Avery Dennison be held liable for consequential, indirect or incidental damages. Products, information and specifications are subject to change without notice. See reverse side for product specifications.

Avery Dennison and the logo are registered trademarks of Avery Dennison Corp. Third party trademarks and/or trade names used herein are the property of their respective owner(s).
© 2012 Avery Dennison Corporation, All Rights Reserved.

Avery Dennison Retail Branding and Information Solutions

Americas

1700 West Park Drive, Suite 400
Westborough, MA 01581
USA
Toll Free +1 800 444 4947
International +1 336 621 2570
Fax +1 336 544 5040

Asia

15/F, Octa Tower
8 Lam Chak Street
Kowloon Bay, Kowloon
Hong Kong
Tel +852 3146 8100
Fax +852 2785 1255

E. Europe, Middle East & Africa

TEM Otoyolu Atış Alanı Mevkii,
Tekstil Kent Koza Plaza A Blok
Kat: 17-18 34235, Esenler
Istanbul
Turkey
Tel +90 212 467 4000
Fax +90 212 467 4001

Western Europe

Kempische Kaai 7C
3500 Hasselt
Belgium
Tel +32 11 28 77 24
Fax +32 11 28 77 29