

AXIS 70U Network Document Server

Smarter document distribution

Connected to an office scanner, the AXIS 70U Network Document Server allows you to scan documents, reports and photos, and instantly e-mail them to any number of recipients.

Documents can be distributed as e-mail attachments in standard Adobe PDF formats, delivering higher image quality than documents sent by fax, even in full color. Supporting a variety of office scanners such as HP, Canon and Fujitsu, AXIS 70U connects to IP networks without the need for a PC or additional software making document distribution quick, easy and safe.

Easy to install and use, AXIS 70U provides a faster and more cost efficient method of distributing documents than by fax, traditional mail or courier.





- Communicates using Internet, not expensive phone lines
- Requires little maintenance (no need to add toner or paper)
- Documents are sent without delay directly to the receivers' e-mail Inbox
- Image quality is better than fax and not limited to black and white
- No busy tone or re-transmissions of multipage documents



AXIS 70U Network Document Server



Specifications			
Supported image file formats	Adobe PDF 1.2: The created PDF file contains uncompressed or compressed bit images in CCITT G.3/G.4 PackBits (4 bit) or JPEG (24 bit) formats TIFF 6.0: CCITT G.3 and G.4 for bilevel images, PackBits (4 bit) for grayscale images; both single- and multi-page TIFF are supported JPEG File Interchange Format (JFIF) for single-page color (24 bit) or grayscale (8 bit) images TIFF 4.0 and PackBits for black/white images PCL5 for black/white and color images	Security	Administrator's log-in for configuration and administration Administrator specifies which destinations are accessible Possible to set a default destination or single destination for fixed application use Optional Windows NT/2000, Server 2003, Active Directory or LDAP user authentication if keyboard is installed E-mail delivery confirmation via MDN or DSN SMTP authentication for outgoing emails 5.1 V, 2A, via external power unit (PS-H)
User interface	Alphanumeric LCD display with 2 rows of 16 characters English, French, German, Italian, Spanish, Danish, Norwegian and Swedish text available 4 multi-color LEDs signaling Status, Busy, Network and Power 7 keys for Menu, Up, Down, Select, Send, Add page and Cancel Menu functionality for selecting Destination, Profile, Paper Size, Double-sided, Sent by, Subject and File name options Multiple destinations selection possible Optional: PC keyboard for easy search, ad-hoc entering of e-mail addresses and shortcuts to menu options. US, UK, German, Danish, Finish, Norwegian, Spanish, French and Swedish keyboard layouts Windows NT/2000, Server 2003 and LDAP User authentication available File naming capability	Operating conditions	5-40 °C (40-105 °F) Humidity 20-80% RH (non-condensing)
		Installation, management and maintenance	Set IP-address via user interface or optional keyboard or via DHCP, BOOTP, RARP or ARP For Send to e-mail, file, URL and print: Configure destinations via Web browser or configuration file E-mail addresses can also be automatically retrieved from the mail server via LDAP
		Minimum Web browsing requirements	Netscape Communicator 4.0 and higher Microsoft Internet Explorer 4.0 and higher Other compatible browsers
		Supported LDAP servers	Microsoft Exchange 2003/5.x, 2000 (multiple containers are supported) Lotus cc:Mail 8.2, Domino Novell GroupWise 5.2, 5.5, 6.5 Netscape iPlanet
Application integration	Meta data support based on XML. See AXIS 7000 developer's section at www.axis.com	Supported systems	OpenLDAP Any system supporting TCP/IP and optionally:
Network attachments	IEEE 802.2, IEEE 802.3, SNAP, Ethernet II frame types simultaneously	,	HyperText Transfer Protocol (HTTP) client (Web browser) File Transfer Protocol (FTP) server Simple Mail Transfer Protocol (SMTP) server
Network management	Configuration and administration via a standard Web browser SNMP MIB II	Supported transfer methods	Send-to-E-mail (SMTP) Send-to-File (FTP active/passive) Send-to-Web browser (HTTP) Send-to-URL (SMTP and FTP) Send-to-Print (LPD and Raw TCP)
Scanner attachment	USB Full speed, type A receptacle		
Optional keyboard attachment	Mini-DIN		
Software updates	Flash memory allows central and remote software updates over the network using FTP	Supported devices	See latest list of supported devices on Axis' Web site www.axis.com
Profiles	Ten pre-defined profiles: Text, Text low/high, Text Photo, Text PDF, Gray low/high, Color low/high and Color PDF (ability to edit these profiles or create new ones to suit specific needs)	Supported mail servers	Microsoft Exchange, Sendmail, Lotus Notes, Novell Groupwise, Compatible SMTP mail servers
		Supported protocols	HTTP, IP, FTP, SMTP, TCP, LPD, Raw TCP/IP, ARP, RARP, BOOTP, DHCP, ICMP, SNMP, UDP, LDAP v.1 & v.3, NTP, WINS, SMB
Paper sizes	Executive, Letter, Legal, Ledger, A5, A4, A3, B5, B4, Photo and Business Card Edit standard paper sizes, or create new ones to suit specific needs	Accessories (not incl.)	Mini-keyboard
		Approvals	FCC Part 15 Subpart B, Class A, EN 55022 Class B, EN 55024, VCCI Class B, EN 60950
Processor and memory	CPU: 32-bit RISC processor (ETRAX 100LX) RAM: 16 MB, Flash: 2 MB	Dimensions (HxWxD) and weight	43 x 149 x 224 mm (1.69" x 5.87" x 8.82") 700 g (25 oz)

