

## **AX1S OfficeBasic** Network Print Server

Sharing printers has never been easier

Combining unique multilingual support and automatic installation, the AXIS OfficeBasic print server is the user-oriented network print server for small offices and local networks.

With support for Windows and MacOS networks, AXIS OfficeBasic is the perfect solution for sharing any USB or parallel printer in PC and Mac environments. Just plug and print!

## Good value today...and tomorrow!

With over 20 years experience of innovative printing excellence, Axis now has over 3 million network print servers installed. With a keen awareness for technological change, Axis encourages customers to keep pace with the very latest printer developments with free firmware upgrades published regularly over the web. By offering cutting-edge, future-proof technology, Axis' print server products continue to represent good value today...and tomorrow!

You'll find Axis' unique network technology and customeroriented approach to design clearly evident in this intuitive, easy-to-use print server.



- Quick and easy installation
- Easy web-based management
- Superior reliability
- Multilingual support



## **AXIS OfficeBasic Network Print Server**



| Specifications        |   |   |   |
|-----------------------|---|---|---|
| Supported printers    | USB 1.1, USB 2.0 and parallel printers from e.g. Brother, Canon, Epson, HP, IBM, Lexmark, Minolta, OKI and Xerox running PCL, PS, LX, LQ, IBM proprinter and other similar languages.*  *Exception: PPA, CAPT, GDI and other host-based printers are not supported. | Installation<br>management and<br>maintenance | Embedded web pages for product configuration, management and monitoring PPM MIB v1.0 for status monitoring and installation Bonjour for printer installation in e.g. Mac OSX.  Bonjour is a trademark of Apple Computer Inc., registered in the U.S. and other countries. |
| Front panel           | 2 LED indicators: Power and Network<br>Test button for information printouts  | Supported systems                             | Microsoft Windows: 2000/XP/2003/VISTA<br>Apple EtherTalk: Macintosh System 7, 8, 9<br>MacOS X version 10.X  |
| Network connection    | Ethernet: RJ-45 connector (Category 5 shielded twisted pair cable) for 10baseT Ethernet or 100base TX   | Supported web browsers                        | Any standard web browser (MS Internet Explorer 5.x or higher, Netscape 6.0 or higher)   |
| Printer connection    | USB 1.1 Low and Full speed. Tested with USB 2.0 printers.   | Supported languages                           | English, French, German, Italian, Japanese and Spanish  |
| Logical connection    | 36-Pin centronics connector parallel port, high speed IEEE 1284 compatible. Including ECP support  Ethernet: Use of IEEE802.2, IEEE802.3, SNAP and Ethernet II  | Supported protocols                           | Windows: NetBIOS/NetBEUI, RawTCP, LPR, WINS, ARP, DHCP, DNS, DDNS, SNMP, SLP TCP/IP: ARP, DHCP, BOOTP, RARP, DNS, DDNS, FTP, LPR, Reverse Telnet, IP, TCP, UDP, HTTP, SLP, ICMP, IGMP, SNMP Apple EtherTalk: AAPR, ATP, DDP, NBP, PAP, RTMP, ZIP                          |
|                       | frame types simultaneously Fast Ethernet: Supports NWay that provides auto-detection of network speed. Use of IEEE802.2, IEEE802.3, SNAP and Ethernet II frame types simultaneously, full duplex  | Included accessories                          | AXIS Network Print Servers CD containing printing and installation tools including AXIS AddPrinter Installation guide, mounting clip USB cable  |
| Processors and memory | 32-bit 100 MHz RISC Controller<br>RAM: 8 MB, Flash: 2 MB  | Approvals                                     | EMC: EN 55022/1998, EN 55024:1998, EN 61000-3-2,<br>EN 61000-3-3, VCCI Class B, C-TICK AS/NZS CISPR 22,<br>Compliance to FCC part 15 Subpart B, Class B<br>Safety: EN 60950   |
| Power                 | Power provided by external supply<br>Maximum 5.6 W (Type PS-H, 5.1 VDC 2000mA)  |   |   |
|                       |   | Dimensions                                    | 29 x 62 x 117 mm (1 1/8" X 2 13/32" X 4 19/32")   |
| Operating conditions  | Temperature: 5-40 °C (40-105 °F)  | (HxWxD) and weight                            | 81 g (2 7/8 oz)   |

www.axis.com

