



Durable, yet thin and flexible enough to conform to most surfaces, the new caliber of foil label stands up to chemicals and moderate abrasion to help identify your assets. Available in a variety of new standard color options including gold, copper, purple and dark blue this product showcases detailed color logos beautifully. The excellent print quality reproduces human-readable numbers clearly (with numbers available in 1/8", 3/16" or 1/4" sizes), while the tough, permanent pressure-sensitive adhesive adheres to unwieldy surfaces, including powder-coated metals and plastics.

With exceptional print quality as well as the design and color options available with this product we guarantee you will not find another foil label like it in its class!

Key Product Features

- Nine standard colors including black, red, yellow, green, blue, dark blue, gold, copper and purple
- Serial numbers available in 1/8", 3/16", or 1/4" sizes
- Excellent print quality showcases detailed color logos
- Permanent pressure-sensitive adhesive adheres to unwieldy surfaces including powder-coated metals and plastics

Not sure what product you need?

Call our trained Experts!

800-437-5283



149 4th Street SW • P.O. Box 1468
Mason City, IA 50401-1468
www.idplate.com
E-mail: metalcraft@idplate.com

Printed Foil Labels Specifications

Material: .003" thick anodized aluminum with a clear coat to provide chemical and abrasion resistance. This material can withstand temperatures up to 350°F for short durations.

Label Copy: The label copy may include block type, stylized type, logos or other designs.

Colors: Standard colors include black, red, yellow, green, blue, dark blue, gold, copper and purple.

Standard Sizes:

No. 001: 1 3/4" x 7/16" No. 277: 2" x 3/4"
No. 002: 2 3/8" x 9/16" No. 019: 2" x 1"
No. 033: 1 1/2" x 3/4"

On-Site Printing: Clear coat makes aluminum receptive to permanent marker. Impact printing (i.e. typewriter or ball point pen) will permanently deboss the aluminum leaving an indentation even if the ink wears away.

Packaging: Shipped in peel-off strips for easy removal. Both cartons and trays are clearly marked to indicate serial numbers of contents. Pressure-sensitive adhesive orders are shipped with cleaner and application instructions.

Shipment: 10 work days after receipt of order and proof approval. ID Express is available at an additional charge cutting lead time to 7 work days with 99% yield.

To Order: Call **1-800-437-5283** and ask for customer service.

Test Results

These tests were conducted for a limited period of time in strict laboratory conditions. In order to achieve maximum satisfaction we highly recommend that any customer considering use of this product test the labels in the environment in which they will be used.

Abrasion Test: Label survived more than 700 revolutions on Taber Abrader using Calibrase CS-10 Wheel with 500g weight.

Heat Test: Printed Foil Labels are able to withstand intermittent heat exposure to 350°F.

Readability Test: This rating measures readability/image stability after being exposed to chemicals listed below for a 16 hour soak.

Test Conditions	Rating
Acetone	0
Isopropyl Alcohol	50
Speedball Power Cleaner	80
Glass Cleaner	100
Water	100
Nitric Acid	100
Caustic Soda	0
Brake Fluid	80

Chemical emergence tests are rated on a scale of 100 to 0:

100 = No Effect

75 = Image Blurred

50 = Image Scratches Off

25 = Image Wipes Off

0 = Label Destroyed