

SMART MOBILITY!

3 inch POS Printer SRP-350IIIOBE



HIGHLIGHTS



Perfect Fit for Smart Retailers

- Compatible with smart devices including iOS (MFi optional) and Android
- Simple-to-use Bluetooth wireless printing



Reliable Printing Performance

- A family of the steady-selling SRP-350 line
- Printing speed up to 200 mm/sec



BIXOLON®
a Better Solution for your Business™

3 inch POS Printer

SRP-350IIIBE

Specifications

Print Characteristics

Print Method

Direct Thermal

Print Speed

Up to 200 mm/sec

Print Resolution

180 dpi

Print Width

Up to 72 mm

Sensor

Paper End, Paper Near End, Cover Open

Media Characteristics

Media Type

Receipt

Media Width

80 mm

Media Roll Diameter

Up to 83 mm

Media Thickness

0.062 ~ 0.075 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (WxLxD)

145 x 203 x 146 mm
(5.70 x 7.99 x 5.74 inch)

Weight

1.65 kg (3.63 lbs.)

Power

EnergyStar Certified,
External Power Adaptor 100-240V AC, 50/60Hz

Drawer Port

2 ports (via y-type adaptor)

Performance Characteristics

Memory

64 Mbit SDRAM, 16 Mbit FlashROM

NV Image Memory

256 Kbytes (mono)

Receive Buffer

4 Kbytes

User Define Buffer

12 Kbytes

Interface

USB V2.0 FS + Ethernet + Bluetooth V2.1 + EDR
* Bluetooth: Class 1 (100 m), MFi certified

Environment Characteristics

Temperature

Operating: 0 ~ 40°C (32 ~ 104°F)
Storage: -20 ~ 60°C (-4 ~ 140°F)

Humidity

Operating: 10 ~ 80% RH
Storage: 10 ~ 90% RH

Reliability

Printer Unit (MCBF)

70 Million Lines

Thermal Print Head (TPH)

150 km

Auto Cutter

1.8 Million Cuts

Software

Emulation

BXL / POS

Driver / Utility

OPOS Driver, Utility Program

SDK

iOS SDK, Android SDK

Fonts / Graphics / Symbologies

Character Size

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24
KOR, CHN, JPN: 24 x 24

Characters Per Line

Font A: 42 Font B, C: 56
KOR, CHN, JPN: 21

Character Sets

Alphanumeric: 95
Extended Graphics: 128 x 33 page
International: 32

Graphics

Supporting user-defined fonts, graphics,
formats, and logos

Barcode Symbologies

1D: Codabar, Code 39, Code 93, Code 128,
EAN-8, EAN-13, ITF, UPC-A, UPC-E
2D: PDF417, QR code



BR-SRP-350IIIBE-EN-MAR17-V1-NF Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON®

BIXOLON Co., Ltd.
+82 (0) 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

www.Bixolon.com

