
# Boca Systems Lemur-X

Kiosk Printer for Receipts and Tickets







### General

Print Method: direct thermal Print Speed: 8" per sec. maximum Resolution: 203 dpi (8 dots/mm) Size: 3.5" H x 4.25" W x 5.5" L

Weight: 1.8 pounds (excluding power supply) Operating Temperature: -10 to 45°C

### **Media Transport**

Media Type: roll or fanfold Ticket Thickness: .003" to .010" Ticket Width: 2.0" to 3.25"

**Positioning:** optical detector senses black mark at 1.5" from ticket edge

Ticket Separation: cutter

Optional Roll Holder: can be attached in 60 60 degree increments.

Roll: inner diameter - 1.5" minimum; outer diameter - 7.0" maximum

### Interfaces

Standard: Serial and USB

Optional: Ethernet, Bluetooth & Wi-Fi

### **Protocols**

Standard: FGL

Drivers: Windows, Mac and Linux

# **Power Requirements**

100-240 VAC, 50/60 Hz, 65W max Amp max 24 V DC, 2.5 Amp max

# **Environmental**

Relative Humidity: 10% to 90% Storage Temperature: -40 to 70°C above specs without condensation

### **Bar Codes**

Most 1D and 2D codes including PDF417 DataMatrix. QR. Aztec

Full speed printing of picket fence and ladder bar codes

### **Fonts**

Resident fonts: 16 bitmapped fonts (including Cyrillic and German characters) and Asian character sets (optional)

Downloadable fonts: HP Soft font /

TrueTypes fonts

Downloadable RAM: up to 27MB

Downloadable Flash: up to 12MB (optional)

# **Graphics**

FGL format, PCX format (1bit b/w), BMP format (1bit b/w)

# Web Interface (ethernet only)

Real-time status monitor Email notification

# **Projected Life**

Cutter: 1 million cuts Print Head: 60 km of paper or 100 million dot activations

**Bonus:** Free print head replacements when exclusively using Boca paper

## **Warranty**

Printer: 1 year, parts and labor

Print head: 90 days

Patents: BOCA has a patented head protection system that prevents premature head failure

# **Approvals**

UL/FCC/CE/CCC





