



## LUMDMU - Multiple Digital Message Unit

MAT #408184000

### Technical Specifications

<b>Message Capacity:</b>	Up to 99 messages can be placed in digital memory for queued replay
<b>Play Capacity:</b>	Program up to 8 messages to play in sequence with time delays
<b>Message Length:</b>	3 minutes 52 seconds
<b>Recording Options:</b>	Dial-up telephone, microphone interface, or tape input
<b>Delay Between Messages:</b>	5 seconds to 30 minutes
<b>Power Supply:</b>	115 VAC, 60 Hz, or 220 VAC, 50 Hz
<b>Fuse Ratings:</b>	AC Power: MDL 0.25 Amp Slo Blo; Battery: MDL 2.0 Amp Slo Blo
<b>Temperature Range:</b>	Operational: 0 to +40° C (32 to 104° F); Storage and Shipment: -40 to +66° C (-40 to +150° F)
<b>Humidity Range:</b>	5 to 95% noncondensing
<b>Altitude:</b>	Operational: Sea level to 10,000 feet Storage and Shipment: 40,000 feet max. shipment
<b>Environmental:</b>	Locate in area free of excess moisture, corrosive gases, dust, and chemicals
<b>Battery Backup:</b>	Allows up to 2 hours of operation during a power failure; total charge time 40 hours
<b>Frequency Response:</b>	-200 Hz to 3.4 kHz (+/- 3 dB)
<b>Output Level:</b>	Adjustable to a maximum of -9 dBm
<b>Input Impedance:</b>	Handset: 220 ohms Microphone: 600 ohms Tape: 10k ohms
<b>Voice Encoding:</b>	8 kHz sampling rate; 8 bits/sample (PCM)
<b>Interconnect Cable:</b>	50 pin, RJ-21 connector providing contact closure message starts
<b>Dimensions:</b>	16-1/4" W x 1-3/4" H x 9-1/4" D (without brackets); 19" W x 1-3/4" H x 9-1/4" D (with brackets)
<b>Product Weight:</b>	13 lb.

Specifications subject to change without notice. 9910