


Pegasus Floor Scale Systems

Calibrated with SBI-521 LED Indicator



- **Pre-calibrated to SBI-521 LED Indicator**
- **Easy Installation**– Units can be placed into service with no on-site installation required
- **Capacity and Size**– Match a capacity and size with SBI-521 LED indicator
- **A/D Conversion Rate**– Up to 25 measurements per second

VALUE IN
WEIGHING

Pegasus Floor Scale Systems Calibrated with SBI-521 LED Indicator

Capacities & Resolution

Capacity	Dimension-in.	Dimension-cm
2,000 x 0.5 lb 1,000 x 0.1 kg	36 x 36 x 3.1	91 x 91 x 7.9
5,000 x 1 lb 2500 x 0.5 kg	48 x 48 x 3.1 60 x 60 x 3.1	122 x 122 x 7.9 152 x 152 x 7.9
10,000 x 2 lb 5000 x 1 kg	48 x 48 x 3.1 60 x 60 x 3.1	122 x 122 x 7.9 152 x 152 x 7.9

All capacities and resolutions shown above are based on 5000d.

Product Code:

816965005345 - DCSB3636-02
816965005352 - DCSB4848-05
816965005369 - DCSB6060-05
816965005376 - DCSB4848-10
816965005383 - DCSB6060-10

SBI-521 LED Indicator

Display: 17 mm / 0.7" LED display

Construction: Heavy duty stainless steel IP65

Power: 6 volt 4 AH rechargeable internal lead acid battery with 110/220 AC internal transformer

Excitation Voltage: ± 5 VDC, 8 x 350 ohm load cells

Serial Port 1: Full-duplex RS-232

Serial Port 2: Full-duplex RS-232 or half-duplex RS-485

Digital Calibration: Front panel calibration and configuration

Keyboard: Hold/Setup, Print/Func, N/G/Total, Unit/Data, Tare/Preset, Zero/On/Off

Functions: Motion, Zero, Net, Gross, Tare, Total, lb, kg, %, pcs, oz, Peak/Hold, HI, OK, LO, AC/CHG

Units: kg, lb, lb:oz, PCS, %

Stand: Stainless steel swivel stand included

Display: Up to 50,000 graduations

Certifications: NTEP at 5,000d, Class III, CC #11-119

Floor Scale Specifications

Floor Scale: Mild steel

J-Box: Stainless steel

Finish: Powder coat paint

Rated: IP65

Certifications: NTEP COC #02-070

Load Cell Specifications

Material: Alloy tool steel potted

Rated Output: 3mv/V

Output Resistance: 350 ohm

Options



a division of Avery Weigh-Tronix, LLC

Brecknell

1000 Armstrong Dr., Fairmont, MN 56031
Toll free: 800-637-0529, Tel: 507-238-8702
Fax: 507-238-8271
e-mail: sales@brecknell scales.co.uk
www.brecknell scales.co.uk



Brecknell

Foundry Lane, Smethwick
West Midlands B66 2LP UK
Tel: +44 (0) 845 246 6717
Fax: +44 (0) 845 246 6718
Email: sales@brecknell scales.co.uk
www.brecknell scales.co.uk

