

# **ESA Series**

## **Economical Precision Balances**



- Accuracy

   Accurate to within ±2 division
   at full load
- Capacity— 150 to 6000 grams
- Construction

   Robust plastic housing,
   stainless steel top plate
- Display

   Large, clear 6 1/2 digits, 0.75"
   (19 mm) high 7-segment backlit LCD display

- Draft Shield—
   Supplied only with 150 g to 600 g units
- Power- AC and battery with auto off feature
- Operator Keys

   On/Off, Count, Cal, Tare, Mode, Units
- Platform- 150 g to 600 g capacities:
   4.65" (120 mm) diameter x 0.4" H (9.5 mm)

1500 g to 6000 g capacities: 6.9" W x 6.9" L x 0.3" H 175 mm (W) x 175 mm (L) x 8 mm (H)



### **ESA Series Economical Precision Balances**

#### **Features**

Through Salter Brecknell, Avery Weigh-Tronix combines years of precision weighing expertise with an economical alternative for what professionals demand from a balance.

With its fine feature set and simple functionality, the Salter Brecknell ESA series is the sensible response to almost any application, in any market sectors requiring an accurate precision weighing solution.

This alternative to premium priced analytical balances is ideal for general laboratory, industrial and educational applications requiring multiple weighing units.

The ESA series balances offer a quality balance at an affordable price. All models come standard with robust plastic housing and an AC adapter, and bi-directional RS232 interface allowing communciation to a PC.

External calibration



#### **Specifications**

**Capacity**– 150 g x 0.005 g, 300 g x 0.005 g, 600 g x 0.01 g, 1500 g x 0.02 g, 3000 g x 0.05 g 6000 g x 0.1 g

**Platform Size**— 150 g to 600 g capacities: 4.65" (120 mm) diameter x 0.4" H (9.5 mm) H

1500 g to 6000 g capacities: 6.9" W x 6.9" L x 0.3" H 175 mm (W) x 175 mm (L) x 8 mm (H)

Display– Front facing 6 1/2 digits, 0.75" (19 mm) high7-segment LCD display with blue backlit. Showsmultiple weighing units plus Cal and low battery indicator.

RS232- Bi-directional

Keyboard- On/Off, Count, Cal, Tare, Mode, Units

Units-g, oz, ozt, dwt, lb, ct, % pc

**Power**– 6 VDC, 200mA output with center negative, UL Approved A/C adapter 150-600 g units uses (6) AA batteries (not included) 1500-6000 g units uses (8) AA batteries (not included)

Battery Life- Approximately 15 hours

**Operating Temp**– 50° F - 95° F (10° C - 35° C)

Packaging Dimensions— 12.5" W x 10.25" D x 5.5" H 318 mm (W) x 261 mm (D) x 140 mm (H)

**Shipping Weight**– 150 g to 600 g units 3.1 lb (1.4 kg) 1500 g to 6000 g units 5.5 lb (2.5 kg)

Certifications- Full FCC compliance, UL/CUL power adapter





Salter Brecknell Weighing Products

1000 Armstrong Dr., Fairmont, MN 56031 Toll free: 800-637-0529, Tel: 507-238-8702 Fax: 507-238-8271

e-mail: sales@salterbrecknell.com www.salterbrecknell.com

