

LPS-15

Portable Bench Scale CE



Shown with optional foot switch

- **Accuracy**– 0.1% of full scale
- **Capacity**– 15 kg / 30 lb
- **Construction**– Low profile stainless steel platform with mild steel understructure, stainless steel/ABS indicator with wall bracket and desk mount included.
- **Platform Size**–
380 mm (L) x 305 mm (H) x 27 mm (W)
15" L x 12" W x 1" H
- **Display**– Five 16 mm / 0.625" digits LCD
- **Power**– Battery or AC power
- **Operator Keys**– On/Off/Zero, Tare, Units (lb, kg, lb/oz), Hold/Print,

LPS-15 Portable Bench Scale

Features

Portion control and product quality requirements make this economic scale perfect for use in pizza parlors, sandwich and salad shops, bakeries and supermarkets. Great for use in food operations to build consistent products and help control ingredient costs. Optional remote switch allows zeroing of the scale without using your hands.

The dual power modes (battery and AC adapter) enable portability or permanent installation (both included).

A large, simple to read display can be wall or stand mounted for easy visibility and the push button switches work with gloved hands (wall and desk mount included).

The indicator cable is a coil style for durability and easy extension to the wall or desk mount display.

The LPS-15 features a full-duplex RS-232 interface that can transmit and receive using a demand type protocol.

The durable low profile SST platform allows for easy weighing and cleanup. Although NOT suitable for washdown, this scale is perfect for an environment where wipe down sanitation is sufficient. The LPS-15 is a low cost, versatile and portable scale.



Shown with optional foot switch

Specifications

Capacity: 15 kg x .005 kg / 30 lb x 0.01 lb/0.2 oz

Platform Dimension:

380 mm (L) x 305 mm (H) x 27 mm (W)

15" L x 12" W x 1" H

Indicator:

164 mm (L) x 81 mm (H) x 29 mm (W)

6.5" L x 3.2" H x 1.2" W

Display: Five 16 mm / 0.625" digits LCD



RS-232: 10' interface cable (DB-9) (included)

Keyboard: On/Off/Zero, Tare, Units (kg/lb), Hold/Print

Units: lb, kg, lb/oz

Power: Four AAA batteries or 6 VDC, 500mA adapter (both included)

Optional Power Adapter:

816965002887: UK

816965002870: EU

Battery Life: 20 hours

Operating Temperature:

5° C to 35° C / 41° F to 95° F

Packaging:

Scale: 450 mm (L) x 400 mm (W) x 60 mm (H)

17" L x 15" W x 2.3" H

Packaging Contents: RS-232 cable, power adapter, four AAA batteries, manual, platform with indicator and stand with misc hardware

Shipping Weight: 5 kg / 11 lb

Optional: Foot Switch

Certifications: Full FCC compliance, UL/CUL power adapter

Product Code: 816965004799



a division of Avery Weigh-Tronix, LLC

Brecknell

1000 Armstrong Dr., Fairmont, MN 56031
Toll free: 800-637-0529, Tel: 507-238-8702
Fax: 507-238-8271
e-mail: sales@brecknellscales.com
www.brecknellscales.com



Brecknell

Foundry Lane, Smethwick
West Midlands B66 2LP UK
Tel: +44 (0) 845 246 6717
Fax: +44 (0) 845 246 6718
Email: sales@brecknellscales.co.uk
www.brecknellscales.co.uk

