Brecknell

LPS150 / LPS400

Portable Shipping Scale

CE

- **Accuracy–** 0.1% of full scale

- **Capacity–** 68 kg / 150 lb and 182 kg / 400 lb

- **Construction–** Low profile stainless steel platform with mild steel understructure, and stainless steel/ABS indicator with wall bracket and desk mount included.

- **Platform Dimension–** 380 mm (L) x 305 mm (W) x 27 mm (H) 15" W x 12" L x 1" H

- **Protocol–** Standard NCI interfaces to most common shipping software, including UPS™ Worldship Online. Not legal for trade

- **Display–** Five 16 mm / 0.625" digits LCD

- **Power–** Battery or AC power

- **Operator Keys–** On/Off/Zero, Tare, Units (lb/kg), Hold/Print

VALUE IN WEIGHING

LPS150 / LPS400 Portable Shipping Scale

Features

LPS150 / LPS400 scales are particularly suited to shipping/warehouse applications and general purpose weighing. These are very affordable scales with accurate weights up to 400 lbs.

The dual power modes (battery and AC adapter) enable portability or permanent installation (both included).

A large, simple to read display can be wall or stand mounted for easy visibility and the large keyboard switches work with gloved hands (wall and desk bracket included).

The indicator cable is a coil style for durability and easy extension.

The LPS Series features RS-232 interface that can transmit and receive using a demand type protocol.

Scale comes standard with NCI protocol and interfaces to most common shipping software, including UPS™ Worldship Online.

A durable low profile platform allows for easy weighing. The LPS Series is a low cost yet versatile and portable scale.

Application – Shipping/Receiving
– Mailroom
– Manifest Systems
– General Purpose Weighing

Not legal for trade

Specifications

Capacity:
68 kg x 0.02 kg / 150 lb x 0.05 lb / 150 lb x 1 oz)
182 kg x 0.1 kg / 400 lb x 0.2 lb / 400 lb x 5 oz

Platform Dimension:
380 mm (L) x 305 mm (W) x 27 mm (H)
15" W x 12" L x 1" H

Indicator: 164 mm (L) x 81 mm (H) x 29 mm (W)
6.5" L x 3.2" H x 1.2" W

Display: Five 16 mm / 0.625" digits LCD

RS-232: 10' interface cable (DB-9) (included)

Keyboard: On/Off/Zero, Tare, Units (kg/lb), Hold/Print

Units: lb, kg, lb/oz

Power:
North America: Four AAA batteries or 6 VDC, 500mA adapter (both included)

Optional Power Adapter:
816965002887: UK
816965002870: EU

Battery Life: 20 hours

Operating Temperature: 5° C to 35° C / 41° F to 95° F

Packaging Dimension:
Scale: 450 mm (L) x 400 mm (W) x 60 mm (H)
17" L x 15" W x 2.3" H

Shipping Weight: 5 kg / 11 lb

Certifications: Full FCC compliance, UL/CUL power adapter

Product Code:
LPS150: 816965001224
LPS400: 816965001231