SBrecknell

SBI-505





- **Display Resolution** Up to 30,000
- Internal ADC- 2,000,000
- Load Cell Capability- 6 @ 350 ohm
- **Construction** Painted mild steel with stainless steel desk stand

- Finish- Powder coat paint
- Time and Date- Standard
- RS-232– Standard DB9 connection
- Rated- IP65
- Function- Checkweighing, count, weight, total and print



SBI-505 Indicator

Specifications

Construction: Painted mild steel with stainless steel desk stand or wall mount stand Dimensions: 47 mm (W) x 220 mm (L) x 149 mm (H) 1.875" W x 8.675" L x 5.875" H Finish: Powder coat paint Rated: IP65 Load Cell Capability: 6 @ 350 ohm Excitation: 5 VDC Internal ADC: 2,000,000 Display Resolution: up to 30,000 Display: Six digit 20 mm (0.8") high red LED Annunciators: -0-, motion, Gross, Net, tared, Total, pcs, lb, kg, Lo, OK, Hi Interface Cable Connectors Included Optional 15' Interface Cable: AWT05-505848 **Optional Power Supply:** AWT05-505962: EU PSU AWT05-505961: UK PSU

RS-232: Female DB9 connection
Time and Date: Military format
Operator Keys: On/Off, Total, Count, kg/lb, Gross, Tare, Zero, Print
Operating Temp: -10° C to 40° C (14° F to 104° F)
Power: 120/220VAC 60Hz/50Hz Output: 9 VDC - 12 VDC center positive
Calibration: Front panel accessible
Accuracy: NTEP at 5,000 divisions, Class III
Shipping Weight: 1.7 kg (3.75 lb)
Packaging Dimensions: 279.5 mm (L) x 184 mm (W) x 266.5 mm (H) 11" L x 7.25 W x 10.5 H
Certifications: NTEP CC #11-082
Product Code: AWT05-505729

Packaging Contents: Indicator, stand, power supply, manual, RS-232 connector, lead seal, load cell connector and knobs

Options









a division of Avery Weigh-Tronix, LLC

Brecknell

1000 Armstrong Dr., Fairmont, MN 56031 Toll free: 800-637-0529, Tel: 507-238-8702 Fax: 507-238-8271 e-mail: sales@brecknellscales.com www.brecknellscales.com



Brecknell

Foundry Lane, Smethwick West Midlands B66 2LP UK Tel: +44 (0) 845 246 6717 Fax: +44 (0) 845 246 6718 Email: sales@brecknellscales.co.uk www.brecknellscales.co.uk



