



## OEM SmartTerminal SR-4044

PCMCIA Smart Card Terminal



### Key benefits

High Quality PCMCIA smart card terminal for insertion into notebooks

PC/SC  
EMV  
CT-API support  
OCF compatible

### High Performance

Smart Card Interface supports maximal smart card speed

### Approvals

cULus  
WHQL  
EMV 2000 Level 1

## Technical Data

### Host Interface

PCMCIA with 16 Mbps

### Smart Card Interface

Reads and writes all ISO 7816 cards  
Supports T=0, T=1  
I<sup>2</sup>C (S=8), SLE4044,  
2-wire SLE4432/42 (S=10)  
3-wire SLE4418/28 (S=9)

### PC/SC Driver Support

Windows XP, 2000, 98, ME, NT 4.0  
Windows CE3.0 / CE.NET (Hardware dependant)  
Linux

All drivers available upon request

### Card Power Supply

60 mA max.

### Card Connecting Unit

Approx. 100,000 insertions

### Smart Card speed

Up to 413 Kbps (when supported by card)

### Smart Card clock

Up to 8 MHz

### Packaging Unit

100 readers per box

### Warranty period

2 years

Cherry Electrical Products  
11200 88<sup>th</sup> Avenue  
Pleasant Prairie, WI 53158  
Phone: 262.942.6500  
Hotline: 800.510.1689  
Fax: 262.942.6566  
Internet: [www.cherrycorp.com](http://www.cherrycorp.com)

The manufacturer assumes no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

©2004 Cherry Electrical Products