

Integrated Security Devices

ST-1210 Smart Terminal Smart Card Reader



**Smart Card Reader
with USB Interface**

Main Applications

Desktop

Access Control
Logical and Network Logon
Single Application Sign-On
Convenient Replacement for Passwords
3-Factor Authentication
Loyalty and Multi-Application Cards
PKI (Private Key Infrastructure)
Digital Signature
Document Encryption
Secure Payment for B2B and B2C

Target Markets

Public Administration
E-Government
Military (CAC)
Border Control
Transportation
Education
Financial
Point-of-Sale

Key Features

- Smart Card reader with USB interface
- One-hand operation with stable stand
- PC/SC smart card reader
- CT-API and OCF support
- T=0, T=1, S=8, S=9 and S=10 protocols
- CCID compatible
- EMV 2000 terminal Level 1-approved
- USB 2.0 compatible

ST-1210 Smart Terminal

Smart Card Reader



Technical Data

Smart Card interface:

- Reads and writes all ISO 7816 cards
- Supports T=0, T=1, I²C (S=8), 2-wire (S=10), 3-wire (S=9)

Drivers:

CCID, PC/SC, CT-API

Card connecting unit:

Approx. 100,000 insertions
sliding contacts

Smart Card speed:

412,903 bps

Clock frequency smartcard:

4.8 MHz

Weight:

Approx. 80 g

Dimensions:

Approx. 105 x 70 x 12 mm

Cable length:

Approx. 1.75 m

Current consumption:

Max. 100 mA

Interface:

USB, 2.0

Storage temperature:

-20 °C to 50 °C

Operating temperature:

0 °C to 60 °C

Delivery volume

1 Smart Terminal

Packaging unit:

Bulk: 250 pcs. per master carton
4 cartons per pallet (1000 pcs.)

Retail: 40 pcs. per master carton
12 cartons per pallet (480 pcs.)

Approvals

GS/VDE, cRUus, CE, FCC,
C-Tick Mark, GOST-R

Microsoft WHQL Windows™ 2000,
XP, Vista

EMV 2000 Level 1

Operating systems

Windows 2000, XP, XP 64Bit, Vista,
Vista 64, Linux

System requirements

USB Interface

Guarantee period:

2 years

Ordering Description

Order Number	Housing	Packaging	Language Packaging
SST-1210UAF	light grey	bulk	—
ST-1210UAE	black	bulk	—
ST-1210UDE-R	black	retail	german / english

Contact

Call, fax or visit our
website for more information.

ZF Electronics Corporation

11200 88th Avenue
Pleasant Prairie, WI 53158

Phone: 262.942.6500
Web: www.cherrycorp.com

E-Mail: keyboardsupport@zf.com
Fax: 262.942.6566

The manufacturer accepts no
liability for errors or non-availability,
and reserves the right to change
specifications without prior notice.

Technical data relates to product
specifications only. Features may
differ from those described.
Only drawings combined with
product specifications shall be
deemed binding.

Last Update: 2/15/10

© 2008 ZF Electronics Corporation