

SPECIFICATIONS

711/8110

Mobile Computer



		711	8110
Communication	Serial	RS232/Serial IR/IrDA	RS232/Serial IR/IrDA
	Wireless option	–	Narrow band (433 MHz)
	Coverage	–	200M line of sight
Power	Operation battery	Two AAA alkaline / rechargeable	
	Backup battery	Rechargeable lithium 3.0V, 7.0mAh	
	Working time (with AAA alkaline)	100 hours	20 hours
General Characteristics	CPU	16-bit CMOS, low power consumption	
	Program memory	1MB flash memory	
	Data memory	1MB/2MB SRAM	256K SRAM
	Display	128x64 graphic dots FSTN with LED backlight	
	Keypad	21 rubber keys with LED backlight	
	Buzzer	Programmable, 1KHz to 4 KHz	
	LED	Dual color, red and green	
Dimensions	Size L x W x H (mm)	145 x 63 x 33.5	175 x 63 x 42
	Weight including battery	180 g	210 g
Scanner	Light source	Linear imager: 650 nm red LED Laser: Visible laser diode operating at 670 ± 15 nm	
	Scan rate	Linear Imager: 100 scans per second Laser: 36 ± 3 scans per second	
	Scan angle	Laser: 42° nominal	
	Depth of field	Linear Imager: 6~13cm Laser: 2~70 cm depends on barcode resolution	
	Resolution	0.075mm (3 mil) ~1.375 mm (55 mil)	
Environmental	Operating temperature	-20°C to 60°C	
	Storage temperature	-30°C to 70°C	
	Humidity	Non-condensed 5% to 95%	
	Impact resistance	1.2 m drops onto concrete	
	EMC regulation	FCC class-A, CE and C-Tick approved	
Programming		C, BASIC, Windows-based Application Generator	
RF station		–	Base station with mounting bracket
Accessories		RS232 cable, communication cradle, battery charger, rechargeable battery pack	
Warranty		1 year	

ACCESSORIES



Battery Charger



Communication Cradle



Base Station With Mounting Bracket (3510)



©2006 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All trademarks and trade names are those of their respective owners.



HEADQUARTERS
CipherLab Co., Ltd.
 12F, 333 Dunhua S. Rd., Sec. 2
 Taipei, Taiwan 106
 Tel +886 2 8647 1166
 Fax +886 2 8732 2255
 www.cipherlab.com

CipherLab China
 Suite 1305, 1065A, Jaojiabang Rd.
 Xuhui District, Shanghai,
 China 200030
 Tel +86 21 3368 0288
 Fax +86 21 3368 0286

CipherLab USA
 2552 Summit Avenue
 Plano, Texas USA 75074
 Tel +1 469 241 97799
 Toll Free 888 300 9779
 Fax +1 469 241 0697

CipherLab EMEA
 Airedale House
 Clayton Wood Rise
 Leeds, LS16 6RF, UK
 Tel +44 113 274 7823
 Fax +44 113 274 7822