

# CRx Desktop Thermal Printer



## Prescription Label and Monograph Printers



## Cost-effective printing solutions for the pharmacy.

With more scripts to fill, more tasks to complete, and less manpower available, workflow improvement and cost management have never been more important. CognitiveTPG's CRx printing solution benefits chain and independent pharmacy operations through:

- Reduced cost of ownership -- no toner or expensive label forms
- Increased reliability and easy maintenance
- Fast print performance (no warm-up time required) and high quality script printing
- Quiet operation in an unobtrusive and small footprint (1/4 the size of a laser printer)
- Easy integration -- includes laser printer emulation and compatibility with leading pharmacy systems
- Network ready -- includes Ethernet connectivity

# COGNITIVE TPG

800.732.8950  
sales@CognitiveTPG.com  
www.CognitiveTPG.com

# CRx

## Cost-Effective Printing Solutions for the Pharmacy

### 2" AND 4" MODELS

### Technical Specifications

|                                      | 2" Model   | 4" Model   |
|--------------------------------------|--|--|
| PRINT                                |  |  |
| Method                               | Direct Thermal or Thermal Transfer   | Direct Thermal or Thermal Transfer                 |
| Width (max)                          | 2.205" (56 mm)   | 4.153" (105.5 mm)                                  |
| Length (max)                         | 218" (5537 mm)   | 218" (5537 mm)                                     |
| Speed (max)                          | 6 ips (152 mm/sec) w/LCD display   | 6 ips (152 mm/sec) w/LCD display                   |
| Resolution                           | 300 dpi (12 dpmm)  | 300 dpi (12 dpmm)                                  |
| MEDIA                                |  |  |
| Width                                | 0.75 - 2.84" (10 mm - 72 mm)   | 2.4" - 4.63" (50 mm - 117 mm)                      |
| Roll Diameter (max)                  | 8" (203 mm)  | 8" (203 mm)  |
| Ribbon Length (max) (TT models only) | 6500" (165 m)  | 5500" (140 m)                                      |
| Indexing                             | Continuous, gap, black bar, black mark, notch/hole   | Continuous, gap, black bar, black mark, notch/hole |
| BAR CODES                            | Add2, Add5, Codabar, Code39, Code93, Code 128A/B/C, D2of5, I2of5, S2of5, EAN8, EAN13, EAN128, MSI/I1, Plessey, Postnet, UPCA/A+/E/E1   |  |
| FONTS                                |  |  |
| Bitmapped                            | 7 styles with up to 10x10 magnification, variable boldness and spacing   |  |
| International                        | Sans serif font in 7 pt. sizes, up to 4x4 magnification, variable boldness and spacing   |  |
| Scalable Smooth Fonts                | 3 Ultra Font styles for smooth characters in any size and boldness   |  |
| Laser Printer Emulation              | Standard: Courier, Univers, Arial, and Times New typefaces   |  |
| Rotations                            | 0, 90, 180, 270 degrees  |  |
| Optional                             | Kanji, Korean, and OCR fonts available   |  |
| GRAPHICS                             | PCX and BMP formats  | PCX and BMP formats                                |
| MEMORY                               | RAM - 16 MB, Flash - 8 MB  | RAM - 16 MB, Flash - 8 MB                          |
| COMMUNICATIONS                       | USB-A/B, Serial or Parallel, Ethernet (internal)   | USB-A/B, Serial or Parallel, Ethernet (internal)   |
| REAL-TIME CLOCK (RTC)                | Standard, All Models   | Standard, All Models                               |
| ELECTRICAL                           | Auto-ranging 100-240VAC, 50-60 Hz, 24VDC output  | Auto-ranging 100-240VAC, 50-60 Hz, 24VDC output    |
| ENVIRONMENTAL                        | Operates at 41°F to 104°F (5°C to 40°C)  | Operates at 41°F to 104°F (5°C to 40°C)            |
| DIMENSIONS                           |  |  |
| Width                                | 5" (127 mm)  | 6.9" (175 mm)                                      |
| Height                               | 7.1" (181 mm)  | 7.1" (181 mm)                                      |
| Depth                                | 10.04" (255 mm)  | 10.04" (255 mm)                                    |
| WEIGHT (DT/TT)                       | 5.02 lbs. (2.28 kg) / 5.23 lbs. (2.38 kg)  | 5.91 lbs. (2.69 kg) / 6.10 lbs. (2.77 kg)          |
| ACCESSORIES                          | Start-up guide, power supply and cord, Window's driver, programmer's guide, NiceLabel design software, 8" OD media roll adapter, USB cable. Optional communication cables available separately |  |
| WARRANTY                             |  |  |
| Printer                              | 24 months from date of purchase (requires registration and excludes printhead)   |  |
| PROGRAMMING LANGUAGE                 | Laser printer emulation (PCL5)   |  |

#### CognitiveTPG Headquarters

25 Tri-State International, Suite 200, Lincolnshire, IL 60069  
Toll Free: 800-732-8950 Phone: 847-383-7900 Fax: 847-383-7949  
www.CognitiveTPG.com  
Copyright 2008 CognitiveTPG. All Rights Reserved.



280-0008-01-1108