



## Superior Technology & Capabilities

- Ultra Compact and Light Weight
- Anti-Grip with Tri-Axis Bracket

## CDD480F43 Dome Camera Specification Sheet



## Camera Features

<b>Sensor</b>	1/3" Interline Sony CCD
<b>Effective Pixels</b>	NTSC: 771 (H) x 492 (V)
<b>Sensitivity</b>	1.0 Lux
<b>Resolution</b>	More than 480 TVL
<b>Video Output</b>	1V p-p composite video via 75Ω
<b>Signal to Noise Ratio</b>	More than 48dB (AGC Off)
<b>Shutter Control</b>	AES 1/60 – 1/100,000 sec.
<b>Gamma Correction</b>	0.45
<b>Auto White Balance</b>	Auto: 2600 ~ 10000° K
<b>Scanning System</b>	2:1 Interlace
<b>AGC</b>	Automatic
<b>Backlight Compensation</b>	Automatic
<b>Synchronisation System</b>	Internal



Global Surveillance Management Solutions

[www.digiop.com](http://www.digiop.com)

## SPECIFICATIONS

# CDD480F43

---

### Lens Options

Lens Mount and Focus	Fixed Lens 4.3mm
----------------------	------------------

---

### Power Supply

Power Source	DC 12V +/- 10%
Consumption	90mA
Power Indicator	LED

---

### Mechanical

Dimension (OxDxH)	80x110x70 mm
Weight	430 g (15.16oz)
Material	Plastic

---

### Environmental

Operating Temperature	-10° C ~ 50° C
Storage Temperature	-20° C ~ 60° C



**Global Surveillance Management Solutions**

General Solutions, Ltd. 5902 Sovereign Dr., Houston, TX 77036 Toll Free (800) 968-3606 Phone (713) 333-4900 Fax (713) 333-4925  
© 2007 General Solutions, Ltd. DIGIOP is a registered trademark of General Solutions, Ltd. All rights reserved.  
All Information subject to change without notice. Intel, Dell, and others are trademarks and are property of their respective owners.

[www.digiop.com](http://www.digiop.com)

CDD480F43\_4.2.07