DIGIOP TRU PIX MiniDome CTD480XV39



CTD480XV39 TRU PIX MiniDome Camera Specification Sheet



Superior Technology & Capabilities

- Extreme Dynamic Range
- Zero Smear
- High Resolution 480 Lines
- Integrated 3~9mm, Varifocal Lens
- 3-Axis Gimbal
- Ceiling/Surface Mount
- Extra Video-Out for Local Focusing

Camera Features

Sensor Digital Image Sensor

Video Processing DSP™ Technology Effective Pixels 720 (H) x 540 (V)

Sensitivity 1.0 lux; for usable picture (40%video) with AGC on; lens at F1.2, no bubble

Resolution 480 TVL (H) x 400 TVL (H)

Video Output 1V p-p composite video via 75Ω BNC connector, plus extra video output on front for

optional service connector

Signal to Noise Ratio Better Than 48dB

Auto White Balance 2,500K ~ 9,500K; Pro: 2,800K~6,500K / Wide: 2,500K~9,500K

AGC Digital

 $\textbf{Electronic Iris} \quad 1/50 s{\sim}1/100,000 s; \ On \ / \ Off$

Backlight Compensation 38k grid/Automatic Configuring

Gamma Correction 0.45

Synchronisation System Internal or Line lock (0~360° adjustment)



SPECIFICATIONS

CTD480XV39

Lens Options

Lens Mountand Focus Integrated 3~9mm Varifocal with DC Iris, F1.2

Power Supply

Low Voltage Source AC: 24V - 15% + 15% @ 50Hz DC: 12V - 10% + 15%

Consumption Less Than 3.4W Normal Use Input Connection 2-Way Screw Terminal Connection

Mechanical

Dimension (LxWxH) 4.72x4.72x4.33 in (120x120x110mm)

Weight Unit: 10.58oz (0.3kg), Shipping: 14.11oz (0.4kg)

Material Grey ABS, Clear Polycarbonate Bubble

Installation Mount Ceiling: via Integral Fixing Clamps (Removable Shroud)

Surface: via Fixing Screws Provided

Environmental

Operating Temperature
Operating Humidity
Storage Temperature
Operating Humidity

 $-10^{\circ}\,\text{C} \sim 40^{\circ}\,\text{C} (14^{\circ} - 104^{\circ}\text{F})$


20% to 80% Relative Humidity, Non Condensing

 -20° C $\sim 70^{\circ}$ C (-4° - 140° F)

lity 20% to 90% Relative Humidity, Non Condensing



3-Axis Gimbal (Shown Here with Ceiling Mount)



Rear View of Dome Base



General Solutions, Ltd. 5902 Sovereign Dr., Houston, TX 77036 Toll Free (800) 968-3606 Phone (713) 333-4900 Fax (713) 333-4925 © 2007 General Solutions, Ltd. DIGIOP is a registered trademark of General Solutions, Ltd. All rights reserved.

All Information subject to change without notice. Intel, Dell, and others are trademarks and are property of their respective owners.