

DIGIOP TRU PIX MiniDome CTD540V39



CTD540V39 TRU PIX MiniDome Camera Specification Sheet



Superior Technology & Capabilities

- Compact and Light weight design
- Integrated 3~9mm Vari-focal Direct Drive Lens allows for Easy installation
- Hi-speed F1.5 Iris Provides Excellent Low Light Performance
- Digital Pixel System (DPS®) Imaging
- DPS® controls for Back Light Compensation, White Balance, and Gain Control
- Video cable with BNC included

Camera Features

Sensor	1/3" Sony Super HAD CCD™
Video Processing	DSP
Effective Pixels	752 (H) x 582 (V)
Sensitivity	0.7 lux; for usable picture (40%video) with AGC on; lens at F1.2, no bubble
Resolution	540 TVL
Video Output	1V p-p composite video connector, plus extra video output on front for optional service connector
Signal to Noise Ratio	50dB
Auto White Balance	2,500K ~ 9,500K
AGC	On / Off, max <28dB
Electronic Iris	1/50s~1/100,000s; On / Off
Backlight Compensation	On/Off center weighted
Gamma Correction	0.45
Synchronisation System	Internal or Line lock (±180° adjustment)



Global Surveillance Management Solutions

www.digiop.com

SPECIFICATIONS

CTD540V39

Lens Options

Lens Mountand Focus Integrated 3~9mm Varifocal with DC Iris, F1.2

Power Supply


Low Voltage Source AC: 24V -15% +33% @ 60Hz DC: 12V - 10% +15%
Consumption Less Than 3.4W Normal Use
Input Connection 2-Way Screw Terminal Connection

Mechanical


Dimension (LxWxH) 4.72x4.72x4.33 in (120x120x110mm)
Weight Unit: 10.58oz (0.3kg), Shipping: 14.11oz (0.4kg)
Material Grey ABS, Clear Polycarbonate Bubble
Installation Mount Ceiling: via Integral Fixing Clamps (Removable Shroud)
Surface: via Fixing Screws Provided

Environmental

Operating Temperature -10° C ~ 50° C (14° - 122°F)
Operating Humidity 20% to 80% Relative Humidity, Non Condensing
Storage Temperature -10° C ~ 70° C (14° - 158°F)
Operating Humidity 20% to 90% Relative Humidity, Non Condensing



3-Axis Gimbal
(Shown Here with Ceiling Mount)



Rear View of Dome Base



Global Surveillance Management Solutions

General Solutions, Ltd. 5902 Sovereign Dr., Houston, TX 77036 Toll Free (800) 968-3606 Phone (713) 333-4900 Fax (713) 333-4925
© 2007 General Solutions, Ltd. DigiOP is a registered trademark of General Solutions, Ltd. All rights reserved.
All Information subject to change without notice. Intel, Dell, and others are trademarks and are property of their respective owners.

www.digiop.com

CTD540V39_4.2.07