DLI 8800 mobile POS tablet

retail • field service • hospitality restaurant • roaming agent

Intel® Atom processor	7" outdoor screen	barcode scanner	magstripe	contactless payment (rfid)	WLAN, WWAN, WPAN

Take payment & mobile computing directly to your customers, no matter where they buy!

The DLI 8800 mobile POS tablet is the ideal rugged device for use in a wide variety of mobile environments including:

- Retail & concession sales in sports stadiums, amusement parks, hotels and resorts

- Mobile payment of in-home repairs, up-sells and field services

- instantly deployable return counters and POS kiosks for use during peak retail seasons

- Delivery verification & signature capture in route accounting and home delivery/sales

In the store. At the customer's home. Pool side, court side or at the front gate. Wherever payment gets taken or retail business gets done, that's where you'll find the DLI 8800 rugged mobile POS tablet. With our revolutionary 3-in-1 payment feature - combining magstripe, barcode scanning and contactless payment - the DLI 8800 is the perfect device from which to conduct retail transactions both indoors and out.

Built around an outdoor readable 7" LED backlit display, the IP54-rated DLI 8800 shares the same rugged heritage as the rest of the DLI-line of rugged tablet and in-vehicle computers. Powered by an industrial-class version of Intel's® low-power Atom processor, the 8800 sports either a shock mounted or solid state storage device, up to 2GB of memory, and a variety of I/O connectivity ports.

Whether it's line busting, mobile payment, age verification, roaming customer service, or field sales, the POS-ready DLI 8800 rugged POS tablet can help you increase sales, improve efficiency, and differentiate yourself from the competition. Call DLI at (800) 526-1299 for more information.

designed manufactured serviced **USA**

dust   water   drop   vibration   extreme temps   wireless

Intel® Atom processor • 7" indoor/outdoor touchscreen
Barcode scanner • Magstripe • Contactless payment (rfid)
WLAN • WWAN • WPAN • VoIP

System

- **Casing -** Impact-resistant ABS+PC polymer, IP54 rated, multiple 4ft drops to bare concrete
- **Processor -** Intel® Atom Industrial Version Z530 1.6Ghz
- **Chipset -** Intel System Controller Hub US15W, L2 Cache: 512KB, FSB: 533Mhz
- **Display -** 7" LCD 375NIT LED Backlit indoor/outdoor readable, 1024 X 600 Resolution, Contrast Ratio: 400: 1
- **Touchscreen –** Digitizer or Resistive (standard or polarized), Industrial rated @ 3 million touches in a single location
- **Video -** 256MB RAM
- **Audio -** Intel High Definition Audio; Integrated speaker
- **Memory -** 2GB DDR2 SODIMM 533Mhz
- **Storage -** HDD: 1.8" 60GB or 80GB Shock Mounted
    - SSD: 8GB, 16GB, 32GB, 64MB Industrial
- **Operating System -** Vista® Business, XP® Pro, XP® Tablet, Windows® Embedded Standard, Windows ® 7, Linux 2.6 (Ubuntu)
- **Ports -** (2) USB 2.0 Connectors, (1) RS232 Port (+5V on Pin9), (1) Ethernet 10/100/1000, (1) Spring Probe Pass through connector to cradle (2-USB, 1-RS232, 1-10/100/1000 Ethernet, 1-VGA), (2) Spring Probe RF Pass through connectors to cradle
- **Barcode Scanner –** Integrated Honeywell™ Adaptus Imager (JPOS-Compliant) (Optional)
- **Magstripe Reader –** Integrated 3 track, Single Head (OPOS/JPOS-Compliant)
- **RFID –** Integrated Reader ISO14443 A/B, ISO15693 (Optional)
- **Keys -** (6) Programmable Keys, (2) Barcode Scanner Keys (L & R side)
- **Biometric -** Access Control / Mouse Function

Environmental

- **Temperature -** Operating -4^{0}F to +122^{0}F (-20^{0}C to ^{0}C); Storage -7^{0}F to 140^{0}F (-22^{0}C to 60^{0}C)
- **Impact -** Multiple 4ft drops to bare concrete
- **Vibration -** 5~500Hz 1G PTP
- **Shock -** Operating -20G, (11ms), Non Operating -40G (11ms), Crash -75G (11ms)
- **EMI/EMC -** FCC Class B, CE
- **Water/Dust -** IP54, Dust - (limited ingress), Water - (Protected against sprays from all directions - limited ingress permitted)

Physical

- **Dimensions -** H – 6.29" (160mm), W – 8.26" (210mm) D-1.41" (36mm)
- **Weight –** 2.3 lbs. (with battery pack)
- **Warranty -** Standard One Year. Available No-Fault Service Coverage
- **WiFi -** 802.11b/g/n WiFi Radio (Cisco® CCX5) Standard 802.11a/b/g/n WiFi Radio (Cisco® CCX5) Optional
- **WWAN -** Integrated Cellular Card including support for External Antenna through Vehicle Cradle. Available cellular carriers included Verizon®, Sprint®, AT&T/Cingular®, T Mobile® (Optional)
- **Bluetooth -** Class 2 radio (Optional)
- **Voice Communications -** VoIP, Integrated Dual microphones
- **Power -** Battery Pack: 2600mAh Lithium Lon Battery (4hrs of usage) *depending on configuration
- **AC Adapter -** 19VDC 120Watt 110/220 VAC 50/60 Hz Input (Multi-Country Line Cords Available)

Accessories

- **Desktop / Vehicle Cradle -** 8hr Battery Pack Option, (2) External RF Antennas, locking mechanism with port replicator, (1) RS232, (2) USB 2.0, (1) 10/100/1000, (1) VGA, (1) K-Lock.
- 3-Bay Battery Charger, Cigarette Lighter Power Adapter, Handle, Shoulder Strap.

Information in this document is subject to change without notice.

intel Centrino® Atom™ inside™   CISCO Compatible   RoHS compliant   No-Fault dli SERVICE   designed manufactured serviced USA

computing without boundaries

shipping: 703 data ltd parkway laporte, indiana 46350 • mail: p.o. box 761 laporte, indiana 46352
toll free: 800.526.1299 • fax: 219.362.1937 • www.dataltd.com