# GRYPHON™ I GD4500 2D



## Premium hand held scanner for general purpose applications



#### **IMAGING TECHNOLOGY**

The Gryphon<sup>™</sup> 4500 series represents the premium range of hand held scanners from Datalogic for general purpose applications. Designed with people in mind, the Gryphon I GD4500 imager stands out with an elegant and trendy design, unchallenged ergonomics and features the most advanced Megapixel sensor with white-illumination 2D technology for outstanding performance.

### TOP TECHNOLOGIES FOR TODAY'S POS

Perfect for both hand held and presentation reading, the Gryphon I GD4500 imager exploits Datalogic's Motionix $^{\text{TM}}$  motion-sensing technology which detects the natural actions of the operator to automatically switch the scanner into the desired scanning mode. This technology works with or without the use of a stand, offering more operational choices. Both the aimer and sensor can be programmed to the user's desired preferences.

Datalogic distinctive reading technology with highly visible whiteillumination is easier on the human eyes and reads colored labels better. The highly visible 4-Dot aimer defines a precise reading zone and reduces accidental reads, while the aimer's center cross provides a locator for targeted scanning in a multiple bar code environment.

#### SIMPLE TO USE AND DEPLOY

The Gryphon I GD4500 omnidirectional imager provides snappy reading performance on all common 1D and 2D codes as well as postal, stacked and composite codes like PDF417. High Density (HD) models are also available for reading smaller, condensed codes. A dedicated version with red illumination optics reads Digital Watermarking.

For mobile marketing or ticketing applications, this imager also offers excellent performance when reading bar codes from mobile devices. The enhanced optics offer improved motion tolerance and high speed imaging to read fast moving codes.

## READY TO BE REGULARLY CLEANED AND DISINFECTED

Most of the working environments now have requirements that scanners need to be regularly cleaned and disinfected. The Gryphon 4500 series exploits Disinfectant-Ready enclosures, designed to withstand regular daily cleaning with harsh disinfectant solutions commonly used in a healthcare environment.

### **FEATURES**

- 1 MP optics for superior scanning and Depth Of Field
- Datalogic distinctive technology with highly visible white-illumination and 4-Dot aimer with center cross for targeted scanning
- Datalogic's patented 'Green Spot' technology and exclusive 3GL™ (3 Green Lights) for superior good-read feedback
- $\bullet$  Motionix  $^{\text{TM}}$  motion-sensing technology for seamless reading mode transitions
- · Omnidirectional reading
- · Advanced motion tolerance optics
- Image capture and document scanning capabilities
- Reads 1D, 2D, postal codes, stacked and composite bar codes and dot codes
- Digital Watermark reading on specific models/applications
- Multi-interface options: USB-only or multi-interface RS-232 / USB / Keyboard Wedge
- Disinfectant-Ready enclosures withstand daily cleaning with harsh disinfectant solutions.
- Specific black models with enclosures treated with anti-microbial additives available (ISO22196 compliant)
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

#### **INDUSTRY - APPLICATION**

- · Retail Point of Sale
- Light Manufacturing
- Healthcare: in laboratories,
   pharmacies and in-room patient care
- Access Control, Transportation and Entertainment
- Commercial Services: Postal, Banks, Public Administration, Utilities















### GRYPHON™ I GD4500 2D

## TECHNICAL SPECIFICATIONS

DECODING CAPABI	LITY
1D / Linear Codes	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
2D Codes	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code; Dot code
Postal Codes	Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)
Stacked Codes	EAN/JAN Composites; GS1 DataBar Composites; GS DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites
Digital Watermarking	Digimarc Barcodes
ELECTRICAL	
Current	Operating: <400 mA @ 5V; < 400 mA @ 12V Standby/Idle: < 90 mA @ 5V; <50 mA @ 12V
Input Voltage	GD4520: 5 VDC GD4590: 4.5 - 14.0 VDC
ENVIRONMENTAL	
Ambient Light	0 - 100,000 lux
Drop Resistance	Withstands repeated drops from 1.8 m / 6.0 ft onto a concrete surface.
ESD Protection (Air Discharge)	16 kV
Humidity (Non-Condensing)	0 - 95%
Particulate and Water	
Sealing	IP52
Sealing Temperature	IP52
Temperature	Operating: 0 to 50 °C / 32 to 122 °F
Temperature INTERFACES Interfaces	Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F GD4520: USB only GD4590: RS-232 / USB / Keyboard Wedge Multi- Interface
Temperature INTERFACES Interfaces	Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F GD4520: USB only GD4590: RS-232 / USB / Keyboard Wedge Multi- Interface
Temperature INTERFACES Interfaces	Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F GD4520: USB only GD4590: RS-232 / USB / Keyboard Wedge Multi- Interface
Temperature INTERFACES Interfaces PHYSICAL CHARAC	Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F GD4520: USB only GD4590: RS-232 / USB / Keyboard Wedge Multi- Interface
Temperature INTERFACES Interfaces PHYSICAL CHARAC Colors Available	Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F  GD4520: USB only GD4590: RS-232 / USB / Keyboard Wedge Multi- Interface  TERISTICS  Black; White  16.6 x 6.8 x 10.9 cm / 6.5 x 2.7 x 4.3 in
Temperature INTERFACES Interfaces PHYSICAL CHARAC Colors Available Dimensions	Operating: 0 to 50 °C / 32 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F  GD4520: USB only GD4590: RS-232 / USB / Keyboard Wedge Multi- Interface  TERISTICS  Black; White  16.6 x 6.8 x 10.9 cm / 6.5 x 2.7 x 4.3 in In Stand: 21 x 7.5 x 10.9 cm / 8.2 x 2.9 x 4.2 in  161.0 g / 5.7 oz

READING PERFORMANCE	
Image Capture	Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2
Image Sensor	1 Megapixel: 1280 x 800 pixels
Light Source	Aiming: Red Laser 650 nm Illumination: Warm White; Hyper Red LED for Digimarc
Motion Tolerance	35 IPS
Print Contrast Ratio (Minimum)	15%
Reading Angle	Pitch: +/- 65°; Roll (Tilt): 360°; Skew (Yaw): +/- 65°
Reading Indicators	Beeper (Adjustable Tone); Datalogic Three Green Lights (3GL) Good Read Feedback: Datalogic 'Green Spot' on the Code, Dual Good Read LEDs
Resolution (Maximum)	High Density (HD): 1D Linear: 0.077 mm / 3 mils; PDF417: 0.077 mm / 3 mils; Data Matrix: 0.102 mm / 4 mils Standard Range (SR): 1D Linear: 0.102 mm / 4 mils; PDF417: 0.127 mm / 5 mils; Data Matrix: 0.195 mm / 7.5 mils
READING RANGES	
Typical Depth of Field	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

## GD4500 Standard Range (SR)

Code 39: 5 mils: 7.0 to 38.0 cm / 2.7 to 14.9 in Code 39: 10 mils: 2.2 to 58.0 cm / 0.8 to 22.8 in Data Matrix: 10 mils: 5.5 to 27.0 cm / 2.2 to 10.6 in Data Matrix: 15 mils: 2.8 to 41.0 cm / 1.1 to 16.1 in EAN-13: 13 mils: 1.0 to 71.0 cm / 0.4 to 27.9 in PDF417: 10 mils: 2.5 to 41.0 cm / 1.0 to 16.1 in QR Code: 10 mils: 5.5 to 24.0 cm / 2.2 to 9.5 in

SAFFTY & REGULATORY

#### GD4500 High Density (HD)

Code 39: 3 mils: 5.0 to 15.0 cm / 2.0 to 5.9 in Code 39: 5 mils: 0.5 to 25.0 cm / 0.2 to 9.8 in Data Matrix: 5 mils: 5.5 to 9.0 cm / 2.2 to 3.5 in Data Matrix: 10 mils: 2.0 to 27.0 cm / 0.8 to 10.6 in EAN-13: 7.5 mils: 2.0 to 23.5 cm / 0.8 to 9.3 in EAN-13: 13 mils: 1.0 to 40.0 cm / 0.4 to 15.7 in PDF417: 4 mils: 3.0 to 12.0 cm / 1.2 to 4.7 in PDF417: 10 mils: 0.5 to 31.0 cm / 0.2 to 12.2 in QR Code: 10 mils: 2.0 to 25.0 cm / 0.8 to 9.8 in

O/ II E I I & II E O O E / I	0/11 211 a 112002/110111	
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use.  The Quick Reference Guide for this product can be referred to for a complete list of certifications.	
Environmental Compliance	Complies to China RoHS; Complies to EU RoHS	
Laser Classification	Caution Laser Radiation - Do not stare into beam; IEC 60825 Class 2	
UTILITIES		
Datalogic Aladdin™	Datalogic Aladdin configuration program is available for download at no charge.	
OPOS JavaPOS	JavaPOS and OPOS Utilities are available for download at no charge.	
Remote Host Download	Remote Host Download Lowers service costs and improves operations	

## **ACCESSORIES**

### **Mounts/Stands**

11-0360 Holder, Multi-Purpose, Black 11-0362 Holder, Multi-Purpose, Grey HLD-G041-BK Desk/Wall Holder, G041, Black HLD-G041-WH Desk/Wall Holder, G041, White STD-G041-BK Basic Stand, G041, Black STD-G041-WH Basic Stand, G041, White









#### **DATALOGIC PRODUCT OFFERING**

















Hand Held scanners Mobile Computers

Stationary Industrial Scanners

© 2018-2020 Datalogic S.p.A. and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic Sp.A. and/or its affiliates. • Datalogic and the Datalogic logo are registered trademarks of Datalogic Sp.A. in many countries, including the U.S. and the E.U. • Gryphon is a trademark of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. • Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. - The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Group companies is under license. • All other trademarks and brands are property of their respective owners • Product specifications are subject to change without notice. DS-GRYPHON-GD45002D-EN Revision G 20200804