



Desktop

1526L

entuitive
Touchmonitors

5000 Series 15" LCD Touchmonitor—Medical

SPECIFICATIONS

Model	1526L
Case/Bezel color	Beige
Display type	Active matrix TFT LCD
Display size	15" diagonal
Useful screen area	Horizontal 11.9" (304 mm)
	Vertical 8.9" (228 mm)
Monitor dimensions	Width 15.4" (391 mm)
	Height (including base) 15.4" (391 mm)
	Depth (including base) 8.2" (208 mm)
Dimensional drawing number	MS500104 (available at www.elotouch.com)
Optimal (native) resolution	1024 x 768 at 60, 70, or 75 Hz
Other supported resolutions	1024 x 768 at 65 Hz (Sun); 832 x 624 at 75 Hz (Mac); 800 x 600 at 56, 60, 72, and 75 Hz; 720 x 400 at 70 Hz; 720 x 350 at 70 Hz; 640 x 480 at 60, 66 (Mac), 72, and 75 Hz
Colors	16.7 million
Brightness	LCD panel 300 cd/m ²
	LCD panel with touchscreen AccuTouch: 255 cd/m ²
Viewing angle (from center)	Horizontal (left/right) ±75° or 150° total
	Vertical (up/down) ±70°/60° or 130° total
Contrast ratio	450:1
Input video format	VGA/SVGA/XGA analog
Input video signal connector	Mini D-Sub 15-Pin (female)
Input frequency	Horizontal 31.5–60 kHz; vertical 56–75 Hz
Video bandwidth	80 MHz
Power supply	External power supply with AC input, 100–240 VAC, 50–60 Hz
Power dissipation	32 W max.
Temperature	Operating –10°C to 40°C; storage –30°C to 60°C
Humidity	Operating 20% to 80%; storage 5% to 90%; noncondensing
Weight (approx.)	Actual 15.2 lb (6.9 kg); shipping 21.6 lb (9.8 kg)
Warranty	Monitor 3 years
	Touch technology 5 years AccuTouch touchscreen
	Backlight lamp life 40,000 hours to half brightness
Other features	Digital on-screen display (OSD); two built-in 1 W speakers; removable base; drip-proof (IEC529/IPX1); VESA mounting; wall mountable when installed by qualified personnel; User's controls: • side: auto, enter, ±, menu, power • OSD: contrast, brightness, H/V position, color, temperature, clock, phase, recall, OSD time, language (English, German, Spanish, Japanese, French) • OSD disable/enable: power, volume, and/or OSD menu

ORDERING INFORMATION

Touch Technology	Touch Interface	Surface Treatment	Elo Part Number	Agency Approvals
AccuTouch	Serial	Antiglare	F65991-000	UL, cUL, CE, FCC-B, UL2601, drip-proof (IEC529/IPX1), CE MDD, DEMKO

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.

tyco
Electronics

elo
TOUCHSYSTEMS