# elo

## 15E3 15-inch

## All-in-One Touchscreen Computer



Integrated Touch



**Commercial Grade** 



## **3-Year Warranty**

## **Product Overview**

The Elo E-Series 15-inch (15E3) 4:3 touchscreen computer is a commercial-grade solution powered by Intel Celeron J1900 Quad-Core processor to provide top-notch performance in a compact form factor. With a rugged design and fan-less operation, the E-Series is ideally suited for use in any retail or hospitality environment, especially with third-party peripherals supported through four USB and two serial ports. A second VGA output is available to add a second customer-facing display for advertising and customer engagement. The fan-less cooling design promotes a noise-free, dust-free and particulate-free operation, allowing you to maximize uptime and performance. Rigorously tested and backed by a three-year warranty, the 15E3 delivers superior quality and reliability.

Available with TouchPro™ Pro-G PCAP or AccuTouch® micro-bezel 5-wire resistive touch technology

Pure glass touchscreen provides optimal picture quality and is factory sealed to resist spills, dust and grease

Durability to withstand the rigors of use in a public environment

#### **15E3 All-in-One Touchscreen Computer**

Specifications			
Enclosure color	Black		
Screen Size	15"		
Processor	Intel Celeron J1900 Quad-Core Processor 2 GHz (up to 2.42 GHz) 2MB L2 Cache; fan-less		
BIOS	AMI		
Memory (RAM)	4GB DDR3L SODIMM on 1 of 1 slot		
Storage Options	128GB 2.5" 7mm SATA SSD1		
Available I/O Ports	Input: 4 x USB 2.0; 2 x Native DB9 RS-232 (standard); 1 x LAN RJ45 (Gigabit); 1 x RJ12 cash drawer (EPSON pinouts)		
	Output: VGA out; 1 x 3.5mm line out		
Display	15" diagonal, active matrix TFT LED LCD		
Aspect Ratio	4:3		
Useful Screen Area (H x V)	TouchPro PCAP: 12.17" x 9.18" (309.1mm x 233.1mm); AccuTouch: 12.09" x 9.10" (307.1mm x 231.1mm)		
Native (optimal) Resolution	1024 x 768 @ 60Hz		
Colors	262K (6-bit)		
Brightness (typical)	LCD panel: 350 nits; TouchPro PCAP: 315 nits; AccuTouch: 280 nits		
Response Time (typical)	8 msec		
Viewing Angle (typical)	Horizontal: ± 80° or 160° total; Vertical: 70°/80° or 150° total		
Contrast Ratio (typical)	800:1		
Touch Technologies	AccuTouch 5-wire resistive (single-touch); TouchPro Pro-G PCAP (10-touch)		
Surface Treatment	Anti-glare		
Touch Interface	USB		
Power	External 19VDC universal-type power supply brick; AC input voltage: 100-240VAC; Input frequency: 50-60Hz;		
i owei	Maximum output power: 65W (Max draw: 74W): Maximum Power Consumption (w/o peripherals): 29W		
Dimensions (max. with stand, dimensions vary with tilt and options)	14.1" x 14.1" x 6.3" (358mm x 357mm x 161mm)		
Shipping Box Dimensions (W x H x D)	18.1" x 9.8" x 16.8" (460mm x 250mm x 425mm)		
Weight	With stand: 11.1 lbs (5 kg); Shipping Weight: 15.9 lbs (7.2 kg)		
Temperature	Operating: 0°C to 35°C (32°F to 95°F); Storage: -20°C to 60°C (-4°F to 140°F)		
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 5% to 95%		
Mounting Options	Wall mount or secure base to tabletop/desktop		
Real-Time Clock	Replaceable lithium-ion battery for clock		
Sealing	Touchscreen sealed to sub-bezel; Touchscreen sealed to LCD		
Other Features	Serviceable internal components: Removable baseplate; Threaded holes on bottom of baseplate for mounting, Kensington security lock		
Warranty	3 year		
MTBF	30,000 hours demonstrated		
Agency Approvals	UL/cUL, FCC, TUV, CB, CE, Mexico CoC, RCM, VCCI, CCC, KC, BSMI, Ukrsepro		
What's in the Box	E-Series Touchcomputer, Quick Install Guide, Power Adapter, US Type-B Power Cord (7A, 125V~), EU Type-E+F Power Cord (2.5A, 250V~), Expended base cap, 1 x secure screw for front cover		

 $^1\!\text{GB}$  equals one billion bytes when referring to storage capacity. Accessible capacity may be less.

### **Ordering Information**

Model	Part Number	Technology	Operating System	Color	Availability
	E291777	AccuTouch	No OS	Black	America, EMEA, Asia
	E292254	AccuTouch	Windows POSReady 7	Black	America, EMEA, Asia
4550	E292635	AccuTouch	Windows 10	Black	America, EMEA, Asia
15E3	E292972	TouchPro PCAP	No OS	Black	America, EMEA, Asia
	E293176	TouchPro PCAP	Windows POSReady 7	Black	America, EMEA, Asia
	E293543	TouchPro PCAP	Windows 10	Black	America, EMEA, Asia

#### **Optional Accessories**

Part Number	Description
E122229	Magnetic Stripe Reader (MSR)
E122426	VFD Customer Display
E791658	7-inch Rear Facing Display
E122610	Rear Facing Display Mount
E143088	Wall Mount

To find out more about our extensive range of Elo touch solutions, go to **elotouch.com**, or call the office nearest you.

#### North America Tel +1 408 597 8000

Fax +1 408 597 8050

Europe Tel +32 (0)16 70 45 00 Fax +32 (0)16 70 45 49 customerservice@elotouch.com elosales@elotouch.com

Asia-Pacific Tel +∞o (∠), 002. Fax +86 (21) 3329 1400 Tel +86 (21) 3329 1385

www.elotouch.com.cn

Latin America Tel +1 786-923-0251 Fax +1 305-931-0124 elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, AccuTouch and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17072AES00088

