



Desktop

2125C

3000 Series
21" CRT Touchmonitor

SPECIFICATIONS

Model		2125C
Case/Bezel color		Beige
Display type		FST CRT
Display size		21.0" diagonal
Display area dimensions, nominal	Default	14.96" (380 mm) H x 11.2" (285 mm) V
Monitor dimensions	Width	19.68" (500 mm)
	Height (including base)	19.48" (495 mm)
	Depth (including base)	19.09" (485 mm)
Dimensional drawing number		MS500197 (available at www.elotouch.com)
Highest recommended resolution		1280 x 1024 at 85 Hz
Resolution presets		1600 x 1200 at 85 Hz 1280 x 1024 at 85 Hz (SXGA) 1024 x 768 at 85 Hz (XGA) 800 x 600 at 85 Hz (VESA)
Dot pitch, nominal		0.25 mm
Video bandwidth		230 MHz
Input frequency		Horizontal 31–107 kHz; vertical 50–150 Hz
Input video format		Analog (no proprietary video card needed)
Input video signal connector		Mini D-Sub 15-Pin (female)
Power supply		90–264 VAC, 47–63 Hz
Power dissipation		145 W max.
Temperature		Operating 0°C to 40°C; storage –20°C to 60°C
Humidity		Operating 35% to 80%; noncondensing
Weight (approx.)		Actual 53.6 lb (24.3 kg); shipping 64.6 lb (29.3 kg)
Warranty	Monitor	2 years
	Touch technology	2 years iTouch
Other features		Digital on-screen display (OSD); removable base; sealing; ENERGY STAR; VESA DPMS (included on external controller version only); VESA DDC 1/2 B Plug and Play; ISO 9241/3

ORDERING INFORMATION

Touch Technology	Touch Interface	Surface Treatment	Elo Part Number	Agency Approvals
iTouch	Serial	Antireflective	074698-000	UL, cUL, FCC-B, VCCI, C-Tick, CE, TÜV-GS, MPR II, TCO 99
iTouch	USB	Antireflective	C37655-000	UL, cUL, FCC-B, VCCI, C-Tick, CE, TÜV-GS, MPR II, TCO 99

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.