# Epson® Mobilink<sup>™</sup> P60II Wireless Receipt/Label Printer



- Compatible with iOS, Android and Windows mobile devices
- Industry-leading operational battery life up to 46 hours\*
- 4-foot drop rating and IP54 environmental certified
- Highest printing speed in its class
- Supports 802.11a/b/g/n with 2.4GHz/5GHz compatibility and Bluetooth<sup>®</sup> 2.1 + EDR
- Offers paper-saving options
- Zebra® emulation available for label applications

Epson's robust Mobilink P60II wireless printer is fast, easy to use and offers an ultra long battery life. Designed to meet the needs of today's mobile systems, it exceeds the printing requirements of iOS, Android and Windows environments.

### Great features for mobile printing

The Mobilink P60II has all the features you need to print receipts or labels anywhere, anytime. Tough and robust, it offers the fastest printing in its class with speeds up to 100mm/second, an industry-leading battery life, flexible connectivity and a ruggedized design to ensure reliability in even the harshest environments.

# Best-in-class battery life

To ensure uninterrupted service to your customers, Epson's Mobilink P60II features an industry-leading operational battery life of up to 27 hours with 802.11 models and up to 46 hours with Bluetooth models<sup>\*</sup>.

### Multi-platform printing made easy

With Epson's unique ePOS-Print technology, the Mobilink P60II can print from any devices running an iOS, Android or Windows operating system with a WiFi or Bluetooth connection, using a HTML5 browser or native application. This provides an easy and smart solution for today's mobile printing requirements.

### Compatible and ready to go

The Mobilink P60II printer is compatible with all of today's best-of-breed POS systems and the latest industrystandard wireless security protocols. The printer supports 802.11a/b/g/n with 2.4GHz/5GHz compatibility or Bluetooth® 2.1 + EDR. It also comes complete with ESC/POS®, OPOS, JavaPOS and Windows® drivers which means your current POS software and applications are instantly compatible.

### Reduce your paper costs

With the Mobilink P60II paper-saving options, you can reduce your paper usage by up to 23%. The paper-saving settings are easy to use and do not affect print quality, readability or font size.

# Backed by the leader

The Mobilink P60II features the quality and reliability that Epson is known for, a low total cost of ownership and is backed by our leading service and support programs.



#### All the features you need

- · Compatible with iOS, Android and Windows mobile devices
- Industry-leading operational battery life up to 46 hours\*
- 4-foot drop rating and IP54 environmental certified
- Highest printing speed in its class
- Supports 802.11α/b/g/n with 2.4GHz/5GHz compatibility & Bluetooth® 2.1 + EDR
- ٠ Supports wireless security WEP, WPA , WPA2-Enterprise
- ٠ Paper-saving options
- Zebra® emulation available for label applications

#### Printer

Print method Print speed (max.)	Thermal line printing Receipt mode 100mm/sec, label mode 80mm/sec; peeler mode 40mm/sec
Dot/line	420/432 dots
Print font	
Font	Font A 12 x 24, new Font B 10 x 24, new Font C 8 x 16
Column capacity	58mm paper, Font A/B/C, 35/42/52 columns; 60mm paper, Font A/B/C, 36/43/54 columns
Character size	1.5 × 3.0 / 1.25 × 3.0 / 1.0 × 2.0 mm (W × H)
Character set	95 Alphanumeric, 48 International, 128 x 10 Graphic
Barcode	1D: EAN-8, EAN-13, UPC-A, UPC-E, JAN13, JAN8, Code 39, Code 93, Code 128, ITF, CODEBAR, GS-1- 128, GS1 DataBar, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded
	2D: QR Code, Maxi Code, PDF417, Composite, Data Matrix, RSS/GS1 and Aztec
Characters per inch	17/20/25 срі
Paper width	Paper or labels, 58mm or 60mm width (receipt version) Paper or labels, 30–60mm (label version)
Paper diameter (max.)	51mm
Reliability	10 million printing lines; 500,000 autocutter (receipt version)

#### General information

Interface	802.11b/g/n (2.4GHz) and 802.11a/n (5GHz) or Bluetooth 2.1 + EDR
Supported mobile operating systems	WiFi (802.11): iOS, Android and Windows (Security Level WEP, WPA, WPA2-Enterprise) Bluetooth: iOS, Android and Windows
Data buffer	4096 bytes
Autocutter Peeler	Partial cut, left uncut (receipt version) Automatic label removal from backing (label version)
Audible alert	Programmable buzzer
Sensors	Paper out (receipt and label versions) Gap, black mark, label taken (label version)
LED indicators Green LED	Power (ON=Power on, OFF=Power off)
Orange LED	Only shown when power is ON Error, Paper end, Cover open, Battery level low (printer does not operate)
Blue LEDs	Four battery level indicators: 3 LED ON = approx. 100%-60% 2 LED ON = approx. 60%-20% 1 LED ON = approx. 20%-10% 1 LED Flashing = approx. 10%-1%
Software	TM-P60II Utility, EpsonNet Config, EpsonNet Simple Viewer, TM-P60II Remote Configuration Tool, TM Bluetooth Connector, Built-In Configuration Page

#### Made for BiPod □iPhone □iPad

\*The Mobilink P60II battery life can last up to 27 hours for WiFi and up to 46 hours for Bluetooth. Battery life can vary significantly depending on usage.



CPD-41752



Epson America, Inc. • 3840 Kilroy Airport Way • Long Beach, CA 90806 • (562) 290-5304 @2014 Epson America, Inc. Epson is a registered trademark and Epson Exceed Your Vision is a registered logo-mark of Seiko Epson Corporation. Mobilink is a trademark of Epson America, Inc. All other trademarks are the property of their respective owners. Specifications are subject to change without notice.

Power Charging	Custom Lithium-Ion battery pack, AC adapter (option) AC adapter (2.5 hours to full charge), custom quad bay charger (2.5 hours to full charge)
Battery life	Up to 27 hours with 802.11n, up to 46 hours with Bluetooth 2.1 + EDR*
Operating temperature	0° C to 45° C
Drop rating	4 feet
Overall dimensions	4.05" x 6.25" x 2.55" (103 x 159 x 65 mm) (W x D x H)
Weight	Receipt version 1.4 lbs (630g) with battery, belt clip Label version 1.3 lbs (600g) with battery, belt clip
Color	Epson Black (EBCK)
Warranty	One-year limited warranty and optional two-year warranty

## What's in the box

Mobilink P60II Battery (Model: OT-BY60II) Roll paper (for checking initial movement of the printer) User's manual USB cable Belt clip (already attached to printer) 58mm spacer (already attached to printer)

#### **Accessories**

Battery (OT-BY60II) Quad Charger (OT-CH60II) Power Supply (PS-11) Shoulder Strap and Padded Case (AB1370EPI)





Spare Battery





Quad Charge

AC/DC Power Supply

Shoulder Strap/Padded Case



