

ID LRU4000

## UHF LONG RANGE READER

- Robust housing with cable glands & plug-in terminals
- Designed for applications in harsh environments (indoor & outdoor) (IP65/IP67)
- 2 Watt Output Power
- 4 Antenna Ports (internal Multiplexer)
- 2 Inputs / 4 Outputs
- Edge Computing Device



### UHF Long Range Reader for various applications

With a reading range of more than 10 m, 4 antenna connections and 4 cable glands several long range applications can be realized.

### Applications in industry and logistics

For applications in harsh environments, the reader offers sealed connections and cable glands as well as plug-in terminals inside the device. This makes it the first choice for use on machines, conveyor systems or other industrial applications.

### Various mounting options

The reader can be mounted directly on a flat surface, via a VESA on a post, via an adapter on a DIN rail or via an plastic insulation plate on a vehicle chassis – you have the choice!

### Features:

- › High receiver sensitivity cares for an enlarged and at the same time homogeneous tag detection range
- › Support of Transponders according to EPC Class1 Gen2 and ISO 18000-63
- › Allows the realization of secure UHF systems by full support of transponder chips according to EPC Class1 Gen2 specification and ISO 29167 (e. g. NXP UCODE DNA)
- › Secure storage of application keys in a secure memory (Secure Element)
- › 2 Inputs, 2 Outputs and 2 Relay Outputs suit industrial needs and allow control of external components and signalization of different events
- › Edge-Computing Platform with Linux OS for installation and operation of custom specific applications directly on the reader
- › Different software applications available e.g. for EPCglobal™ LLRP support
- › Reader protection against fault conditions like antenna shortcut, antenna mismatching and electrostatic discharge

# UHF LONG RANGE READER FOR VARIOUS APPLICATIONS

ID LRU4000

## Technical data

### Dimensions (w x h x d)

Without Connectors	approx. 225 mm x 140 mm x 55 mm
With Connectors	ca. 225 mm x 190 mm x 55 mm
Weight	approx. 1200 g
Housing	Aluminium housing, plastic cover
Color	Aluminium, anthracite (cover)
Protection Class	IP65, IP67
Power Supply	12 V – 24 V DC $\pm$ 10 %, Power-over Ethernet (PoE+)
Power Consumption	max. 18 W*
Output Power	100 mW to max. 2 W configurable in steps of 100 mW
Antenna Connector	4 x R-TNC-Jack (50 Ohm), integrated Multiplexer, support of external Multiplexer ID ANT.UMUX
RF Diagnosis	RF-channel monitoring, Antenna SWR control, internal overheating control
Connections	Power supply, RS485, Mini USB Connector, I/Os: plug-in terminals Ethernet: RJ45 socket on the outside of the housing with the option of sealing

### Outputs

2 Optocoupler	max. 24 V DC / 20 mA
2 Relays	max. 24 V DC / 1 A switching current, 2 A permanent current

### Inputs

2 Optocoupler	max. 24 V DC / 20 mA
Interfaces	RS485, Ethernet (IPv4/IPv6), USB (On-the-Go)
Computing Platform (Linux OS)	ARM single Cortex-A7 800 MHz + Cortex-M4 (RFID), 1 GB Flash, 512 MB RAM
Reader Modes	Host Mode, Buffered Read Mode, Notification Mode
Supported Transponders	EPC Class1 Gen2, ISO 18000-63, ISO/IEC 29167
Indicator	Highly visible status display (green/red/blue; customizable indication)
Others	Anti-Collision, Output of RSSI values and phase angle, Secure Key Storage, "Config Cloning" function, Action-on-EPC, Web-Interface

### Temperature Range

Operation	-40 °C – +70 °C**
Storage	-40 °C – +85 °C
Relative Air Humidity	5 % up to 95 % (non-condensing)
Vibration	EN 60068-2-6 10 Hz up to 150 Hz: 0.075 mm / 1 g

## Versions

EU	865 MHz to 868 MHz
FCC	902 MHz to 928 MHz

\* not including power consumption due to external Multiplexer

\*\* additional measures may be required

# UHF LONG RANGE READER FOR VARIOUS APPLICATIONS

ID LRU4000

## Standard Conformity

### Radio License

Europe, UK	EN 302 208
USA	FCC 47 CFR Part 15
Canada	IC RSS-247
EMC	EN 301 489
Safety & Health	EN 62368-1, EN 50364
Cyber Security	EN 18031-1



ID LRU4000, front view



ID LRU4000, antenna connections



ID LRU4000, Connections for VCC, Interfaces, I/Os