

Gvision LCD Monitor J2ES-DA

- Product Specification -

Configuration		J2ES-DA
LCD Display		12.1" TFT active matrix panel
Display Size (HxV mm)		246 x 184.5
Pixel Pitch (HxV mm)		0.3075 x 0.3075
Max. Resolution		SVGA 800x600
Contrast Ratio		100:1 (typical)
Brightness		200 cd/m ² (typical)
Response Time		30 ms (typical)
Display Color		262K
Viewing Angle	L/R	+40°~-40° (typical)
	U/D	+20°~-10° (typical)
PC Interface	Video	RGB analog 0.7V _{peak} to peak
	Sync.	TTL positive or negative
Display Mode		VGA 640X350 (70/85 Hz)
		VGA 720X400 (70/85Hz)
		VGA 640X480 (60/72/75/85 Hz)
		SVGA 800x600 (56/60/72/75/85 Hz)
		Mac. 832 x 624 (75Hz)
Signal Connector		D-sub 15 pin
Front Control		Power on/off with LED, Menu, Select, Adjustment (Up, Down)
OSD		Brightness, Contrast, R.G.B. Contrast,
		Auto Setup, Frequency, Phase, H-position, V-position,
		Track, Text/Graphics, Expansion, Display Mode/Freq., Recall
Plug & Play		DDC1/2B compatible
Power	Form	AC/DC Adapter
	Input/Output	Input AC 90-264V, 50-60Hz; Output DC 12V/3.5A
Operating Conditions	Temperature	5°C~40°C (32°F~104°F)
	Humidity	10%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C~60°C (-4°F~140°F)
	Humidity	10%-80% (no condensation)
Dimensions (HxDxW inches)		9.3 x 12.3 x 2.9
Weight (lbs)		6.6
Standard Features &	Touch Panel	Resistive type
	Video-In	S & RCA connectors
Options	Stand/Arm	Desktop stand, Photo frame stand, Adjustable arm
Certification		C-UL, FCC, CE

* Specifications are subject to change without notice.

Catch the wave of the future - Now!

Gvision USA Inc.

1582 Parkway Loop, Suite C, Tustin, CA 92780

