

GVision LCD Monitor J5PX Series

15-inch TFT Display with Touchscreen

- Product Specification -

Configuration		J5PX
LCD Display		15" TFT active matrix panel
Display Size (HxV mm)		304 x 228
Pixel Pitch (HxV mm)		0.297 x 0.297
Max. Resolution		XGA 1024x768
Contrast Ratio		350:1 (typical)
Brightness		250 cd/m ² (typical)
Response Time		30 ms
Display Color		16M
Viewing Angle	L/R	+70°~-70° (typical)
	U/D	+70°~-70° (typical)
PC Interface	Video	RGB analog 0.7V peak to peak
	Sync.	TTL positive or negative
Display Mode		VGA 720x400 (70 Hz)
		VGA 640x480 (60/66/70/72/75 Hz)
		SVGA 800x600 (60/70/72/75 Hz)
		XGA 1024x768 (60/70/75 Hz)
Signal Connector		D-sub 15 pin
Front Control		Power on/off with LED, Menu, Select, Adjustment (+,-)
OSD		Brightness, Contrast, Clock, Phase, Auto-tune, H-position, V-position,
		R.G.B. color drive, OSD format, Volume
Plug & Play		DDC1/2B compatible
Speaker		1W/per channel driver
Power		Embedded AC input power system, universal 90-264 Volts
Operating Conditions	Temperature	0°C~40°C (32°F~104°F)
	Humidity	10%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C~60°C (-4°F~140°F)
	Humidity	10%-80% (no condensation)
Dimensions (HxDxW inches)		15.3 x 14.9 x 3.0 (without base)
Weight (lbs)		11.4 (without base)
Standard Features & Options		Capacitive, Resistive or SAW touch interface available.
Certification		C-UL, FCC, TUV/GS, CE, MPR II, EPA, NUTEK, D, N, S, F, TCO (optional)

* Specifications are subject to change without notice.

* Color available in beige and black.

Gvision USA Inc.

1582 Parkway Loop, Suite C, Tustin, CA 92780

