

# Semi-Rugged Tablet PC

# CA10

## Rugged Features

|                  |   |
|------------------|---|
| Drop Resistance  | MIL-STD 810G 516.6 Procedure IV, 26 drops from 4 feet height                              |
| Shock Resistance | MIL-STD 810G 514.6 General Vibration<br>ASTM 4169-08 Truck Assurance Level II, Schedule E |
| Spill Resistance | IP-43   |

## System Specifications

|                         |   |
|-------------------------|---|
| Processor               | Intel® Atom Processor N2600 (1.6GHz)  |
| System Memory           | One 204-pin DDR3-800 SODIMM socket for 2GB Max  |
| Storage                 | SD card slot<br>m-SATA SSD 32GB / 64GB / 128GB  |
| Display                 | 10.1" WXGA (1280 x 800 resolution) TFT LCD with resistive multi-touch screen panel, LED backlight<br>Optional: Sunlight readable screen, resistive multi-touch panel and all touch panel are with tempered glass  |
| Chipset                 | Intel® NM10   |
| Audio                   | • HD Audio • Microphone x 2 (array) • Built-in speaker x 1  |
| Interface               | • DC-in Jack • USB2.0 x 2 • RJ-45 x 1 • Serial port x1<br>• One docking connector (includes power, USB, serial port, and Ethernet signal support)<br>• Optional: Integrated rear facing 5 Mega Pixel camera with LED light / RFID reader / Magnetic Stripe Reader/ Integrated bar code scanner support 1D/ 2D symbologies |
| Webcam                  | • 1.3 Mega-pixel Web-cam on top of the front panel<br>• Optional Integrated rear facing 5 Mega Pixel camera at the back of unit with LED light  |
| Wireless & Connectivity | • Integrated Giga LAN Ethernet network (RJ45)<br>• Intel Centrino Wireless N 135 ( WLAN 1x1 b/g/n, Bluetooth 3.0 EDR)<br>• Optional Mini PCI-e connector for WWAN/GPS (AT&T, T-Mobile & Sprint)   |
| Power Supply            | • AC/DC adapter : Output: 19V, 3.42A ; 65W, Input: 100V-240V, 50Hz-60Hz<br>• Two battery packs, supports hot-swap.<br>• Lithium Ion battery pack ( 11.1V, 2600mAh, 28.86W)<br>• Battery life : 6~7hrs depends on configuration (with 2 Li-Ion battery packs)<br>• Hot-Swappable batteries provide all day computing       |
| Security                | Computrace Enable BIOS, Administrator password, Boot password<br>Smart Card Reader, TPM 1.2 , Kensington Lock   |
| Software                | Microsoft Windows® 7  |
| Dimensions & Weight     | 10.62"(W) x 7.79"(D) x 1.61"(H) / 270mm(W) x 198mm(D) x 40.9mm(H)<br>Weight: 2.9 lbs / 1.36 kgs   |
| Certifications          | • US: FCC, DOC+, CUS, FCC ID • EU: CE, CB • CAN: CUS, IC  |
| Warranty                | 2-Year Warranty   |
| Accessories/Options     | AC adapter, Power cord, Stylus Pen<br>Optional Car Adapter, Hand-strap, Shoulder strap.   |



- The specification and pictures are subject to change without notice.
- All brand names are registered trademarks of their respective owners.
- Battery life may vary based on setting and usage.