Getac



ZX70 FULLY RUGGED TABLET

- Qualcomm[®] Snapdragon[™] 660, Octa-core Processor
- Verified as Android enterprise recommended
- 7" LumiBond® display with Getac sunlight readable technology and glove-enabled capacitive touchscreen
- 6-ft drop, MIL-STD-810H and IP67 certified
- Optional barcode reader, RFID reader











Specifications

Operating System

Android™ 10.0

Mobile Computing Platform

Qualcomm[®] Snapdragon[™] 660, Octa-core 1.95GHz Max 2 2GHz

VGA Controller

Qualcomm[®] Adreno[™] 512 GPU

7" IPS TFT LCD HD (1280 x 720)

Protection film

LumiBond® display with Getac sunlight readable technology

Capacitive multi-touch screen

Storage & Memory

4GB LPDDR4

64GB eMMC

Keyboard

Power button

3 tablet programmable buttons

Pointing Device

Touchscreen

- Capacitive multi-touch screen

I/O Interface

8M pixels webcam x 1

12M pixels auto focus rear camera x 1

DC in Jack x 1

USB 2.0 (Host) x 1 MicroUSB 2.0 (Client) x 1

MicroSD x 1

Docking connector (Pogo/JAE) x 1

Optional: RF antenna pass-through for GPS and

Communication Interface

Wi-Fi 802.11ac

Bluetooth (v5.0)

Dedicated GPS

Optional: 4G LTE mobile broadband

Security Feature

Optional: Contactless HF RFID/NFC combo reader ii,iii Optional: Barcode reader

AC adapter (25W, 100-240VAC, 50/60Hz) Li-ion battery (3.8V, typical 8480mAh; min. 8220mAh)

Dimension (W x D x H) & Weight

218 x 142 x 27mm (8.58" x 5.6" x 1.08") 762g (1.68lbs) in

Rugged Feature

MIL-STD-810H certified

IP67 certified

Vibration & 6ft (1.8m) drop resistant $^{\rm v}$ Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D)

Environmental Specification

Temperature ^v

- Operating: -21°C to 60°C / -6°F to 140°F
- Storage: -40°C to 71°C / -40°F to 160°F
- 95% RH, non-condensing

Pre-installed Software

Getac File Browser Getac Camera Getac Input Method

DeployeXpress Client Getac settings and Google applications (Search, Chrome, Gmail, Maps, YouTube, Play, Drive, Play music, Play movies, Duo and photos)

Accessories

AC adapter (25W; 12V/2A, 100-240VAC; 50/60Hz) Capacitive stylus with tether Pen holder

Wrist strap

Optional:

Carry bag
AC adapter (25W; 12V/2A, 100-240VAC; 50/60Hz)
Office dock AC adapter (60W, 110-240VAC)
Vehicle adapter (40W, 11-16V, 20-32VDC)
Capacitive stylus with tether

Shoulder strap (2-point) Wrist strap Rotating hand strap with kickstand and stylus holder

USB to RS232 converter cable
Docking connector to HDMI converter cable
Vehicle dock

Office dock

Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can dépend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- i Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.

 ii 13.56MHz contactless HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compoliant).
- HF RFID/NFC combo reader applies to US & EU.
- Weight and dimensions vary from configurations and optional accessories.
- Drop test results vary from configurations and optional accessories.
- vi Tested by an independent third-party test lab following MIL-STD-810H. vii Android enterprise recommended rugged
- devices deliver a consistent set of features verified by Google with an elevated device baseline, increased security standards and enterprise-focused features and behaviors to meet the needs of users. Google and Android are trademarks of Google LLC

Fully Rugged Tablet



Docking Solutions

	Getac-made Vehicle Dock (JAE)	Havis Vehide Dock (Pogo,power only)	Havis Vehide Dock (JAE)	Gamber-Johnsor Charging Cradle (Pogo)	n Havis Vehicle Dock (Pogo)	Office Dock (JAE)	Office Dock (Pogo)
Serial Port	1	-	1		1	-	_
Speaker	1	-			-	_	_
Audio Output	1	1	1		1	1	1
DC in Jack	1	1	1	1	1	1	1
USB	USB Host x 2	-	USB2.0 x 2		USB2.0 x 2	USB Host x 2 MicroUSB Client x 1	USB Host x 2
LAN	1	-	1		1	1	1
HDMI	1		1		-	1	
RF Antenna Connector	(WWAN, GPS)	(WWAN, GPS)	(WWAN, GPS)	-	(WWAN, GPS)	-	-



Getac USA

15495 Sand Canyon Ave. Suite 350 Irvine, CA 92618 Tel: 949-681-2900 GetacSales_US@getac.com | www.getac.com/us/



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved available specification shall be subjected to quotation by request. V03M07Y21US