

<b>Print Method:</b>	HDP® Retransfer: Dye Sublimation / Resin Thermal Transfer
<b>Resolution:</b>	300 dpi (11.8 dots/mm) continuous tone
<b>Colors:</b>	Up to 16.7 million / 256 shades per pixel
<b>Print Ribbon Options:</b>	<ul style="list-style-type: none"> <li>• Full-color, YMC*, 750 prints</li> <li>• Full-color with resin black, YMCK*, 500 prints</li> <li>• Full-color with two resin black panels, YMCKK*, 500 prints</li> <li>• Full-color with resin black and heat seal panel for difficult-to-print surfaces, YMCKH*, 500 prints</li> <li>• Full-color with resin black and inhibit panel for signature or other non-printing areas, YMCKI*, 500 prints</li> <li>• Full-color with fluorescing and resin black, YMCFK*, 500 prints</li> <li>• Resin black, K, 3000 prints</li> </ul>
<b>HDP Film Options:</b>	Clear (1,500 prints) Standard Holographic (500 prints) Custom Holographic, special order (500 prints)
<b>Print Speed:*</b>	Batch Mode: <ul style="list-style-type: none"> <li>• 26 seconds per card / 138 cards per hour (YMC with transfer)*</li> <li>• 32 seconds per card / 113 cards per hour (YMCK with transfer)*</li> <li>• 47 seconds per card / 77 cards per hour (YMCKK with transfer)*</li> <li>• 52 seconds per card / 69 cards per hour (YMCKI with transfer)*</li> </ul>
<b>Accepted Standard Card Sizes:</b>	CR-80 (3.370"L x 2.125"W / 85.6mmL x 54mmW)
<b>Print Area:</b>	Over-the-edge on CR-80 cards
<b>Accepted Card Thickness:</b>	Print only: .030" (30 mil) to .050" (50 mil) / .762mm to 1.27mm
<b>Accepted Card Types:</b>	ABS, Laminated PVC, PET, PETG, proximity, smart and mag stripe cards, optical memory cards
<b>Input Hopper Card Capacity:</b>	100 cards each (.030" / .762mm)
<b>Output Hopper Card Capacity:</b>	100 cards (.030" / .762mm)
<b>Reject Hopper Card Capacity:</b>	15 cards (.030" / .762mm)
<b>Card Cleaning:</b>	Replaceable cleaning roller (included with each print ribbon)
<b>Memory:</b>	16MB RAM
<b>Display:</b>	User-friendly, SmartScreen™ LCD Control Panel
<b>Software Drivers:</b>	Windows® 2000 / XP / Server 2003 / Vista (32 bit)
<b>Single Wire USB 2.0 Encoding Options:</b>	ISO Magnetic Stripe Encoding, dual high- and low-coercivity, Tracks 1, 2, and 3 Contactless Smart Card Encoder (HID iCLASS® and MIFARE®) Contact Smart Card Encoder reads from and writes to all ISO7816-1/2/3/4 memory and microprocessor smart cards (T=0, T=1) as well as synchronous cards
<b>Interface:</b>	USB 2.0 (high speed) and Ethernet with internal print server
<b>Operating Temperature:</b>	65° to 90° F / 18° to 32° C
<b>Humidity:</b>	20 – 80% non-condensing
<b>Dimensions:</b>	11.50"H x 14.75"W x 9.25"D / 292mmH x 630mmW x 235mmD
<b>Weight:</b>	28 lbs. / 12.8 kg
<b>Agency Listings:</b>	Safety: IEC/UL 60950-1 (2001) 1st Edition, CSA C22.2 No 60950-1-03 1st Edition, CB report, CE marking EMC: FCC Part 15 Class A, EN 55022:2006 Class A, CRC c1374, EN 61000-3-2:2006, EN 61000-3-3:1995 +A1:2001 +A2:2006, EN 55024:1998 +A1:2001 + A2:2003, CNS 13438 (BSMI No.:SL2-IN-E-014R), CE mark, and CCC.
<b>Supply Voltage:</b>	100-240 VAC, 3.8A
<b>Supply Frequency:</b>	50 Hz / 60 Hz
<b>Warranty:</b>	Printer - Two Years, Printhead - Lifetime; unlimited pass
<b>Fargo Materials:</b>	Fargo Card Printer/Encoders require highly specialized media to function properly. To maximize printed card quality and durability, printhead life and printer/encoder reliability, use only Fargo materials. Fargo warranties are void, where not prohibited by law, when non-Fargo materials are used.
<b>Options:</b>	<ul style="list-style-type: none"> <li>• Smart card encoding (contact/contactless), EMV Level I</li> <li>• Printer cleaning kit</li> </ul>
<b>Software:</b>	Fargo Workbench Diagnostic Utility

\* Indicates the ribbon type and the number of ribbon panels printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, I=Inhibit, F=Fluorescing, H=Heat Seal  
 \*\* Print speed indicates an approximate print speed and is measured from the time a card drops into the output hopper to the time the next card drops into the output hopper. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is dependent on the size of the file, the CPU, amount of RAM and the amount of available resources at the time of the print.

This data sheet is for informational purposes only. HID Global makes no warranties, expressed or implied, in this summary. Company and product names and data used in sample output are fictitious. Specifications are subject to change without notice. Fargo and Asure ID are registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. This is not an offer of sale. © 2009, HID Global Corporation. All rights reserved. REV09B



## ACCESS experience.

[fargo.hidglobal.com](http://fargo.hidglobal.com)

### HID Global Offices:

**Card Issuance Center of Excellence**  
 6533 Flying Cloud Drive  
 Eden Prairie, MN 55344  
 U.S.A.  
 Phone: 1 800 459 5636  
 Phone: + 1 952 941 9470  
 Fax: + 1 952 941 7836

**Corporate North America**  
 15370 Barranca Pkwy  
 Irvine, CA 92618  
 U.S.A.  
 Phone: 1 800 237 7769  
 Phone: + 1 949 732 2000  
 Fax: + 1 949 732 2360

**Asia Pacific**  
 19/F 625 King's Road  
 North Point  
 Island East  
 Hong Kong  
 Phone: +852 3160 9800  
 Fax: +852 3160 4809

**Latin America**  
 Circunvalación Ote. #201 B  
 Despacho 2  
 Col. Jardines del Moral  
 Leon 37160, Gto.  
 Mexico  
 Phone: +52 477 779 1492  
 Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
 Haverhill Business Park  
 Phoenix Road  
 Haverhill, Suffolk  
 CB9 7AE  
 England  
 Phone: +44 1440 714 850  
 Fax: +44 1440 714 840