

Logi Tag™

Discreet RFID tags that withstand liquid immersion, high pressure conditions and extreme temperatures



HID Logi Tag™ transponders endure severe conditions while protecting data integrity. These small, thin discs enable discreet placement in a broad range of applications.

The smallest Logi Tag discs are ideal for tagging industrial tools and small equipment. Among the smallest HF tags available, Logi Tag 081 and 121 units are assembled using patented DBond™ Vigo™ technology that enables HID to produce tags in thinner, smaller formats without compromising performance. They mount with industrial adhesives, with options for metal or non-metal surfaces. Logi Tag HF transponders are NFC Tag Type 5 compliant when formatted with NDEF data structure.

As part of a commercial laundry logistics system, Logi Tag discs ensure accurate item counting and documentation, while enabling automatic billing and real-time inventory control.

Logi Tag discs enable medical facilities automatically track clothing, linens, rags, surgical sponges, and life-saving equipment. Effective tracking of reusable assets and verification of cleaning and sterilization procedures ensures better patient and staff safety through improved infection control.

Logi Tag discs are easily sewn into the hem or seam of a garment, uniform, napkin, tablecloth or runner. They may also be affixed to custodial supplies, such as mats, mops, washrags and towels or are used to tag the hangers to automate laundry workflows. The Logi Tag Button 162 transponder is indistinguishable from ordinary buttons, and can be sewn onto clothing with standard stitching equipment and processes.

Logi Tag transponders empower logistics applications via radio frequency identification (RFID) technology, enabling more accurate, efficient asset management and inventory control processes. LogiTag 161 is also available in a radiation resistant, high-memory FRAM option for most demanding application scenarios. The HF LogiTag 161 (see PN “-EX”) is also available in ATEX and IECEx certified for use in explosive environments.



KEY BENEFITS:

- **Inconspicuous** – Compact form factors conceal easily in textile assets, hand tools or small equipment.
- **Durable** – Resistant to extreme temperature, chemicals, fluids, industrial detergents and high pressure.
- **Powerful** – Rapid, accurate asset identification and data storage, with anti-collision functionality for simultaneous processing of multiple items.

TECHNOLOGY HIGHLIGHTS:

- LF 125 kHz, HF 13.56 MHz / NFC
- 64-bit UID; up to 8KB read-write user memory, crypto options (Vigo™ 2K)
- Anti-collision, multi-read capable (HF)
- High chemical and mechanical resistance
- Temperature resistant up to 347° F (175° C)
- Options for mounting on metal or non-metal surfaces, or radiation resistant FRAM

APPLICATION AREAS:

ASSET TRACKING AND LOGISTICS

- Inventory
- Tools and small equipment

LAUNDRY

- Automated accounting of cleaning
- Automated sorting and inventory
- Clothing, uniforms
- Commercial laundry
- Owner identification

MEDICAL AND HEALTH

- Hospital laundry
- Medical and surgical accessories

For further information, contact tagsales@hidglobal.com

	120			160	081	121	121 OM	161		162 Button
										
Base Model Number	624115-001	612115	601115-102	601106	6A9081-010 (Vigo 1K)	6A9121-010 (Vigo 1K) 629121-012 (SLIX2)	6A9121-310 (Vigo 1K), 6A9121-313 (Vigo 1k FOAM) 629121-312 (SLIX2)	629108-415 629108-412-EX (ATEX/IECEx) 629108-401 (ICODE SLIX)	634108-410 (F-Mem 2K) 6D1108-410 (F-Mem 8K)	629110-401 (SLIX) 629110-415 (SLIX2)
	ELECTRONIC									
Operating Frequency	125 kHz				13.56 MHz					
Chip Type	Hitag S	Q5	Unique		Vigo or ICODE SLIX2			ICODE SLIX2	F-Mem	ICODE SLIX2
Memory	2048 bit EEPROM	264 bit EEPROM	64 bit read-only		1024 bit (Vigo) or 2560 bit UM (ICODE SLIX2)			2560 bit UM	2 or 8 Kbyte FRAM	2560 bit UM
Anti-Collision	Yes	yes				Yes		Yes		
Reading Distance [4 W reader]					Proximity		Up to 13.4 in (34 cm)			
	PHYSICAL									
Dimensions (for exact dimension tolerances, request drawing)	Ø 0.5×0.1 in (12 x 2 mm)			Ø 0.6 × 0.1 in (16 x 3 mm)	Ø 0.31 × 0.1 in (8 x 2 mm)	Ø 0.49 × 0.1 in (12.4 x 2 mm)		Ø 0.6 × 0.1 in (16 x 3 mm)		Ø 0.6 × 0.1 in (16 x 2.5 mm)
Mounting Method	Sew into, glue, embed									Sew on
Embeds In / Affixes To	Clothing and Textiles, non-metal Tools and Boxes					Non-metal	Metal	Clothing and Textiles, non-metal Tools and Boxes		
Housing Material	PPS with epoxy potting			Epoxy	ABS with epoxy potting	PPS with epoxy potting		PPS		
Color	Black							White		
Weight	0.02 oz (0.6 g)			0.04 oz (1.1 g)	0.004 oz (0.11 g)	0.01 oz (0.4 g)		0.04 oz (1.0 g)		0.03 oz (0.85 g)
	CHEMICAL AND MECHANICAL RESISTANCE									
Water	IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h							IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h		
Pressure	70 bars, 3 min isostatic							70 bars, 3 min isostatic		
Withstands Exposure To	Bleach (5%), caustic soda (pH 11), formic acid (pH7), gasoline, HCL (10%), oil, petroleum, salt water				Fuel B, mineral and vegetable oils, petroleum, salt mist		Hydrogen peroxide (5%), industrial laundry detergent (pH 10 - 11), neutralizing agent, perchlorethylen (100%)			
Environmental Test Conditions	68° F (20° C), 100 h									
Vibration	IEC 68.2.6 [10g, 10...2000Hz, 3 axis, 2.5 h]									
Shock	IEC 60068-2-27:2008 [40g, 18ms, 6 axis, 2000 x]									
Drop Test	100 x 6 ft (1.8 m)									
Axial/Radial Force	800 N / 500 N, 10 sec			1000 N / 1000 N, 10 sec	800 N / 500 N, 10 sec		800 N / 500 N, 10 sec			
	THERMAL									
Storage	-40° to +266° F (-40° to 130° C), 1000 h			-13° to +248° F (-25° to +120° C), 1000 h	-40° to +194° F (-40° to +90° C), 1000 h		-40° to +185° F (-40° to +85° C), 1000 h			
Operating	-13° to +185° F (-25° to +85° C)	-40° to +185° F (-40° to +85° C)				-40° to +194° F (-40° to +90° C)		-13° to 185° F (-25° to +85° C)		
Shock/Fatigue	68° to +320° F (20°C to +160°C), 100 x 5 min with 30 sec transition				-40° to +194° F (-40°C to +90°C), 100 x 5 min with 30 sec transition		68° to +356° F (20°C to +180°C), 300 x 5 min with 30 sec transition			
Peak	320° F (160° C), 35 h						248° F (120° C), 100 h, 428° F (220° C), 30 sec		248° F (120° C), 100 h	
Spin dryer / tunnel finisher (set point)				347° F (175° C), 100 x 10 min			347° F (175° C), 100 x 10 min			
	OTHER									
Standards	EN 60079-0:2009, EN 60079-11:2007, EN 50303:2001				EN 60079-0:2009, EN 60079-11:2007, EN 50303:2001 ISO 15693, ISO 18000-3 , NFC Tag Type 5 (optional)					
Options	Custom printed logo				Custom printed logo, Vigo chip 1.6K			Custom embossed logo, UID laser engraving		Laser engraving
Box Size	2,500 pcs			2,000 pcs	5,000 pcs	2,500 pcs		2,000 pcs		
Warranty	2 Years									



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +353 91 506 900
Asia Pacific: +852 3160 9800 | Latin America: +52 55 9171 1108
For more global phone numbers click here

© 2025 HID Global Corporation/ASSA ABLOY AB. All rights reserved.
2025-09-03-idt-rfid-il-logi-tag-family-ds-en PLT-00280
Part of ASSA ABLOY