

OMNIKEY® 4040 Mobile PCMCIA

Mobile Contact Smart Card Reader

- ▶ **Plug and Play** - Designed to facilitate easy device installation with high quality drivers* for all major PC operating systems
- ▶ **Readily Compliant** - Meets all relevant industry standards for smooth integration in PC environment
- ▶ **Convenient and Reliable** – Robust metal housing
- ▶ **Suits Any Application** - Compatible with virtually any smart card and major PC operating systems



ACCESS quality.

The OMNIKEY® 4040 reader is designed to secure laptops or other mobile devices using smart card technology that can be connected via PCMCIA. Small and handy, these mobile smart card readers offer the same firstclass technology as our desktop versions. Compliant with all major industry standards, the 4040 reader is compatible with virtually any contact smart card, operating system and application, making it the preferred solutions for integration into notebooks, PDA's or other PC bus-based systems.

- ▶ Designed to meet all major standards like ISO 7816, EMV (Europay®, Mastercard®, Visa®) 2000, Microsoft WHQL, PC/SC, HBCI (Home Banking Computer Interface) and PC-2001 Specification
- ▶ Readers work well with all relevant industry standards, including PC/SC, CT-API or OCF (Open Card Framework)
- ▶ Utilizes the OMNIKEY® Smart@Bus Chipset
- ▶ Meets GSA FIPS 201 requirements
- ▶ Robust metal housing for added durability
- ▶ Data transmission speed to the card of up to 420 Kbps.
- ▶ Supports all major operating systems
- ▶ Reader can be customized with company logo or corporate colors
- ▶ Provides added security for mobile devices against unauthorized access or unsecured remote log-on to networks
- ▶ Compliant with all major industry standards

* For driver download, please visit www.omnikey.com.

Specifications

Base Model Number	OMNIKEY® 4040
Dimensions	3.35" x 2.13" x 0.2" / 85 x 54 x 5 mm
Weight	2.12 oz / 60 g
Power supply	PCMCIA slot
Operating temperature	32°-131° F (0° - 55° C)
Operating humidity	10-90% rH
HOST INTERFACE	
Host Interface	PCMCIA
Transmission speed	16 Mbps
SMART CARD INTERFACE	
Standards	ISO 7816 & EMV ² 2000 Level I
Protocols	T=0, T=1, 2-wire: SLE 4432/42 (S=10), 3-wire: SLE 4418/28 (S=9), I ² C (S=8)
Card size	ID-1 (full-size)
Smart Card interface speed	420 kbps (when supported by card)
Smart Card clock frequency	Up to 8 MHz
Supported card types	5V, 3V and 1.8V Smart Cards, ISO 7816 Class A, B and C
Power to Smart Card	60 mA
Smart Card detection	Movement detection with auto power-off / Automatic detection of smart card type/ Short circuit and thermal protection
8 Pin Handling	C4 / C8 supported
Supported APIs	PC/SC driver (ready for 2.01), CT-API (on top of PC/SC), Synchronous-API (on top of PC/SC), OCF (on top of PC/SC)
PC/SC Driver Support	Windows® 2000 / XP (32bit), Windows® CE 5.0 / CE.NET / CE 6.0 (depending on hardware), Windows® XP 64bit, Windows® Vista (32bit / 64bit), Windows 7 (32bit / 64bit), Linux®
Embedded Technology	OMNIKEY Smart@Bus Chipset
Color	Silver
Options	Customer Specific Label: Available upon request
Composition	Stainless Steel
Durability	30,000 Insertions
Meantime between failure (MTBF)	500,000 hours
Compliance / Certification	Microsoft® WHQL ³ , EMV ² 2000 Level I, ISO 7816, HBCI ⁴ , USB 2.0 (USB 1.1 compatible), CCID ¹ , GSA FIPS 201 approved product list
Safety / Environmental	CE, WEEE, FCC, UL, VCCI, MIC, RoHS
Warranty	Two year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

1 = Chip Card Interface Device, 2 = Europay® MasterCard® Visa®, 3 = Windows® Hardware Quality Lab, 4 = Home Banking Computer Interface



© 2008 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 08/2008

MKT-OMNIKEY_4040_DS-EN

ACCESS experience.

hidglobal.com

HID Global Offices:

Corporate North America
15370 Barranca Pkwy
Irvine, CA 92618
U.S.A.
Phone: 800 237-7769
Phone: +1 949 732-2000
Fax: +1 949 732-2360

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Phone: +852 3160-9800
Fax: +852 3160-4809

Latin America
Circunvalacion Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Tel: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Haverhill Business Park
Phoenix Road
Haverhill, Suffolk
CB9 7AE
England
Phone: +44 (0) 1440 714 850
Fax: +44 (0) 1440 714 840