
QuickSpecs

Overview



Models

HP USB Receipt Printer EY023AA

Introduction

The HP USB Receipt Printer is the ideal single station thermal receipt printer for retail environments. Its compact size makes the HP USB Receipt Printer one of the smallest on the market today - perfect for space-constrained locations.

The HP USB Receipt Printer features a large 90mm paper roll capacity and prints up to 38 lines per second making it one of the fastest printers in its class, dramatically reducing wait times at the point of sale.

The HP USB Receipt Printer is the ideal printing companion for the HP Point of Sale System rp5000 and rp5700 and the HP Cash Drawer (Model No. EY026AA).

Key Benefits

- Compact sized with large paper roll capacity
- Prints up to 38 lines per second making it one of the fastest receipt printers in the retail industry today
- 8 dots/mm print resolution with up to 130 mm/sec throughput speed
- Connector for 1 cash drawer
- Powered by USB connection
- Selectable 44 or 56 columns of print on 80 mm wide thermal paper
- Clamshell™ drop-in paper loading system



QuickSpecs

Overview

Compatibility

The HP USB Receipt Printer is compatible with the HP Point of Sale System rp5000 and rp5700.

Service and Support

Your Option Limited Warranty is a one (1) year (HP Option Limited Warranty Period) parts replacement warranty on any HP-branded or Compaq-branded options (HP Options). If your HP Option is installed in an HP Hardware Product, HP may provide warranty service either for the HP Option Limited Warranty Period or the remaining Limited Warranty Period of the HP Hardware Product in which the HP Option is being installed, whichever period is the longer but not to exceed three (3) years from the date you purchased the HP Option.



QuickSpecs

Technical Specifications

Dimensions (H x W x D) 5.3 x 5.6 x 7.3 in (13.4 x 14.4 x 18.5 cm)

Paper roll dimensions 3.15 x 3.55 in Dia (8 x 9 cm Dia)

(W x D)

Weight 3 lbs (135 g)

Print method Direct thermal, 203 DPI
Paper type Direct thermal POS Grade(s)

Character cell size 13 x 24, 10 x 24

CPI 15.6, 20.3

Print columns 44 and 56 columns

Bar codes UPC-A, UPC-E, Code 39, Code 128, EAN128, Jan8 and Jan13 (EAN), Interleaved 2 of 5,

Codabar, PDF417

Printing speed Up to 38 lines per second (130 mm/s)

Auto cutter Full and partial cut selectable

Data butter 4K

User memory 256K up to 1792K Flash Shared (graphics, logo, user defined characters)

Communications Mother/Daughter board architecture

Interface Powered USB (24V)
Power 24 VDC +/-5%

Certifications EMI: FCC, ICES-003, VCCI: Class A; CE, Austel: Class B Safety, UL 1950, CSA 22.2 No. 950,

CE (EN60950), MITI (power supply), WHQL, USB-IF

Reliability 150 km paper/55 million lines/1.5 million autocuts

Control Language Application Compatible Escape Commands

Emulation modes Native (A794)

A793

Legacy (application escape commands)

Printer class

Printer drivers Windows XP/OPOS 1.4/OPOS

Kit Contents HP USB Printer, Starter paper roll, Powered USB cable, Point of Sale System Software and

Documentation CD and the Options Warranty Manual

© Copyright 2007 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are US registered trademarks of Microsoft Corporation.

