

HP L6015tm and L6017tm Retail Touch Monitors

Retail touch displays designed for increased usability, superior durability, and a modernized appearance that seamlessly integrate into retail environments.



The sleek and stylish HP L6015tm 15-inch and L6017tm 17-inch Retail Touch Monitors¹ are designed for increased performance, enhanced usability, and outstanding durability in retail environments. Both monitors feature multi-touch Projected Capacitive touch technology for a familiar, intuitive experience similar to smartphone and tablet devices.

Retail-ready

The modernized appearance and sleek design add a wow factor to your retail environment. The chemically strengthened, flush-glass design is both stylish and easy to clean.

White LED industrial panels offer improved brightness, extended product life, and energy efficiency. Anti-glare screens help make content and graphics easier to read in ambient light. The sturdy design withstands environments up to 40° C and areas with low air circulation.

The standard aspect ratio screens are compatible with the vast majority of retail applications and are ideal for use in small spaces. The On-Screen Display lockout function helps prevent accidental adjustment of display settings by associates or customers.

Flexible design

Industry-standard, 100-mm VESA patterns enable flexible mounting in a variety of retail settings. An optional stand is also available for additional user adjustability and flexibility.¹

Technology that grows with you

DisplayPort, DVI, and VGA video inputs enable legacy and future video technology compatibility; integrated speakers eliminate the need for separate hardware. Four mounting ports on each side of the bezel accept integration of an HP Magnetic Stripe Reader, Biometric Fingerprint Reader, and Webcam to enhance functionality and maximize counter space.^{2,3}

Designed with the environment in mind

Both monitors are ENERGY STAR[®]-qualified and registered as EPEAT[®] Gold to help reduce your impact on the environment and lower operating costs.⁴

Industry-leading warranty and support

The monitors are backed by a three-year limited warranty that includes Advanced Exchange.⁵ For more information about HP Retail Solutions, please visit <u>www.hp.com/qo/pos</u>.





HP L6015tm and L6017tm Retail Touch Monitors

SPECIFICATIONS				
Product	HP L6015tr	n Retail Touch Monitor	HP L6017tm Retail Touch Monitor	
Product number		A1X78AA	A1X77AA	
Panel type	15-inch diag. TN (Tv	visted Nematic) LED Backlit LCD	17-inch diag. TN (Twisted Nematic) LED Backlit LCD	
Viewable image area		(38 cm) diagonal	17 in (43.18 cm) diagonal	
Viewing angle		izontal/140 degrees vertical	170 degrees horizontal/160 degrees vertical	
		imum contrast ratio)	(10:1 minimum contrast ratio)	
Brightness ⁶		50 nits (cd/m ²)	$270 \text{ nits } (cd/m^2)$	
Contrast ratio ⁶		700:1	800:1	
Response rate ⁶			30 ms	
•		25 ms		
Frequency			KHz; Vertical: 50 to 76 Hz	
Native resolution		@ 60 Hz (recommended)	1280 x 1024 @ 60 Hz	
Preset VESA Graphic Mo	des 1024 x 768 ወ	60 Hz, 800 x 600 @ 60 Hz,	1280 x 1024 @ 60 Hz, 1024 x 768 @ 60 Hz,	
(non-interlaced)		70 Hz, 640 x 480 @ 60 Hz	800 x 600 @ 60 Hz, 720 x 400 @ 70 Hz, 640 x 480 @ 60 Hz	
Ports and connectors	(1)	(1) VGA,(1) DisplayPort, and (1) DVI-D Note: HDCP supported on digital inputs.		
Input cables		VGA, DVI-D, DisplayPort, audio, USB, and power cord; each 5.9 ft (1.8 m)		
User controls (on-screei	Brightness, Contrast, Color Temperature, Image Control, OSD Control, Management, Language, Information, Factor			
display)		Reset, Source Control, Exit		
Input power		Input Voltage: 90 to 265 VAC; Frequency: 50/60 Hz		
Power consumption	Tup : 20 W. May	: 30 W; Sleep:1 W; Off: 0.5 W	Typ.: 20 W, Max.: 35 W, Sleep: 1 W, Off: 0.5 W	
Dimensions (w × d × h)		tand: 14.4 x 11.2 x 16.3 in	Unpacked w/ stand: 15.2 x 11.1 x 16.7 in	
	-		•	
	· · · · ·	x 18.3 x 41.4 cm)	38.6 x 28.3 x 42.3 cm)	
		only: 14.4 x 2.3 x 12.3 in	Display head only: 15.2 x 2.3 x 13.3 in	
Package		x 5.8 x 31.3 cm)	38.6 x 5.8 x 33.9 cm	
		: 16.9 x 6.14 x 15.4 in	Packaged: 17.8 x 6.3 x 16.6 in	
		x 15.6 x 39.2 cm)	45.1 x 16 x 42.2 cm	
Weight (head only)		ay head only: 8.82 lb (4 kg)	Unpacked display head only: 10.36 lb (4.7 kg)	
		/ stand: 14.99 lb (6.8 kg)	Unpacked w/ stand: 16.53 lb (7.5 kg)	
	Packaged display	y head only: 12.76 lb (5.9 kg)	Packaged display head only: 14.33 lb (6.5 kg)	
Temperature		5° to 40° C (41° to 104° F)		
Certification and		UL Listed, CSA for Canada and US, FCC approval, ICES, BSMI for Taiwan, CCC/CECP/SEPA/CEL for China, C-Tick for		
compliance	Austra	Australia, S-Mark for Argentina, CB, CE approval, VCCI, ENERGY STAR [®] , EPEAT [®] Gold ⁴		
Limited warranty ⁵		Protected by HP, including a 3 years parts, 3 years labor, and Advanced Exchange (3/3/0) standard limited warranty		
• • • • • • • • • • • • • • • • • • •	Certain restrictions and exclusions apply. ies included (1) VGA, (1) DisplayPort, and (1) DVI-D cables, (1) detachable AC power cord, documentation kit, and user			
Accessories included	(1) VGA, (1) Display	Port, and (1) DVI-D cables, (1) det	achable AC power cord, documentation kit, and user CD.	
OPTIONS ^{1,2,3}				
62	HP Retail Integrated	Additional security for retailers a	at the POS by enabling employee authentication procedure	
	Fingerprint Reader for opening the cash drawer to dispense cash and for approving certain transa			
	(QZ672AA)	······································		
61	-			
	HP Retail Integrated		tions or loyalty card integration without adding clutter to	
	Dual-Head MSR (QZ673AA)	the retail work space.		
	HP Retail Integrated	Enables interactive technical sur	oport for retail serviceability; supports personalized	
	Webcam (QZ700AA)	customer interface with online/remote customer service representatives in a kiosk setup.		
(***)	HP Height-Adjustable	Set the display on a counter or co	ash drawer. This retail-hardened, small footprint stand	
	Stand for Touch Monitors		ployees and customers. Maximum vertical adjustment and	
	A1X81AA)			
			he display to be customized for your exact countertop work	
1 m l			positioning for vertical viewing or recessed flat for top-dow	
		viewing.		

1. The HP L6015tm and the L6017tm come standard as a head-only displays. The optional stand (A1X81AA) may be purchased separately. 2. HP does not support the use of any other standard USB device beyond the HP Retail Integrated Fingerprint Reader (QZ672AA), HP Retail Integrated Dual-Head MSR (QZ673AA), and HP Retail Integrated Webcam (QZ700AA). 3. Internet access required for Webcam. 4. EPEAT® Gold where HP registers commercial display products. See <u>www.epeat.net</u> for registration status in your country. 5. Certain restrictions and exclusions apply. HP Care Pack Services extend service contracts beyond the standard warranties. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at <u>www.hp.com/qo/lookuptool</u>. Additional HP Care Pack Services information by product is available at <u>www.hp.com/hps/carepack</u>. 6. All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

© 2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. To learn more, visit www.hp.com. May 2012