Overview



Input/Output		Controls	
Touch USB	Connects a touch USB cable from the computer to the display.	INPUT	Changes the input source.
HDMI	Connects voice or audio input cable.	MENU	Accesses the main menus, or saves your input and exits the menus.
DP IN	Connects DisplayPort in cable to the display.	ΛV	Moves the selection up and down.
DP OUT	Connects DisplayPort out cable to the display.	< >	Adjusts the volume level.
LAN/VOE	Connects a local area network cable.	AUTO/SET	Displays the current signal and mode. Press
SPEAKER OUT	Connects optional external speakers to the display.		this button to adjust the screen automatically (RGB mode only).
AUDIO IN	Connects an audio cable to the display.	%/I	Turns the power on or off.
RGB/VGA COMPONENT OUT	Connects an RGB/VGA component out cable to the display.		
RGB/VGA COMPONENT IN	Connects an RGB/VGA component in cable to the display.		
RS-232C OUT	Connects an RS-232C out cable to the display.		
RS-232C IN	Connects an RS-232C in cable to the display.		
USB	USB Connects a USB cable to the display.		

**IR IN** 

Connects an IR cable to the display.

# HP LD4245tm 41.92-inch Interactive LED Digital Signage Display

# QuickSpecs

**Overview** 

Model

F1M93AA, F1M93AC



# QuickSpecs

### **Technical Specifications**

Panel	Panel	IPS, LED with direct backlit
	Viewable Image Area	106,467 cm (41.92 in) widescreen; diagonally measured
	Panel Active Area (W x H)	<b>92,79 x 52,19cm</b> (36.53 x 20.54 in)
	Aspect Ratio	16:9
	Viewing Angle (typical)	Up to 178° horizontal/178° vertical (10:1 minimum contrast ratio)
	Brightness (typical)*	340 cd/m <sup>2</sup>
	Static Contrast Ratio (typical)*	1000:1
	<b>Dynamic Contrast Ratio</b> (typical)*	500,000:1
	Response Time (typical)*	6 ms gray to gray
	Pixel Pitch	0.4833 mm
	Color Gamut	68%
	Color Support**	Can display up to 16.7 million colors
	The state of the s	ions represent the typical specifications provided by HP's component ormance may vary either higher or lower. nology.
Touch Frame	Touch Module Type	IR Spread Technology; 5-point multitouch plus gesture
Specifications	Touch Input	Finger, gloved hand, or passive stylus (?8mm diameter)
	<b>Touch Point Response</b>	<10ms with dual touch
	Refresh Rate	100 point/ sec (single-and multi-touch)
	Positional Accuracy	< ± 1.0mm @ 95% area
	Controller Resolution Support	1920 x 1080
	Glass Transmission	85%
	<b>Touch Certification</b>	No certification, only supports Win-7 and Win-8 functionality
On Screen Display	<b>Buttons or Switches</b>	Input, menu, ≜up, ▼down, ◀left, ▶right, auto/set, power
(OSD) Controls	Languages	9 (German, Simplified Chinese, Traditional Chinese, English, Spanish, French, Italian, Dutch, and Portuguese)
	User Controls	Brightness, Contrast, Backlight, Sharpness, Color, Tint, Color temperature, Image Control, Sound Mode, Input, Aspect Ratio, Audio, Time, Language, Factory Reset
	User Programmable Modes	10
	Audio Controls*	Infinite Sound, Treble, Bass, Standard, Music, Cinema, Sport, Game. *NOTE: Monitor does not ship with speakers (available as an accessory)
Signal Interface/	<b>Horizontal Frequency</b>	30 to 83 kHz
Performance	<b>Vertical Frequency</b>	50 to 60 Hz
	Recommended Resolution	1920 x 1080 @ 60 Hz
	Max Resolution	1920 x 1080 @ 60 Hz



## QuickSpecs

#### **Technical Specifications**

 Preset VESA Graphic
 1920 x 1080 @ 60 Hz

 Modes
 1680 x 1050 @ 60Hz

 (non-interlaced)
 1600 x 900 @ 60Hz

1440 x 900 @ 60Hz 1280 x 1024 @ 60 Hz 1280 x 800 @ 60 Hz

1280 x 720 @ 60 Hz 1024 x 768 @ 60 Hz 800 x 600 @ 60 Hz 720 x 400 @ 70 Hz 640 x 480 @ 60 Hz

**Maximum Pixel Clock** 

**Speed** 

150 MHz (Digital and Analog)

Anti-Glare Yes

**Default Color** Standard (9300K)

Temperature

Plug and Play Yes

Pluy allu Play

Input Signal RGB/VGA, DisplayPort 1.1a, HDMI (HDCP support on DisplayPort and HDMI)

Output RGB/VGA, DisplayPort 1.1a out for tiling

**USB** (1) USB 2.0 input for use with HP Media Sign Player, Type A port

**USB Touch** (1) USB 2.0 port for powering touch module, Type B port **LAN (RJ45)** (1) RJ45 Input, command, control and video over Ethernet

RS232C In and Out

Audio (1) audio input jack

Speakers Not included

IR (1) input

Video Cables included (1)VGA, (1) HDMI, (1) DisplayPort

Video Cable Lengths 1,8 m (5.9ft )
Power Supply Internal

Input Power 100 ~ 240 VAC Frequency 50~60Hz Typical Power 95 W

Consumption

**Maximum** 105 W (without speakers)

**Power Saving** = 2.0W when Wake on Lan is on; = 0.5W when Wake on Lan is off

Power Cable Length 1,8 m (5.9 ft )

Mechanical Dimensions Unpacked (head only) 99,09 x 9,27 x 58,5cm

 $(W \times D \times H)$  (39.01 x 3.64 x 23.03 in)

Packaged 108,7 x 73,6 x 23 cm

(47.79 x 28.97 x 9.05 in)

Bezel Width Left/right and 15 mm (.59 in)

top/bottom

Video/

Power

Other I/O

## QuickSpecs

#### **Technical Specifications**

Weight - maximum	Unpacked	<b>20,7 kg</b> (45.63 lb)
	Packaged	<b>24,3 kg</b> (53.57 lb)
Tilt Range	None	
Swivel Range	None	
Height Adjustable	None	
<b>Pivot Rotation</b>	None	
Base (feet/stand)	There is no stand included.	
Temperature - Operating	<b>0° to 40° C</b> (32° to 104° F)	
Temperature - Non- operating	<b>-20° to 60° C</b> (-4° to 140° F)	
<b>Humidity - Operating</b>	20% to 80% non-condensin	g
<b>Humidity - Non-operating</b>	5% to 95%, 38.7° C max we	t-bulb
Altitude - Operating	<b>0 to 5000 m</b> (0 to 16,400 ft)	
Altitude - Non-operating	<b>0 to 12192 m</b> (0 to 40,000 f	t)
White LED Backlights	Yes	
CCFL Panel	No	
Arsenic-Free Display Glass	Yes	
Low Halogen <sup>3</sup>	No	
Mercury- Free Display Backlighting	Yes	
<b>Eco-Label Certifications</b> T	his product has received or i	s in the process of bei

#### **Environmental Data**

**Environmental** 

& declarations

**Eco-Label Certifications** This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

• IT ECO declaration

#### **Energy Consumption** (in accordance with US **ENERGY STAR® test**

method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz	
Normal Operation	81.4 W	80.1 W	82.3 W	
Sleep	0.58 W	0.71 W	0.58 W	
Off	0.28 W	0.39 W	0.27 W	

<b>Heat Dissipation*</b>	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz	
Normal Operation	278 BTU/hr	274 BTU/hr	281 BTU/hr	
Sleep	2 BTU/hr	2 BTU/hr	2 BTU/hr	
Off	1 BTU/hr	1 BTU/hr	1 BTU/hr	

<sup>\*</sup> Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

#### **Additional Information**

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.
- This HP product is designed to comply with the Waste Electrical and

# HP LD4245tm 41.92-inch Interactive LED Digital Signage Display

### **Technical Specifications**

Electronic Equipment (WEEE) Directive - 2002/96/EC.

- This product is in compliance with California Proposition 65 (State of California: Safe Drinking Water and Toxic Enforcement Act of 1986).
- Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.
- This product contains 0 % post-consumer recycled plastic (by wt.)
- This product is 99 % recycle-able when properly disposed of at end of life.

2876 g

Packaging Materials External: PAPER/Corrugated

**Internal:** PLASTIC/EPP (Expanded 671 g

Polypropylene)

**RoHS Compliance** 

Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis. By July 1, 2006, RoHS substances will be virtually eliminated (virtually = to levels below legal limits) for all HP electronic products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive).

**Material Usage** 

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at: (http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) except for wires and cables, and certain retail
  packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

**Packaging** 

HP follows these guidelines to decrease the environmental impact of product packaging:



#### HP LD4245tm 41.92-inch Interactive LED Digital Signage Display

#### **Technical Specifications**

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

### and Recycling

End-of-life Management Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to:

> http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

#### **Hewlett-Packard** Corporate **Environmental** Information

For more information about HP's commitment to the environment:

#### **Global Citizenship Report**

http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html

**Eco-label certifications** 

http://www.hp.com/hpinfo/globalcitizenship/environment/

productdesign/ecolabels.html

ISO 14001 certificates:

http://www.hp.com/hpinfo/globalcitizenship/environment/operations/

envmanagement.html

### **Options**

(sold separately)

**HP DSD Speakers - Part** number F2B36AA

**HP DSD Security Wall** Mount - Part number WB975AA

Ability to install in a variety of commercial applications where an extra-large screen is desired. Enables bundling with select HP Media Players, Thin Clients, or EliteDesk Mini & USDT PC's, directly behind the display, away from view, for a guick and easy comprehensive solution.

Includes a Quick Release for easy mounting and removal of a compatible HP Thin Client or HP USDT PC. Supports 40" to 60" display sizes. Weight

restrictions may apply.

Includes tilt friction knobs to retain tilt in any position.

HP MP4 Model 4200. Digital Signage Player -

Part number G5R07UT/G5R07UA Attract and inform your customers with the compact and affordable HP MP4 Digital Signage Player, Model 4200, designed to drive static screen layouts and full-screen

video signage content.4



### **Technical Specifications**

HP MP9 Model 9000,

Digital Signage Player -

Part number G5R08UT/G4R08UA Boost sales and engage customers with compelling dynamic and interactive signage content driven by the HP MP9 Model 9000, HP's smallest and most powerful digital signage player.4

**HP Digital Signage** A range of installation service Care Packs. See **Installation Service** 

www.hp.com/go/digitalsignage.

What's in the box? **Display and Accessories** 

HP LD4245tm 41.92-inch Interactive LED Digital Signage Display

VGA cable (1.8m) 5.9 ft HDMI cable (1.8m) 5.9 ft DisplayPort cable (1.8m) 5.9 ft

USB cable Type A male to Type B male(1.8 m) 5.9 ft

IR Receiver cable (1.5 m) 4.9 ft Wireless remote control

**Documentation** CD (includes user guide, warranty, drivers) **Featured Software** Network Sign Manager, Video Over Ethernet

**User Guide Languages** EMEA Region: Danish, Dutch, Finnish, French, German, Italian, Norwegian,

Spanish (Int'l), Swedish, Czech, Greek, Hungarian, Polish, Russian, Slovenian,

Turkish, Arabic, Kazakh

Americas Region: English, French, Spanish, B. Portuguese APJ Region: English, S. Chinese, T. Chinese, Bahasa Indonesia

**Warranty Languages** EMEA Region: Danish, Dutch, Finnish, French, German, Italian, Norwegian,

Spanish (Int'l), Swedish, Czech, Greek, Hungarian, Polish, Russian, Slovenian,

Turkish, Arabic, Kazakh

Americas Region: English, French, Spanish, B. Portuguese APJ Region: English, S. Chinese, T. Chinese, Bahasa Indonesia

Black Color

**VESA External Mounting** Yes, 200 x 200mm

**Security Lock-Ready** Yes

**Certification and** Compliance

CE, CB, NOM, PSB, ICE, TUV-S, CCC, BSMI, FCC, C-UL, PSB, C-Tick, SmartWay Transport Partnership (NA), Microsoft WHQL Certification (Windows 8.

Windows 7).

Compatibility Compatible with platforms using the VESA standard video modes.

Recommended for use with HP products.

**Country of Origin** South Korea

**Service and Warranty** Protected by HP, including a 3 year standard limited warranty. Optional Care Pack Services are extended

service contracts which go beyond your standard warranties.5



**Other** 

## HP LD4245tm 41.92-inch Interactive LED Digital Signage Display

## QuickSpecs

#### **Technical Specifications**

- © Copyright 2014 Hewlett-Packard Development Company, L.P.
- 1. HD content required for HD images.
- 2. All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.
- 3. External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.
- 4. Mounting hardware sold separately.
- 5. HP Care Pack Services are sold separately. Service levels and response times for HP Care Pack Services may vary depending on your geographic location. Service starts from date of hardware purchase. Restrictions and limitations apply. See <a href="https://www.hp.com/go/cpc">www.hp.com/go/cpc</a> for details.

All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

