# HP LaserJet Enterprise M608 series



## The pinnacle of performance and security.

This HP LaserJet Printer with JetIntelligence combines exceptional performance and energy efficiency with professional-quality documents right when you need them – all while protecting your network from attacks with the industry's deepest security<sup>1</sup>



HP LaserJet Enterprise M608n



HP LaserJet Enterprise M608dn



Tray input

Instant-on technology



The world's most secure printing<sup>1</sup>

- With HP Sure Start, each printer regularly checks its operating code and repairs itself from attempted hacks.
- Whitelisting checks firmware during startup to help ensure it's authentic, good code digitally signed by HP.
- Run-time intrusion detection continually monitors activity to detect and stop attacks, then automatically reboots.
- Centralise control of your printing environment with HP Web Jetadmin and help build business efficiency.  $^{\rm 2}$

#### High-speed performance meets energy efficiency

- Speed through tasks and save paper. Print two-sided documents nearly as fast as single-sided.
- This printer wakes up fast and prints your first page faster in as quickly as 7.9 seconds.  $^{\rm 3}$
- This printer uses exceptionally low amounts of energy thanks to its innovative design and toner technology.<sup>4</sup>

## More. Pages, Performance, and Protection.<sup>5</sup>

- Produce sharp text, bold blacks, and crisp graphics with precision black toner.
- Original HP Toner cartridges with JetIntelligence deliver more pages per cartridge than predecessors.<sup>5</sup>
- Help retain the Original HP quality you paid for with anti-fraud and cartridge authentication technology.
- Spend less time replacing toner, and more on business. Choose high-yield toner cartridges.  $^{\rm 6}$

## Product walkaround

### HP LaserJet Enterprise M608x shown

- Hardware Integration Pocket
   10.9 cm colour touchscreen control panel
   Easy-access USB port
   100-sheet multipurpose tray 1
   Front door access to toner cartridges
   550-sheet input tray 2
   550-sheet input tray 3
   500-sheet output bin
   Automatic two-sided printing
   Wi-Fi Direct®/Bluetooth® Low Energy
   Host USB port
- 12. Gigabit Ethernet network port
- 13. Hi-Speed USB 2.0 printing port
- 14. Slot for cable-type security lock



## Series at a glance



Model	HP LaserJet Enterprise M608n	HP LaserJet Enterprise M608dn	HP LaserJet Enterprise M608x	
Product number	K0Q17A	K0Q18A	K0Q19A	
Print speeds (A4)	Up to 61 ppm			
Control panel	6.9 cm LCD with keypad 10.9 cm cc		10.9 cm colour touchscreen	
Automatic two-sided printing	Not available	Not available Yes		
Hardware Integration Pocket	Not available	Yes		
100-sheet tray 1, 550-sheet tray 2	Yes			
550-sheet paper feeder	Optional (up to four)		Yes (plus up to three optional)	
2.100-sheet paper feeder	Optional			
Envelope feeder	Optional (up to two)			
Printer stand	Optional			
5-bin stapler/stacker/mailbox with job offset	Optional			
Direct mobile printing	Optional wireless direct/NFC		Embedded Wi-Fi Direct/Bluetooth Low Energy	
Wireless networking	Opti	Optional Embedded		
HP High-Performance Secure Hard Disk	Optional			

## Accessories, Supplies and Support

Supplies	CF237A HP 37A Black Original LaserJet Toner Cartridge (11,000 pages)
	CF237X HP 37X High Yield Black Original LaserJet Toner Cartridge (25,000 pages)
	CF237Y HP 37Y Extra High Yield Black Original LaserJet Toner Cartridge (41,000 pages)
	LOH25A HP LaserJet 220V Maintenance Kit (Up to 225,000 pages)
Accessories	B5L28A HP Internal USB Ports
	LOH17A HP LaserJet 550-sheet Paper Tray
	LOH18A HP LaserJet 2100 Sheet Paper Tray
	LOH19A HP LaserJet Printer Stand
	LOH20A HP LaserJet Stapler/Stacker/Mailbox
	LOH21A HP LaserJet Envelope Feeder
	LOH22A HP LaserJet Extension Tray Cover
	B5L29A HP High-Performance Secure Hard Disk
	J8030A HP Jetdirect 3000w NFC/Wireless Accessory
	J8031A HP Jetdirect 2900nw Print Server
Service and Support	U9NEOE HP 3 year Next Business Day Hardware Support with Defective Media Retention for LaserJet Enterprise M608 U9NE1E HP 4 year Next Business Day Hardware Support with Defective Media Retention for LaserJet Enterprise M608 U9NE2E HP 5 year Next Business Day Hardware Support with Defective Media Retention for LaserJet Enterprise M608 U9NG4PE HP 1 year Post Warranty Next Business Day Hardware Support with Defective Media Retention for LaserJet Enterprise M608 U9NG5PE HP 2 year Post Warranty Next Business Day Hardware Support with Defective Media Retention for LaserJet Enterprise M608

## Technical specifications

Model	HP LaserJet Enterprise M608n	HP LaserJet Enterprise M608dn	HP LaserJet Enterprise M608x
Product number	KOQ17A	K0Q18A	K0Q19A
Functions	Print	•	•
Control panel	6.86 cm (2.7 in) QVGA LCD (colour graphics), rotating (adjustable angle) display with 24-key pad		10.92 cm (4.3 in) Colour Graphics Display (CGD) with touchscreen, rotating (adjustable angle) display, home button
Print			·
Print technology	Laser		
Print speed <sup>1</sup>	Black (A4, normal) Up to 61 ppm;	Up to 61 ppm; Black (A4, normal) Up to 61 ppm; Black (A4, duplex): Up to 50 ppm;	
First page out <sup>2</sup>	Black (A4, ready): As fast as 5.4 sec; Black (A4, sleep): As fast as 7.9 sec;		
Print resolution	Black (best): Up to 1200 x 1200 dpi; Technology: FastRes 1200; 1200 x 1200 dpi;		
Monthly duty cycle	Up to 275,000 pages A4; Recommended monthly page volume: 5,000 to 25,000		
Printer smart software features	Print preview, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy- access USB	Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB	
Standard print languages	HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™		
Fonts and typefaces	105 internal TrueType fonts scalable in HP PCL, 92 in (Andale Mono WorldType); 2 Internal Windows Vista & Fonts and IPDS Emulation available at http://www.hp	ternal scalable fonts in HP postscript level 3 emulati 3 Fonts (Calibri, Cambria); Additional font solutions av 0.com/go/laserjetfonts	on (Euro symbol built-in); 1 internal Unicode Fonts vailable via third-party flash memory cards; HP LaserJet
Print area	Print margins Top: 4.3 mm, Bottom: 4.3 mm, Left: 4.3 mm, Right: 4.3 mm; Maximum print area:		
Duplex printing	Manual (driver support provided)	Automatic (standard)	

Data sheet | HP LaserJet Enterprise M608 series

Model	HP LaserJet Enterprise M608n	HP LaserJet Enterprise M608dn	HP LaserJet Enterprise M608x
Product number	KOQ17A	K0Q18A	K0Q19A
Processor speed	1.2 GHz		•
Connectivity	•		
Standard	1 Hi-Speed Device USB 2.0; 2 Hi-Speed USB 2.0 Host; 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network; Hardware Integration Pocket		1 Hi-Speed Device USB 2.0; 2 Hi-Speed USB 2.0 Host; 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network; Hardware Integration Pocket; 1 Wi-Fi direct 802.11b/g/n; 1 Bluetooth low energy I/O
Optional	HP Jetdirect 2900nw Print Server J8031A; HP Jetdirect 3000w NFC/Wireless Accessory J8030A		
Wireless	Optional, enabled with purchase of HP Jetdirect 2900nw Print Server J8031A or HP Jetdirect 3000w NFC/Wireless Accessory J8030A		
Mobile printing capability <sup>3</sup>	HP ePrint; Apple AirPrint™; Mopria-certified		HP ePrint; Wireless direct printing; Apple AirPrint™; Mopria-certified
Supported network protocols	Via built-in networking solution: TCP/IP, If AirPrint <sup>™</sup> , HP ePrint, FTP Print, Google CI ARP-Ping), IPv6 (Stateless Link-Local and Syslog; Security: SNMPv3, SSL Cert Mana	Pv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue su oud Print; DISCOVERY: SLP, Bonjour, Web Services Discovery; IP CC d via Router, Statefull via DHCPv6); Management: SNMPv2/v3, HTT igement, Firewall, ACL, 802.1x	ipport only), Web Services Printing, IPP 2.0, Apple INFIG: IPv4 (BootP, DHCP, AutolP, Manual, TFTP Config, IP/HTTPs, Telnet, TFTP Config, FTP FW Download,
Hard disk	Optional, 500 GB (with accessory B5L29/	A)	
Memory	Standard: 512 MB; Maximum: 1.5 GB, MA	X memory, when 1GB Accessory DIMM is installed	
Media handling			
Number of paper trays	Standard: 2 ; Maximum: Up to 6		Standard: 3 ; Maximum: Up to 6
Media types	Paper (plain, light, bond, recycled, heavy, letterhead, envelope, heavy envelope	extra heavy, cardstock, pre-printed, pre-punched, coloured, roug	h, heavy rough), monochrome transparency, labels,
Media size	Custom (metric): Feeder 1: 76 x 127 to 2 (metric): Feeder 1: A4, A5, A6, RA4, B5 (J B5, C6, DL ISO), Postcard (JIS single and c	Custom (metric): Feeder 1: 76 x 127 to 216 x 356 mm; Feeder 2: 99 x 148 to 216 x 356 mm, Feeder 3: 99 x 148 to 216 x 356 mm; Supported (metric): 	
	Standard input <sup>.</sup> 100-sheet multipurpose	Standard input: 100-sheet multipurpose feeder, 550-sheet input feeder, 550 accessory feeder Standard output: 500 sheet output bin	
Media handling	Standard input: 100-sheet multipurpose Standard output: 500 sheet output bin Optional input: Optional 1 × 550-sheet p optional 3 × 550-sheet paper feeder and sheet feeder and 1 × 2,000-sheet feeder	aper feeder, optional 1 x 550 paper feeder and stand with cabinet I stand. optional high-capacity paper feeder and stand with 1 x 55	stand, optional high-capacity paper feeder and stand with 1 x 550 sheet feeder and 1 x 2,000-sheet feeder
Media handling Media weight	Optional input: Optional 1 x 550-sheet p optional 3 x 550-sheet paper feeder and	aper feeder, optional 1 x 550 paper feeder and stand with cabinet I stand, optional high-capacity paper feeder and stand with 1 x 55	stand, optional high-capacity paper feeder and stand with 1 x 550 sheet feeder and 1 x 2,000-sheet

Model	HP LaserJet Enterprise M608n	HP LaserJet Enterprise M608dn	HP LaserJet Enterprise M608x
Product number	K0Q17A	KOQ18A	K0Q19A
Output capacity	Standard: Up to 500 sheets Envelopes: Up to 75 envelopes Transparencies: 200 Maximum: Up to 1,300 sheets		
Compatible operating systems			5, 8.6), Linux Fedora (22, 23, 24), Linux Mint (17, 17.1, .10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.11 dows 7 all 32/64-bit editions, Windows 8/8.1 all rofessional, etc.), Windows XP SP3 32-bit editions (XP
Compatible network operating systems	<ul> <li>Totile, XF Project.)</li> <li>Citrix MetaFrame Presentation Server 3.0, Citrix MetaFrame XP Presentation Server (Feature Release 1, 2, and 3), Citrix on Windows Server 2003/2003 R2, Citrix on Windows Server 2008/2008 R2/2008 R2 SP1, Citrix on Windows Server 2012/2012 R2, Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0 (Plus Feature Pack 2 &amp; 3) for Windows Server 2008 R2/2008 R2 SP1, Citrix on Windows Server 2012/2012 R2, Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0 (Plus Feature Pack 2 &amp; 3) for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit, Citrix XenApp 5.0 (For Windows Server 2012 and 2012 R2 Terminal Services, 64-bit), Citrix XenApp 5.6 (for Windows Server 2012 and 2012 R2 Terminal Services, 64-bit), Citrix XenDesktop 5.6 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix XenApp 5.6 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, 32/64-bit), Citrix XenDesktop 5.6/7.0/7.5 (for Windows Server 2008 R2 SP1 Terminal Services, SP), Novell Doen Enterprise Server 1/SP1, Novell Doen Enterprise Server 2 for Linux, Novell Servers 10.1, Novell Doen Enterprise Server 1/SP1, Novell Doen Enterprise Server 2 for Linux, Novell Servers Server 2.003/2003 R2 32/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster &amp; Terminal Services), Windows Server 2008 22/64-bit (SP2) Standard/Enterprise (+ Cluster &amp; Terminal Services), Windows Server 2008/2008 R2 32/64-bit (SP1) Standard/Enterprise (+ Cluster &amp; Terminal Services), Windows Server 2008/2008 R2 32/64-bit (SP2) Standard/Enterprise (+ Cluster &amp; Terminal S</li></ul>		
Minimum system requirements	Mac: 1.3 GB available hard disk space; US hardwar	e requirements see http://www.microsoft.com; ardware requirements see http://www.Apple.com for r	nore info
Software included	HP Connected, HP Device Experience (DXP), HP PCL 6 http://www.123.HP.com or OS App Source for printer	(XPS) Printer Driver, HP Software Installer/Uninstaller,	Mac OS Welcome Screen (Directs users to
Security management	Identity management: Kerberos authentication; LDAP authentication; 1000 user PIN codes; optional HP and 3rd party advanced authentication solutions (e.g.; badge readers); Network: IPsec/firewall with Certificate; Pre-Shared Key, and Kerberos authentication; Supports WJA-10 IPsec configuration Plug-in; 802.1X authentication (EAP-PEAP; EAP-TLS); SIMPPv3; HTTPS; Certificates; Access Control List; Data: Storage Encryption; Encrypted PDF & Email (uses FIP5 140 validated cryptographic libraries from Microsoft); Secure Erase; SSL/TLS (HTTPS); Encrypted Credentials; Device: Security lock slot; USB port disablement; Intrusion Detection with Red Balloon Security Technology - Constant in-device monitoring for attacks; SureStart Secure Boot - BIOS Integrity Checking with self-healing capability; Whitelisting - loads only known good code (DLLs, EXEs,); Security Manager, Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMS	Identity management: Kerberos authentication; LDAP authentication; 1000 user PIN codes; optional HP and 3rd party advanced authentication solutions (e.g.; badge readers); Network: IPsec/firewall with Certificate; Pre-Shared Key, and Kerberos authentication; Supports WJA-10 IPsec configuration Plug-in; 802.1X authentication (EAP-PEAP; EAP-TLS); SNMPV3; ITTPS; Certificates; Access Control List; Data: Storage Encryption; Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft); Secure Frase; SSI/TLS (ITTPS); Encrypted Credentials; Device: Security Mck slot; USB port disablement; Hardware integration pocket for security solutions; Intrusion Detection with Red Balloon Security Technology - Constant in-device monitoring for attacks; SureStart Secure Boot - BIOS Integrity Checking with self-healing with HP JetAdvantage Security Manager, Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMs	
Printer management	HP JetAdvantage Security Manager; HP SNMP Proxy A	gent; HP Web JetAdmin Software; HP WS Pro Proxy Ag	gent; Printer Administrator Resource Kit for HP
	Universal Print Driver		
Dimensions and weight Printer dimensions (W x D x H)	<b>Minimum</b> 431 x 466 x 380 mm; <b>Maximum</b> : 431 x 104	10 x 453 mm;	Minimum 431 x 466 x 505 mm; Maximum: 431 x 1100 x 581 mm;
Package dimensions (W x D x H)	597 x 497 x 539 mm		
	551 X 1255 1101		762 x 593 x 511 mm
Printer weight	21.6 kg		762 x 593 x 511 mm
Printer weight Package weight	21.6 kg 27.2 kg		
Printer weight Package weight <b>Operating environment</b>	21.6 kg 27.2 kg <b>Temperature</b> : 10 to 32.5°C; <b>Humidity</b> : 30 to 70% RH		762 x 593 x 511 mm
Printer weight Package weight Operating environment Storage conditions	21.6 kg 27.2 kg Temperature: 10 to 32.5°C; Humidity: 30 to 70% RH Temperature: -20 to 40°C; Humidity: 10 to 80% RH		762 x 593 x 511 mm 33.80 kg
Printer weight Package weight Operating environment Storage conditions Acoustics	21.6 kg 27.2 kg Temperature: 10 to 32.5°C; Humidity: 30 to 70% RH Temperature: -20 to 40°C; Humidity: 10 to 80% RH Acoustic power emissions: 6.9 B(A); Acoustic pressure		762 x 593 x 511 mm 33.80 kg Acoustic power emissions: 6 9 B(A); Acoustic pressure emissions: 54 dB(A)
Printer weight Package weight Operating environment Storage conditions Acoustics Power <sup>4</sup>	21.6 kg 27.2 kg Temperature: 10 to 32.5°C; Humidity: 30 to 70% RH Temperature: -20 to 40°C; Humidity: 10 to 80% RH Acoustic power emissions: 6.9 B(A); Acoustic pressure	e <b>emissions</b> : 55 dB(A) 98V, Max 264V); 50 - 60Hz nominal +/- 3Hz (min 47Hz ), 3.1 watts (sleep), < 0,1 watts (Auto Off/Manual On), /week, BA: 2.425 kWh/week;	762 x 593 x 511 mm 33.80 kg Acoustic power emissions: 6 9 B(A); Acoustic pressure emissions: 54 dB(A)
Printer weight Package weight Operating environment Storage conditions Acoustics	21.6 kg 27.2 kg Temperature: 10 to 32.5°C; Humidity: 30 to 70% RH Temperature: -20 to 40°C; Humidity: 10 to 80% RH Acoustic power emissions: 6.9 B(A); Acoustic pressure Requirements: 220V - 240V nominal; +/-10% (min 1 Consumption: 780 watts (printing), 15.3 watts (ready Typical Electricity Consumption (TEC) <sup>5</sup> : ES: 2.622 kW Power supply type: Built in 220V Power Supply; HP Auto-On/Auto-Off Technology; Instant-on Technol	98V, Max 264V); 50 - 60Hz nominal +/- 3Hz (min 47Hz ), 3.1 watts (sleep), < 0.1 watts (Auto Off/Manual On), · /week, BA: 2.425 kWh/week;	762 x 593 x 511 mm 33.80 kg Acoustic power emissions: 6 9 B(A); Acoustic pressure emissions: 54 dB(A)
Printer weight Package weight Operating environment Storage conditions Acoustics Power <sup>4</sup> Energy savings feature	21.6 kg 27.2 kg Temperature: 10 to 32.5°C; Humidity: 30 to 70% RH Temperature: -20 to 40°C; Humidity: 10 to 80% RH Acoustic power emissions: 6.9 B(A); Acoustic pressure Requirements: 220V - 240V nominal; +/-10% (min 13 Consumption: 780 watts (printing), 15.3 watts (ready Typical Electricity Consumption (TEO): E5: 2.622 kWF Power supply type: Built in 220V Power Supply;	98V, Max 264V); 50 - 60Hz nominal +/- 3Hz (min 47Hz ), 3.1 watts (sleep), < 0.1 watts (Auto Off/Manual On), · /week, BA: 2.425 kWh/week;	762 x 593 x 511 mm 33.80 kg Acoustic power emissions: 6.9 B(A); Acoustic pressure emissions: 54 dB(A) max 63H2, 6 A; 0.1 watts (Manual Off); 0.1 watts (Manual Off); 0.10 (EU) - Class A, EN 61000-3-2:2006 +A1:2009 (Directive 2004/108/EC: Other EMC approvals as
Printer weight Package weight Operating environment Storage conditions Acoustics Power <sup>4</sup> Energy savings feature technology	21.6 kg 27.2 kg <b>Temperature:</b> 10 to 32.5°C; <b>Humidity:</b> 30 to 70% RH <b>Temperature:</b> -20 to 40°C; <b>Humidity:</b> 10 to 80% RH <b>Acoustic power emissions:</b> 6.9 B(A); <b>Acoustic pressure</b> <b>Requirements:</b> 220V - 240V nominal; +/-10% (min 12 <b>Consumption:</b> 780 watts (printing), 1,53 watts (ready <b>Typical Electricity Consumption (TEC)</b> <sup>5</sup> : ES: 2.622 kWF <b>Power supply type:</b> Built in 220V Power Supply; HP Auto-On/Auto-Off Technology; Instant-on Technol CISPR 22:2008 (International) - Class A, EN 55022:21016 (EU) - Class A, EN 61000-3-3:2008, EN 55022:2016 (EU) - Class A, EN 61000-3-3:2008, EN 55022:2008 (International) - Class A, EN 55022:2016 (EU) - Class A, EN 61000-3-3:2008, EN 5502:2016 (EU) - Class A, EN 5502 - Class A, EN 5502:2016 (EU) - Class A, EN 5502 - Class A,	98V, Max 264V); 50 - 60Hz nominal +/- 3Hz (min 47Hz ), 3.1 watts (sleep), < 0,1 watts (Auto Off/Manual On), //week, BA: 2.425 kWh/week; logy CISPR 22:2008 (International) - Class A, EN 55022:21 + 42:2009 EN 61000-3-3:2008 EN 55024:2010 EM	762 x 593 x 511 mm         33.80 kg         Acoustic power emissions: 6.9 B(A); Acoustic pressure emissions: 54 dB(A)         max 63Hz), 6 A;         0.1 watts (Manual Off);         010 (EU) - Class A, EN 61000-3-2:2006 +A1:2009         IC Directive 2004/108/EC; Other EMC approvals as         (#AAZ, #201 options only)         nly ensured when using Original HP supplies         HP Laser Jet Enterprise M608x Printer; HP Black         Original Laser Jet Toner Cartridge (11,000 yield); CD with software drivers and documentation; Documentation (hardware install guide); Power cord

#### Footnotes

<sup>1</sup> Based on HP review of 2016 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit hp.com/go/PrintersThatProtect. For more information: http://www.hp.com/go/printersecurityclaims.

<sup>2</sup> HP Web Jetadmin is available for download at no additional charge at http://www.hp.com/go/webjetadmin.

<sup>3</sup> Measured after 15 min in sleep. Exact speed varies depending on the system configuration, software application, driver, document complexity and time in sleep.

<sup>4</sup> Based on HP testing using the ENERGY STAR<sup>®</sup> programme's Typical Electricity Consumption (TEC) method or as reported in energystar.gov versus the top three leading competitors as of 8/2015. Actual results may vary. For details see http://www.hp.com/go/Ljclaims.

<sup>5</sup> More pages versus predecessor cartridges claim based on page-yield comparison of HP 37X High Yield Black Original LaserJet Toner Cartridges with HP 87X High Yield Black Original LaserJet Toner Cartridges. For more information, see hp.com/go/learnaboutsupplies.

<sup>6</sup> HP 37X High Yield Black Original Laser Jet Toner Cartridges not included; please purchase separately.

#### Technical specifications disclaimers

<sup>1</sup> Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

<sup>2</sup> Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

<sup>3</sup> May require a firmware upgrade to be compatible, download at http://www.hp.com/go/support

<sup>4</sup> Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty.

<sup>5</sup> Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115 V device.

<sup>6</sup> EPEAT<sup>®</sup> registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.

<sup>7</sup> Cartridges included, yields 11,000 black pages based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/learnaboutsupplies







#### http://www.hp.com/uk

The product could differ from the images shown. © Copyright 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Published in EMEA 4AAG-9825, July 2019

