

SCANTEAM® 6901 Multiple Track Magnetic Stripe Card Reader

The SCANTEAM® 6901 Series magnetic stripe card readers are multiple track magnetic stripe readers used with Hand Held Products' ST8300/8400 check readers or ST2000/2010 Series point of sale interface decoders. Its compact design and velcro mounting pads provide easy, unobtrusive mounting. When combined with Hand Held Products' check reader and decoder products, automatic credit card data capture is provided to most POS terminals.

The SCANTEAM® 6901 Series provides the addition of credit card data capture to leading POS systems. The 6901 Series products are available to read combinations of Tracks 1, 2, and 3. When an MSR 6901 is connected to a Hand Held Products interface decoder or check reader, the data from tracks 1 or 2 and/or 3 can be edited and formatted to exactly match the terminal program requirements as well as any mandated formats by credit card companies. The SCANTEAM 6901 Series MSR's may also be used to read membership ID cards, access cards, time and attendance cards, and driver's licenses which contain magnetic stripe data.

Features & Benefits

Multiple Track Capability

ST6901 Series product are available to read combinations of tracks 1, 2, and 3.

High Scan Speed

Provides fast magnetic stripe data capture, improving salesperson productivity in cash wrap and check stand environments. Increases customer satisfaction.

Compact Design

Fits neatly in any sales area.

Compatibility

All existing credit cards and proprietary cards that adhere to ANSIx 4.16-1983 or ISO/IEC 7813: 1990(E).

High Coercivity (Hi-Co) and Low Coercivity (Lo-Co) magnetic stripe cards.

SCANTEAM® 6901

Performance

Recording Method: Two-frequency coherent phase (F2F), high or low coercivity magnetic media, compatible with ISO 3554.

Swipe Speed: Card speed through unit may vary from 5 to 50 inches per second (127 to 1270 mm/sec) for track two data encoded at

75 bpi, or for track one or track three data encoded at 210 bpi. Tolerates ±12% jitter encoded in card.

Model

COMPATIBILITY AND PRODUCT CONFIGURATION

Compatible HHP

RJ45

RJ45

Connector Type

Decoders

ST8300/8400 ST2000/2010

ST8300/8400 ST2000/2010

Tracks Read

6901/B Tracks 1 & 2

6901/D Tracks 1, 2, & 3

Life: 300,000 passes. Longer life version available. Consult factory.

Mechanical/Electrical

Dimensions

Weight: 3 oz. (86g) with cord Length: 3.94 in. (100mm) Height: 1.17 in. (28mm) Width: 1.34 in. (34mm)

Case Color: Beige

Cord Length: 20 in. (50.8cm) Cord Exit Path: Case Bottom

Cord Color: Beige

Power Requirements

Voltage: 5V+5% at 2.5mA (dual track)

5V± 5% at 4.2mA (triple track)

Output Signal Levels: Vol-0.4 volts at 2mA

Voh-4.5 volts at 0.2mA

Connector: 8 pin modular, RJ45

Mounting: Unit may be mounted by screws using threaded inserts in the case, or by using the velcro mounting kit (included).

Environmental

Temperature

Operating: 50°F to 104°F (-10°C to 40°C)

Humidity: 10% to 90% humidity

Agency Conformance: Complies with FCC Class A.

CE: The system has been tested to and conforms with the provisions within 89/336/EEC, Electromagnetic Compatibility

directive (EMC)

Complies with EMC 89/336/EEC

Worldwide Offices

Offices Serving North America Skaneateles Falls, NY

Tel: +1 315 685 8945 or, in North America: +1 800 782 4263 sales@hhp.com

Charlotte, NC Tel: +1 704 998 3998 or, in North America: +1 800 782 4263

sales@hhp.com

euro sales@hhp.com Ireland Tel: +353 (0) 502 44007 euro_sales@hhp.com

Offices Serving Europe Middle East, and Africa

Tel: +31 (0) 40 29 01 600

Tel: +44 (0) 1 925 240055

euro_sales@hhp.com

United Kingdom

France

Tel: +33 (0) 1 461 04111 euro_sales@hhp.com Germany Tel: +49 (0) 7 477 151377 euro_sales@hhp.com

Spain Tel: +34 93 228 76 68

euro_sales@hhp.com

Offices Serving Asia and the Pacific Rim

Hong Kong Tel: +852 2511 3050/2511 3132 asia sales@hhp.com Tel: +813 52127392

asia sales@hhp.com

Offices Serving Latin America Naples, Florida

Tel: +1 239 263 7600 la-sales@hhp.com S,, o Paulo Tel: +55 11 5016 3454 la-sales@hhp.com Rio De Janiero Tel: +55 21 2494 7060 la-sales@hhp.com

Web Site Address www.hhp.com

Hand Held Products, Inc. d/b/a HHP (iHHPî) a1999-2002. All rights reserved. Printed in the U.S.A.

Europe

Due to HHPIs continuing product improvement programs, specifications and features herein are subject to change without notice.