



## HRNC1 Wireless Video Camera Specifications

### Network Specifications:

- IEEE 802.11b/g standards
- 100T Base-TX Fast Ethernet

### Camera Specifications:

- Max. Resolution: 640 x 480 pixels
- Image Sensor: 1/4" color CMOS sensor
- Gain control: Automatic
- Exposure: Automatic
- White Balance: Automatic
- Aperture: F=1.8
- Focal Length: 6.0mm

### Video Settings:

- Supported Stream: Motion Jpeg; Jpeg for still images
- Frame Rate: 30+ FPS @ 160 x 120 (QCIF) / 30FPS @ 320 x 240 (CIF) / 10FPS @ 640 x 480 (VGA)
- Cell Link\* Frame Rate: 1 – 10 FPS (Depending on cellular broadband network and mobile phone model/screen size)
- Adjustable Image Size (Cell Link and Web Browser viewing modes)
- Configurable Motion Detection (HomeRemote Gateway independent feature)

### Hardware Interface:

- LAN Port: 1 RJ-45, 10/100M Auto-Sensed
- One RP-SMA Antenna Connector (2.4GHz Wi-Fi)
- External Power Supply Connector
- LEDs: Power and Link Indicator, LAN and WLAN Indicators
- Reset Button

### HTTP/Utility:

- Administrator Utility software application
- Viewer/Recorder Utility Software Application (Supports 4 cameras simultaneously)
- Manual/Scheduled/Motion – Triggered Recroding
- Video Playback/Stop/Forward/Pause
- Web Management Interface
- HomeRemote Software Setup Wizard (HomeRemote Gateway Room Assignment and Naming)
- HomeRemote Cell Link Compatible Setup (Live streaming video to Cell Link compatible mobile phone)

### Dimensions:

- 4.13" x 4.13" x 4.92" (L x W x H)

### Operating Environment:

- Temperature: 0 – 40 C / 32 – 104 F

### Certifications:

- FCC, CE
- UPC: 603992-506552
- Warranty: 1 Year

\* The HomeRemote Cell Link feature is a subscription based service from Hawking Technologies / HomeRemote that enables cellular phone based control of Z-Wave lighting and appliances and viewing of live video through the HomeRemote HRGZ1 Gateway.  
- Setup of the HRNC1 requires that you MUST have a HRGZ1 pre-configured on your network.