

# *IMAGETEAM*<sup>™</sup> *4710HD/HD10 Fixed Mount 2D Image Reader*



### **Features**

2D Image Reader - Hand held or fixed mount image reader for reading and decoding 2D symbologies, and capturing images.

Supports All Popular 2D Symbologies - Fixed mount IT4710 supports all popular matrix and stacked linear symbologies: MaxiCode, Aztec, Aztec Mesa, Data Matrix, PDF417, QR, and MicroPDF417.

Fixed Position Reader - Opens up new 2D bar code and image capture possibilities for fixed scanning applications.

Omni-Directional Scanning - The video technology offers omni-directional scanning, even on linear codes, greatly simplifying operator training and increasing productivity.

Aiming - The IT4710 has a bright, intuitive aiming line.

Autodiscriminates Between Supported Symbologies and Fonts - Reads all major linear, stacked linear, and matrix bar codes as well as machine readable fonts used in Optical Character Recognition (OCR).

2D Print Quality Assessment (PQA) - An easy and inexpensive approach to providing test results useful for 2D bar code symbol process control, and improvement of the overall 2D data acquisition system. The HHP IMAGETEAM<sup>™</sup> (IT) 4710 Image Reader can be configured as either a hand held or fixed mount device that reads matrix, stacked linear and conventional linear bar codes, as well as a single line of OCR-A and OCR-B fonts. Multi-line OCR applications can also be read. The IT4710 has the power to capture and download images to a PC for applications that include signature capture, PC-based decoding, and image lift requirements.

The IT4710 Reader can be used in retail, transportation, packaging, printed circuit board manufacturing, electronic component manufacturing, and clinical/ diagnostic applications that include test tube and reagent package labels.

The IT4710 can be configured for keyboard wedge, HHLC (Code 128 emulation), TTL, or True RS-232. The IT4710 connects to all popular PCs and portable data terminals. HHLC mode can be used with external wedge decoders and portable terminals or other devices without 2D decoding capability.

The IT4710 features integrated processing for a onepiece scanning solution -- no additional boxes or electronics needed. The reader provides omnidirectional and auto-discrimination decoding for symbologies, such as MaxiCode, PDF417, QR, Data Matrix, Aztec code, RSS code, composite codes, postal codes, Code 39, Code 93, Interleaved 2 of 5, Codabar, Code 128, UPC, and EAN. Additional symbologies will be added based on market demand.

Because the IT4710 is a fixed focus device, four product models with different focal points are available. Two high density scanners are available: IT4710HD and IT4710HD10. The IT4710HD, with a focal point of 2 inches, is recommended when the matrix symbols are less than 10 mil. The IT4710HD10 is recommended for applications when the matrix codes are greater than 10 mil. This version, with a focal point of 3 inches, maximizes the depth of field on 10 mil matrix codes, which directly correlates to greater functionality by the end user. The long range (LR/LX) models of the IT4710 are highlighted in separate data sheets.

To learn how the IT4710HD or IT4710HD10 can work for you, contact us at any of the locations listed on the back or visit us at **www.hhp.com**.

Upgrade your image.

# IMAGETEAM<sup>™</sup> 4710HD/HD10 Specifications

6.6 mil QR

<u>(.017 cm)</u>

1.7 in. (4.3 cm)

2.45 in. (6.2 cm)

#### Performance

Near

(typical)

Near Far

Far

HD Focal Point: HD10 Focal Point:

HD10 Working Range:

**Rotational Sensitivity:** Viewing Angle:

Ambient Light:

HD Working Range: (typical)

3 inches from nose 6 pt OCR <u>20 cpi</u> 2 in. (5.1 cm)

3.5 in. (8.9 cm)

10 mil QR

(.025 cm)

360°

2 inches from nose

10 mil Data Matrix <u>(.025 cm)</u> 2.0 in. (5.1 cm) 2.2 in. (5.6 cm) 4.0 in. (10.2 cm) 3.8 in. (9.6 cm)

5 mil Linear (.013 cm) 2.75 in. (7.0 cm) 3.75 in. (9.5 cm)

6.6 mil Data Matrix 4 mil Linear

(.01 cm)

1.6 in. (4.6 cm)

2.7 in. (6.9 cm)

(.017 cm)

1.7 in. (4.3 cm)

2.45 in. (6.2 cm)

<u>+</u>45° Total darkness to 100,000 lux (full sunlight) 660nm LEDs provide bright aiming line

### Aiming: **Symbologies**

/	
2 Dimensional:	MaxiCode, PDF417, MicroPDF417, Aztec, Aztec Mesa, Data Matrix, QR Code, Code 49, UCC Composite, Snowflake*, Vericode*, Dataolyphs*
Linear:	Code 39, Code 128, Codabar, UPC, EAN, I 2 of 5, RSS, BC 412*, Code 93, Codablock * available to licensed users only
Postal:	Postnet (US), BPO4 State, Canadian 4 State, Japanese Post, KIX (Dutch Post), Planet Code
OCR Fonts:	OCR-A, OCR-B
Interfaces:	RS232, Wedge, and HHLC (Code 128 Emulation)
Programmable Options:	Baud, Parity, Data Formatting, Code Options

#### Mechanical/Electrical

Dimensions		
Length:	4.85 in. (12.3 cm)	
Height	1.85 in. (4.7 cm)	
Width:	2.50 in. (6.35 cm)	
Weight w/o cord:	5.5 oz. (156 g) or less	
Power Requirements:	4 to 9 volts	
Current Draw:	Low Power Mode - average @ 5 VDC-40mA Medium Power Mode - average @ 5 VDC-125mA High Power Mode - average @ 5 VDC-175mA	
Standby Current:	< 200µA @ 5V	
Environmental		
Temperature Operating: Storage:	-0°C to 50°C -40°C to +70°C	
Humidity:	95% RH, non condensing at 50°C	
Shock:	10 drops 5 ft. to concrete @ room temperature	
ESD:	Functional after 15KV discharge	
Agency:	FCC Class B, CE	



Complies with EMC 89/336/EEC and LVD 73/23/EEC

#### Worldwide Offices

Contraction of the contract of sales@hhp.com

## Offices Serving Europe, Middle East, and Africa

*Europe* Tel: +31 (0) 40 29 01 600 euro\_sales@hhp.com United Kingdom Tel: +44 (0) 1 925 240055 euro\_sales@hhp.com Ireland Tel: +353 (0) 502 44007 euro\_sales@hhp.com

France Tel: +33 (0) 1 461 04111 euro\_sales@hhp.com Germany Tel: +49 (0) 7 477 151377 euro\_sales@hhp.com Spain Tel: +34 93 228 76 68 euro\_sales@hhp.com

Offices Serving Asia and the Pacific Rim Hong Kong Tel: +852 2511 3050/2511 3132 asia\_sales@hhp.com Janan Japan Tel: +813 52127392 asia\_sales@hhp.com

# Offices Serving Latin America Naples, Florida Tel: +1 239 263 7600 la-sales@hhp.com São Paulo Tel: +55 11 5016 3454 la-sales@hhp.com Rio De Janiero Tel: +55 21 2494 7060 la-sales@hhp.com

Web Site Address www.hhp.com Hand Held Products, Inc. d/b/a HHP ("HHP") <sup>©</sup>1999-2002. All rights reserved. Printed in the U.S.A. Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.