

# Duratran II Paper Label

Thermal Transfer Paper



- Duratran II labels provide high-quality, cost-effective printing for general use applications
- Compatible with TMX1500 and TMX2200 ribbons
- Offered with a variety of adhesive options
- Take From Stock labels available in an assortment of colors

## Duratran II Paper Label

Intermec's Duratran II paper label is a coated, thermal transfer paper label that exhibits excellent print quality when paired with the TMX1500 and TMX2200 ribbons. Duratran II paper labels are offered with a variety of adhesive options and are recommended when moderate abrasion, heat, or sunlight is present. Stock Duratran II products offer a robust general-purpose permanent adhesive that is excellent for use on corrugated containers, plastics, and many other common substrates. Special adhesives are available with custom orders. This label stock is ideally suited for applications such as:

- Shipping label
- Inventory tracking label
- Work-in-process
- Receiving label
- Bin labeling
- General purpose labeling

### Better Together

The Intermec media solution has added advantages when paired with Intermec printers:

- Co-engineered printers and media ensure consistent print quality and performance
- Thermal transfer printability allows on-demand generation of durable labels, eliminating high cost and inventory obsolescence associated with preprinting
- When Intermec media is used exclusively with Intermec printers, the Free Printhead Replacement Program offers significant cost savings

## Product Characteristics:

### Face Stock

**Description:** Coated Paper Label  
**Physical Attributes:** 2.6 - 3.2 mils

### Adhesive

**Description:** Acrylic Permanent  
**Caliper:** 0.4 - 0.6 mil  
**Peel Adhesion (90° Stainless Steel):** 33.0 target

### Liner

**Description:** 42# white kraft  
**Physical Attributes:** 2.3 - 2.8 mils

### Ribbon Compatibility

TMX1500  
TMX2200

**Outdoor Use:** Not recommended for outdoor use

### Environment

**Storage Temperature:** 40°F to 80°F  
**Storage Humidity:** 35% to 70%  
**Shelf Life:** 12 months  
**Minimum Application Temperature:** 25°F  
**Service Temperature:** -65°F to 200°F

### North America

**Corporate Headquarters**  
6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348-2600  
Fax: (425) 355-9551

### Intermec Deutschland

Burgunder Strasse 31  
40549 Düsseldorf  
Germany  
Phone: 0049 211 53601-0  
Fax: 0049 211 53601-50  
Email: [germany.marketing@intermec.com](mailto:germany.marketing@intermec.com)  
Web: [www.intermec.de](http://www.intermec.de)

### South America & Mexico

**Headquarters Office**  
Newport Beach, California  
Phone: (949) 955-0785  
Fax: (949) 756-8782

### Europe/Middle East & Africa

**Headquarters Office**  
Reading, United Kingdom  
Phone: +44 118 923 0800  
Fax: +44 118 923 0801

### Asia Pacific

**Headquarters Office**  
Singapore  
Phone: +65 6303 2100  
Fax: +65 6303 2199

### Internet

[www.intermec.com](http://www.intermec.com)  
Worldwide Locations:  
[www.intermec.com/locations](http://www.intermec.com/locations)

### Sales

Toll Free NA: (800) 934-3163  
Toll in NA: (425) 348-2726  
Freephone ROW: 00 800 4488 8844  
Toll ROW: +44 134 435 0296

### OEM Sales

Phone: (425) 348-2762

### Media Sales

Phone: (513) 874-5882

### Customer Service and Support

Toll Free NA: (800) 755-5505  
Toll in NA: (425) 356-1799

Copyright © 2008 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611841-A 09/07

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

