

INFINEA® OMNI

©2015 Infinite Peripherals, Inc.

General Specifications

Mobilize The self-helper. All the information your customer seeks without having to look for it. From price Your checking in stores to checking in at airports, the Infinea Omni reimagines what—and where—a kiosk Enterprise[™] can be. For Apple® iPad Air®. Mobility Sales/ Office (949) 222-0300 Headquarters/ Office (847) 818-1260 Technical Support Center Main Warehouse Fax (847) 818-1287 Fax (949) 222-0375 Toll-Free (800) 278-7860 1641 McGaw Avenue Toll-Free (866) 278-7860 2312 Touhy Avenue Elk Grove Village, IL 60007 Email info@ipcprint.com Irvine, CA 92614 Email info@ipcprint.com Standard Features Lightning™ Connector 1D/2D Barcode Reader ipcprint.com



INFINEA OMNI

MECHANICAL		ENVIRONMENT	
Compatability	iPad Air®		-
Dimensions	283 mm (L) x 225 mm (W) x 84 mm (H)	Operating Environment	Temperature: 10°C to 40°C 50°F to 104°F Humidity: 5 to 90% RH
Weight	1250 grams (44.1 oz) without iPad Air®		
ELECTRICAL		Storage Environment	Temperature: -20°C to 50°C -4°F to 122°F Humidity: 5 to 90% RH
Input Power	PoE class 0, IEEE802.3af compliant, RJ-45, Cat5e, 36V to 57V input, 5V 2.4A max output	CERTIFICATIONS	
Barcode Scanner	2D high speed imager, supports all major 1D or 2D barcodes	North America	UL, CE, FCC, RoHS, RCM
Buttons	- Home Button - Scanner Hardware Reset Button	Part Number IO-O2D-A-XX, 10-O2O-A-SW-XX	
LEDs	Green LED indicates that there is PoE power to the RJ-45 connector panel.		
	$\langle \rangle$	11	